



CERTIFICATE OF CALIBRATION

Ricardo Energy & Environment 18 Blythswood Square, Glasgow, G2 4BG

Telephone 01235 753434



Page 1 of 3

Approved Signatories:		S. Eaton D Hector N Rand B Davies	☐ B Stacey ☐ S Stratton ☑ S Telfer ☐ S Gray				
Signed:	Stelki						
	2 July 2021	1					
Certificate Number: 5	477						
Customer Name and Address:	Water, A	gh					
Description:		Calibration factors for the air monitoring station(s) at Clackmannanshire Council					
Ricardo Energy & Environment ID:	ED1119	4/5477					
The reported expanded uncertainties are based on a sta level of confidence of approximately 95% The uncertain requirements. This certificate is issued in accordance with the laborato Service. It provides traceability of measurement to the S National Physical Laboratory or other recognised nation than in full, except with the prior written approval of the	ty evaluation has been carried or some carried	out in accordance with UKAS of the United Kingdom Accredit ts of measurement realised at tl	ration he				
Ricardo Energy & Environment 18 Blythswood Square (2 nd Floor), Glasgow, G2 4BG Tel: 01235 753205	Registered office Shoreham Technical Centre Shoreham-by-Sea West Sussex BH43 5FG Registered in England No. 08229264 VAT Registration No. GB 212 8365 24						

ee.**ricardo**.com



CERTIFICATE OF CALIBRATION



Page 2 of 3

Date of issue: 02 July 2021

Certificate Number: 5477

Ricardo Energy & Environment ID: ED11194/5477

Clackmannanshire Council

NOx analysers

Station	Date of Audit	Species	Analyser Serial no	Zero Response ¹	Zero uncertainty ppb	Calibration Factor ²	Factor uncertainty %	Converter eff. (%) ³
Alloa A907	09 June 2021	NOx	1502764112	0.1	2.6	1.0580	3.50	98.4
		NO		-0.1	2.5	1.0624	3.50	

FIDAS analysers

O			Analyser	Calculated	Uncertainty	Uncertainty		Uncertainty	
Station	Station	Date of audit				Total flow⁴		Main flow	%
All	loa A907	09 June 2021	8790			4.81	2.2		2.2

ee.**ricardo**.com



CERTIFICATE OF CALIBRATION



Page 3 of 3

Date of issue:

02 July 2021

Certificate Number:

5477

Ricardo Energy & Environment ID:

ED11194/5477

The gaseous ambient analysers listed above have been tested for zero response, calibration factor, linearity and converter efficiency (NOx analysers) by documented methods. The factors have been calculated using certified gas standards. The particulate analysers listed above have been tested for sample flow rates and ko(where appropriate) by documented methods. Note that the test results are valid on the day of test only, as analyser drift over time cannot be quantified. All results for gaseous species are given in ppb (parts per billion) mole fractions or ppm (parts per million) mole fractions.

Concentration = F(Output - Zero Response)

Where F = Calibration Factor provided on this certificate

Output = Reading on the data logging system of the analyser

Zero Response = Zero Response provided on this certificate

The calibration results shaded are those that fall within our scope of accreditation, all other results on this certificate are not UKAS accredited, but have been included for completeness.

ee.ricardo.com

¹ The zero response is the zero reading on the data logging system of the analyser when audit zero gas was introduced to the analysers under test.

² The calibration factor is the multiplying factor required to scale the reading on the data logging system of the analyser into reported concentration units (ppb for NO, NOx, SO₂, O₃ and ppm for CO. Where 1ppm = 1000ppb). It should be used in conjunction with the zero response. A corrected concentration is calculated using the following equation:

³ Converter eff. is the measured efficiency of the NO₂ to NO converter within the oxides of nitrogen analyser under test.

⁴ The measured main flow rate (where this is applicable) is the flow rate through the sensor unit of the TEOM particulate analyser under test. The measured total flow rate is the total flow rate through the particulate analyser under test. Units of flow are l.min⁻¹, reported at prevailing ambient conditions unless otherwise specified. Where flow rates are highlighted in bold, it indicates that measurements were not made at the analyser sample inlet. These measurements therefore may not accurately reflect analyser performance in normal operation.

⁵ The calculated ko value (specifically for TEOM analysers) is the calculated ko spring constant based on tests undertaken with filters of known weight. The % deviation indicates the closeness of the calculated result to the manufacturer's specified value of ko.