	IFICATE OF CALIBRATION & Environment 18 Blythswood Square, Glasgow, G2 4 Telephone 01235 753434	
		Page 1 of 3
Approved Signatories:	 S. Eat D Hec N Ran B Dav 	tor 🗌 S Stratton d 🤄 S Telfer
C'and	Stelfer	
Signed:		
	27 July 2022	
Certificate Number:	5932	
Customer Name and Address:	Scottish Governme Water, Air, Soils au Environmental Qua Scottish Governme Victoria Quay Edinburgh EH6 6QQ	nd Flooding Division ality Directorate
Description:	Calibration factors Dundee City Cound	for the air monitoring station(s) at il
Ricardo Energy & Environment ID:	ED11194/5932	
The reported expanded uncertainties are based on a st level of confidence of approximately 95% The uncertain requirements. This certificate is issued in accordance with the laborat Service. It provides traceability of measurement to the National Physical Laboratory or other recognised natio than in full, except with the prior written approval of th	ty evaluation has been carried out in accordance ory accreditation requirements of the United Kin Sysstem of units and/or to units of measureme nal metrology institutes. This certificate may not	gdom Accreditation nt realised at the
Ricardo Energy & Environment 18 Blythswood Square (2 nd Floor), Glasgow, G2 4BG Tel: 01235 753205	Registered office Shoreham Technical Centre Shoreham-by-Sea West Sussex BN43 5FG Registered in England No. 08228264 VAT Registration No. GB 212 8365 24	
		ee. ricardo. com



CERTIFICATE OF CALIBRATION



Page 2 of 3

Date of issue:	27 July 2022	Tage 2 (
Certificate Number:	5932	
Ricardo Energy & Environment ID:	ED11194/5932	

Dundee City Council NOx analysers

Station	Date of Audit	Species	Analyser Serial no	Zero Response ¹	Zero uncertainty ppb	Calibration Factor ²	Factor uncertainty %	Converter eff. (%) ³
Dundee Broughty Ferry Road	20-Jun	NOx	607	2.9	2.6	1.2656	3.50	100.0
		NO		2.0	2.6	1.2597	3.50	
Dundee Lochee Road	21-Jun	NOx	727	5.2	2.6	1.0589	3.65	98.4
		NO		4.0	2.6	1.0713	3.50	
Dundee Meadowside	21-Jun	NOx	20-1728	-1.0	2.6	0.9743	3.57	100.0
		NO		0.0	2.5	0.9743	3.50	
Dundee Seagate	22-Jun	NOx	726	7.0	2.6	1.2281	3.63	100.0
		NO		4.5	2.6	1.2479	3.50	
Dundee Whitehall Street	21-Jun	NOx	725	9.0	2.7	1.3162	3.68	95.3
		NO		7.5	2.7	1.3011	3.50	

Fidas analysers

Station	Date of audit	Analyser Serial no	Calculated ko⁵	Uncertainty %	Total flow ^₄	Uncertainty %	Main flow	Uncertainty %
Dundee Broughty Ferry Road	20-Jun	11911			4.81	2.2		2.2
Dundee Lochee Road	21-Jun	8732			4.68	2.2		2.2
Dundee Mains Loan	20-Jun	8379			4.94	2.2		2.2
Dundee Meadowside	21-Jun	10883			4.95	2.2		2.2
Dundee Seagate	22-Jun	10881			4.62	2.2		2.2
Dundee Whitehall Street	21-Jun	10882			4.73	2.2		2.2

ee.**ricardo**.com



CERTIFICATE OF CALIBRATION



Page 3 of 3

Date of issue:	27 July 2022
Certificate Number:	5932
Ricardo Energy & Environment ID:	ED11194/5932

The gaseous ambient analysers listed above have been tested for zero response, calibration factor, linearity and converter efficiency (NOx analysers) by documented methods. The factors have been calculated using certified gas standards. The particulate analysers listed above have been tested for sample flow rates and ko(where appropriate) by documented methods. Note that the test results are valid on the day of test only, as analyser drift over time cannot be quantified. All results for gaseous species are given in ppb (parts per billion) mole fractions or ppm (parts per million) mole fractions.

¹ The zero response is the zero reading on the data logging system of the analyser when audit zero gas was introduced to the analysers under test.

² The calibration factor is the multiplying factor required to scale the reading on the data logging system of the analyser into reported concentration units (ppb for NO, NOx, SO₂, O₃ and ppm for CO. Where 1ppm = 1000ppb). It should be used in conjunction with the zero response. A corrected concentration is calculated using the following equation:

Concentration = F(Output - Zero Response)

Where F = Calibration Factor provided on this certificate Output = Reading on the data logging system of the analyser

Zero Response = Zero Response provided on this certificate

³ Converter eff. is the measured efficiency of the NO₂ to NO converter within the oxides of nitrogen analyser under test.

⁴ The measured main flow rate (where this is applicable) is the flow rate through the sensor unit of the TEOM particulate analyser under test. The measured total flow rate is the total flow rate through the particulate analyser under test. Units of flow are l.min⁻¹, reported at prevailing ambient conditions unless otherwise specified. Where flow rates are highlighted in bold, it indicates that measurements were not made at the analyser sample inlet. These measurements therefore may not accurately reflect analyser performance in normal operation.

⁵ The calculated ko value (specifically for TEOM analysers) is the calculated ko spring constant based on tests undertaken with filters of known weight. The % deviation indicates the closeness of the calculated result to the manufacturer's specified value of ko.

The calibration results shaded are those that fall within our scope of accreditation, all other results on this certificate are not UKAS accredited, but have been included for completeness.

ee.ricardo.com