



CERTIFICATE OF CALIBRATION

Ricardo Energy & Environment 18 Blythswood Square, Glasgow, G2 4BG





Page 1 of 3

Approved Signatories:		S. Eaton D Hector N Rand B Davies	□ B Stacey□ S Stratton☑ S Telfer□ S Gray			
Signed:	Stelke					
Date of issue:	27 July 2022					
Certificate Number:	5934					
Customer Name and Address:		Scottish Government Water, Air, Soils and Flooding Divisior Environmental Quality Directorate Scottish Government Victoria Quay Edinburgh EH6 6QQ	n			
Description:		Calibration factors for the air mor East Dunbartonshire Council	nitoring station(s) at			
Ricardo Energy & Environment ID:		ED11194/5934				
The reported expanded uncertainties are based on a sta level of confidence of approximately 95% The uncertaint requirements. This certificate is issued in accordance with the laborato Service. It provides traceability of measurement to the S National Physical Laboratory or other recognised nation than in full, except with the prior written approval of the	ry evaluation has been ry accreditation requir I system of units and/ al metrology institutes	carried out in accordance with UKAS rements of the United Kingdom Accreditation or to units of measurement realised at the . This certificate may not be reproduced other				
Ricardo Energy & Environment 18 Blythswood Square (2 nd Floor), Glasgow, G2 4BG Tel: 01235 753205	Shoreham Technical Centre Shoreham Technical Centre Shoreham-by-Sea West Sussex BN43 5FG Registered in England No. 08229264 VAT Registration No. GB 212 8365 24					

ee.**ricardo**.com



CERTIFICATE OF CALIBRATION



Page 2 of 3

Date of issue: 27 July 2022

Certificate Number: 5934

Ricardo Energy & Environment ID: ED11194/5934

East Dunbartonshire Council

NOx analysers

dit	dit Specie	Analyser Serial no	Zero Response ¹	Zero uncertainty ppb	Calibration Factor ²	Factor uncertainty %	Converter eff. (%) ³
2	2 NOx	YEPTA800	-0.1	2.5	1.0002	3.61	100.0
	NO		-0.5	2.7	1.0243	3.50	
2	2 NOx	B8BVW9XY	-2.3	2.6	0.9904	3.64	98.5
	NO		-0.1	2.6	1.0168	3.62	
2	2 NOx	CM07010003	0.0	2.5	1.0000	3.57	98.7
	NO		0.0	2.5	1.0000	3.50	
2	2 NOx	CM10020066	-26.7	2.6	1.0255	3.50	98.6
	NO		-25.5	2.6	1.0259	3.50	
2		CM10020066					

Fidas analysers

Station	Date of audit	Analyser Serial no	Calculated ko⁵	Uncertainty %	Total flow⁴	Uncertainty %	Main flow	Uncertainty %
East Dunbartonshire Bearsden	13 July 2022	10490			4.67	2.2		2.2
East Dunbartonshire Bishopbriggs	13 July 2022	10491			4.74	2.2		2.2
East Dunbartonshire Kirkintilloch	13 July 2022	8150			4.69	2.2		2.2
East Dunbartonshire Milngavie	14 July 2022	12500			4.77	2.2		2.2

ee.**ricardo**.com





CERTIFICATE OF CALIBRATION



Page 3 of 3

Date of issue: 27 July 2022

Certificate Number: 5934

Ricardo Energy & Environment ID: ED11194/5934

The gaseous ambient analysers listed above have been tested for zero response, calibration factor, linearity and converter efficiency (NOx analysers) by documented methods. The factors have been calculated using certified gas standards. The particulate analysers listed above have been tested for sample flow rates and ko(where appropriate) by documented methods. Note that the test results are valid on the day of test only, as analyser drift over time cannot be quantified. All results for gaseous species are given in ppb (parts per billion) mole fractions or ppm (parts per million) mole fractions.

Concentration = F(Output - Zero Response)

Where F = Calibration Factor provided on this certificate

Output = Reading on the data logging system of the analyser

Zero Response = Zero Response provided on this certificate

The calibration results shaded are those that fall within our scope of accreditation, all other results on this certificate are not UKAS accredited, but have been included for completeness.

ee.ricardo.com

¹ The zero response is the zero reading on the data logging system of the analyser when audit zero gas was introduced to the analysers under test.

² The calibration factor is the multiplying factor required to scale the reading on the data logging system of the analyser into reported concentration units (ppb for NO, NOx, SO2, O3 and ppm for CO. Where 1ppm = 1000ppb). It should be used in conjunction with the zero response. A corrected concentration is calculated using the following equation:

³ Converter eff. is the measured efficiency of the NO₂ to NO converter within the oxides of nitrogen analyser under test.

⁴ The measured main flow rate (where this is applicable) is the flow rate through the sensor unit of the TEOM particulate analyser under test. The measured total flow rate is the total flow rate through the particulate analyser under test. Units of flow are l.min⁻¹, reported at prevailing ambient conditions unless otherwise specified. Where flow rates are highlighted in bold, it indicates that measurements were not made at the analyser sample inlet. These measurements therefore may not accurately reflect analyser performance in normal operation.

⁵ The calculated ko value (specifically for TEOM analysers) is the calculated ko spring constant based on tests undertaken with filters of known weight. The % deviation indicates the closeness of the calculated result to the manufacturer's specified value of ko.