	Ricardo Energy &	FICATE OF CALIE Environment 18 Blythswood Sq Telephone 01235 753434		ARDO
				Page 1 of 3
Approved Signatories:			. Eaton Hector Rand Davies	 □ B Stacey □ S Stratton ☑ S Telfer □ S Gray
Signed:	Stelfer			
Date of issue: 14	4 January 2021			
Certificate Number: 52	268			
Customer Name and Address:		Scottish Governmen Water, Air, Soils an Environmental Qual Scottish Governmen Victoria Quay Edinburgh EH6 6QQ	d Flooding Division lity Directorate	
Description:		Calibration factors f Edinburgh City Cou	for the air monitoring and incil	station(s) at
Ricardo Energy & Environment ID:		ED11194/5268		
The reported expanded uncertainties are based on a standard uncertaint level of confidence of approximately 95% The uncertainty evaluation has requirements. This certificate is issued in accordance with the laboratory accreditation r Service. It provides traceability of measurement to the SI system of units. National Physical Laboratory or other recognised national metrology insti than in full, except with the prior written approval of the issuing laborato	been carried out in accor equirements of the Unite and/or to units of measu itutes. This certificate ma	rdance with UKAS ed Kingdom Accreditation urement realised at the		
Ricardo Energy & Environment 18 Blythswood Square (2 nd Floor), Glasgow, G2 4BG Tel: 01235 753205	Registered office Shoreham-Vs-Sea Shoreham-Vs-Sea West Sussex BN43 5FG Registered in England 08229264 VAT Registration No. GB 212 8365 24	I No.	. ricardo .com	



CERTIFICATE OF CALIBRATION



Page 2 of 3

Date of issue:

Certificate Number:

14 January 2021

5268

Ricardo Energy & Environment ID:

ED11194/5268

Edinburgh City Council NOx analysers

Station	Date of Audit	Species	Analyser Serial no	Zero Response ¹	Zero uncertainty ppb	Calibration Factor ²	Factor uncertainty %	Converter eff. (%) ³
Edinburgh Currie	09 December 2020	NOx	6232	-0.2	2.5	1.0081	3.50	98.2
		NO		0.2	2.5	1.0261	3.50	
Edinburgh Glasgow Road 09 December 2020	NOx	6234	-2.8	2.5	1.0134	3.84	99.2	
	NO		0.0	2.5	1.0227	3.82		
Edinburgh Gorgie Road 10 December 2020	NOx	601915008	-4.1	2.6	1.1114	3.50	9.5	
	NO		-2.9	2.6	1.1152	3.50		
Edinburgh Queensferry Road 10 December 2020	NOx	4180	2.7	2.6	1.1079	3.50	99.4	
	NO		1.8	2.6	1.1095	3.50		
Edinburgh Salamander St 08 December 2020	NOx	6233	-6.1	2.5	1.0517	3.63	101.0	
		NO		0.4	2.5	1.0597	3.98	
Edinburgh St John's Road	10 December 2020	NOx	5555	1.5	2.6	1.0830	3.50	98.2
		NO		0.2	2.6	1.0767	3.50	

PM10 analysers

Station	Date of audit	Analyser Serial no	Calculated ko ^s	Uncertainty %	Total flow ^₄	Uncertainty %	Main flow	Uncertainty %
Edinburgh Currie	09 December 2020	1200c203110903	11861	1.0	16.67	2.2	3.13	2.2
Edinburgh Glasgow Road	09 December 2020	1200c167410207	14257	1.0	16.10	2.2	3.04	2.2
Edinburgh Salamander Street	08 December 2020	1200b133769603	18210	1.0	16.48	2.2	2.99	2.2

Fidas analysers

Station	Date of audit	Analyser Serial no	Calculated ko⁵	Uncertainty %	Total flow ^₄	Uncertainty %	Main flow	Uncertainty %
Edinburgh Queensferry Road	10 December 2020	11391			4.51	2.2		2.2
Edinburgh St John's Road	10 December 2020	7749			4.54	2.2		2.2
Edinburgh Tower Street	07 December 2020	9635			4.46	2.2		2.2
Edinburgh Nicolson Street	18 January 2021	11955			4.65	2.2		2.2

ee.**ricardo**.com



CERTIFICATE OF CALIBRATION



Page 3 of 3

14 January 2021

5268

Date of issue:

.

Certificate Number:

Ricardo Energy & Environment ID:

ED11194/5268

The gaseous ambient analysers listed above have been tested for zero response, calibration factor, linearity and converter efficiency (NOx analysers) by documented methods. The factors have been calculated using certified gas standards. The particulate analysers listed above have been tested for sample flow rates and ko (where appropriate) by documented methods. Note that the test results are valid on the day of test only, as analyser drift over time cannot be quantified. All results for gaseous species are given in ppb (parts per billion) mole fractions.

¹ The zero response is the zero reading on the data logging system of the analyser when audit zero gas was introduced to the analysers under test.

² The calibration factor is the multiplying factor required to scale the reading on the data logging system of the analyser into reported concentration units (ppb for NO, NOx, SO2, O3 and ppm for CO. Where 1ppm = 1000ppb). It should be used in conjunction with the zero response. A corrected concentration is calculated using the following equation:

Concentration = F(Output - Zero Response) Where F = Calibration Factor provided on this certificate Output = Reading on the data logging system of the analyser Zero Response = Zero Response provided on this certificate

³ Converter eff. is the measured efficiency of the NO₂ to NO converter within the oxides of nitrogen analyser under test.

⁴ The measured main flow rate (where this is applicable) is the flow rate through the sensor unit of the TEOM particulate analyser under test. The measured total flow rate is the total flow rate through the particulate analyser under test. Units of flow are l.min⁻¹, reported at prevailing ambient conditions unless otherwise specified. Where flow rates are highlighted in bold, it indicates that measurements were not made at the analyser sample inlet. These measurements therefore may not accurately reflect analyser performance in normal operation.

⁵ The calculated ko value (specifically for TEOM analysers) is the calculated ko spring constant based on tests undertaken with filters of known weight. The % deviation indicates the closeness of the calculated result to the manufacturer's specified value of ko.

The calibration results shaded are those that fall within our scope of accreditation, all other results on this certificate are not UKAS accredited, but have been included for completeness.

ee.ricardo.com