



CERTIFICATE OF CALIBRATION

Ricardo Energy & Environment 18 Blythswood Square, Glasgow, G2 48G

Telephone 01235 753434



Page 1 of 3

Approved Signatories:		S. Ea D He N Ra B Da	ctor nd	☐ B Stacey ☐ S Stratton ☑ S Telfer ☐ S Gray			
Signed:	Stelp	1					
Date of issue:	29 July 2021						
Certificate Number:	5499						
Customer Name and Address:		Scottish Governm Water, Air, Soils a Environmental Qu Scottish Governm Victoria Quay Edinburgh EH6 6QQ	and Flooding Divisionality Directorate	on			
Description:		Calibration factors for the air monitoring station(s) at Fife Council					
Ricardo Energy & Environment ID:		ED11194/5499					
The reported expanded uncertainties are based on a level of confidence of approximately 95% The uncert requirements. This certificate is issued in accordance with the labor Service. It provides traceability of measurement to tl National Physical Laboratory or other recognised nat than in full, except with the prior written approval of	ainty evaluation has b atory accreditation re ne SI system of units a tional metrology instit	peen carried out in accorda equirements of the United I and/or to units of measure rutes. This certificate may n	nce with UKAS Kingdom Accreditation ment realised at the				
Ricardo Energy & Environment 18 Blythswood Square (2 nd Floor), Glasgow, G2 4BG Tel: 01235 753205	Shoreham Tech Shoreham-by-S West Sussex BN43 5FG Registered in I 08229264	BN43 5FG Registered in England No.					

ee.**ricardo**.com



CERTIFICATE OF CALIBRATION



Page 2 of 3

Date of issue: 29 July 2021

Certificate Number: 5499

Ricardo Energy & Environment ID: ED11194/5499

Fife Council NOx analysers

Station	Date of Audit	Species	Analyser Serial no	Zero Response ¹	Zero uncertainty ppb	Calibration Factor ²	Factor uncertainty %	Converter eff. (%) ³
Fife Cupar	28 June 2021	NOx	1172410005	0.1	2.5	1.0447	3.95	99.6
		NO		0.2	2.5	1.0536	3.64	
Fife Dunfermline	28 June 2021	NOx	1151310002	0.3	2.5	1.0572	3.50	100.0
		NO		0.2	2.5	1.0577	3.50	
Fife Kirkcaldy	28 June 2021	NOx	1007841323	-0.1	2.5	1.0548	3.50	103.0
		NO		0.3	2.5	1.0570	3.50	
Fife Rosyth	28 June 2021	NOx	1172410006	0.3	2.5	0.9730	3.50	101.2
		NO		0.3	2.5	0.9751	3.50	

FIDAS analysers

Station	Date of audit	Analyser Serial no	Calculated ko⁵	Uncertainty %	Total flow⁴	Uncertainty %	Main flow	Uncertainty %
Fife Cupar	28 June 2021	7663			4.73	2.2		2.2
Fife Dunfermline	28 June 2021	7449			4.73	2.2		2.2
Fife Kirkcaldy	28 June 2021	6655			4.77	2.2		2.2

PM10 analysers

Station	Date of audit	Analyser Serial no	Calculated ko⁵	Uncertainty %	Total flow⁴	Uncertainty %	Main flow	Uncertainty %
Fife Rosyth	21 July 2021	F5585			16.74	2.2		2.2

ee.**ricardo**.com



CERTIFICATE OF CALIBRATION



Page 3 of 3

Date of issue: 29 July 2021

Certificate Number: 5499

Ricardo Energy & Environment ID: ED11194/5499

The gaseous ambient analysers listed above have been tested for zero response, calibration factor, linearity and converter efficiency (NOx analysers) by documented methods. The factors have been calculated using certified gas standards. The particulate analysers listed above have been tested for sample flow rates and ko(where appropriate) by documented methods. Note that the test results are valid on the day of test only, as analyser drift over time cannot be quantified. All results for gaseous species are given in ppb (parts per billion) mole fractions or ppm (parts per million) mole fractions.

Concentration = F(Output - Zero Response)

Where F = Calibration Factor provided on this certificate

Output = Reading on the data logging system of the analyser

Zero Response = Zero Response provided on this certificate

The calibration results shaded are those that fall within our scope of accreditation, all other results on this certificate are not UKAS accredited, but have been included for completeness.

ee.ricardo.com

¹ The zero response is the zero reading on the data logging system of the analyser when audit zero gas was introduced to the analysers under test.

² The calibration factor is the multiplying factor required to scale the reading on the data logging system of the analyser into reported concentration units (ppb for NO, NOx, SO₂, O₃ and ppm for CO. Where 1ppm = 1000ppb). It should be used in conjunction with the zero response. A corrected concentration is calculated using the following equation:

³ Converter eff. is the measured efficiency of the NO₂ to NO converter within the oxides of nitrogen analyser under test.

⁴ The measured main flow rate (where this is applicable) is the flow rate through the sensor unit of the TEOM particulate analyser under test. The measured total flow rate is the total flow rate through the particulate analyser under test. Units of flow are l.min⁻¹, reported at prevailing ambient conditions unless otherwise specified. Where flow rates are highlighted in bold, it indicates that measurements were not made at the analyser sample inlet. These measurements therefore may not accurately reflect analyser performance in normal operation.

⁵ The calculated ko value (specifically for TEOM analysers) is the calculated ko spring constant based on tests undertaken with filters of known weight. The % deviation indicates the closeness of the calculated result to the manufacturer's specified value of ko.