



Ricardo Energy & Environment 18 Blythswood Square, Glasgow, G2 4BG

Telephone 01235 753434



Page 1 of 4

Approved Signatories:			S. Eaton N Rand B Davies	<ul><li>□ B Stacey</li><li>□ S Stratton</li><li>☑ S Telfer</li><li>□ S Gray</li></ul>		
Signed:	Stelker					
Date of issue:	17 August 2023					
Certificate Number:	6412					
Customer Name and Address:			Soils and Flooding D tal Quality Directora vernment			
Description:		Calibration factors for the air monitoring station(s) at Glasgow City Council				
Ricardo Energy & Environment ID:		ED11194/64	112			
The reported expanded uncertainties are based on a st level of confidence of approximately 95% The uncertain requirements.  This certificate is issued in accordance with the laborat Service. It provides traceability of measurement to the National Physical Laboratory or other recognised nation than in full, except with the prior written approval of the second secon	nty evaluation has been car ory accreditation requirem SI system of units and/or to nal metrology institutes. Th	ried out in accorda ents of the United o units of measure	nce with UKAS  Kingdom Accreditation ment realised at the			
Ricardo Energy & Environment  18 Blythswood Square (2 <sup>nd</sup> Floor), Glasgow, G2 4BG Tel: 01235 753205	Centre Id No.					





Page 2 of 4

Date of issue: 17 August 2023

Certificate Number: 6412

Ricardo Energy & Environment ID: ED11194/6412

# Glasgow City Council NOx analysers

NOX allalysels								
Station	Date of Audit	Species	Analyser Serial no	Zero Response <sup>1</sup>	Zero uncertainty ppb	Calibration Factor <sup>2</sup>	Factor uncertainty %	Converter eff. (%) <sup>3</sup>
Glasgow Anderston	20 June 2023	NOx	18-0383	-0.1	2.5	1.0133	3.50	100 (242nmol/mol)
		NO		0.3	2.5	0.9947	3.62	99.1 (142nmol/mol)
Glasgow Burgher Street	21 June 2023	NOx	22-1532	-1.1	2.5	1.0670	3.50	101.2 (240nmol/mol)
		NO		-0.1	2.5	1.0615	3.50	100.5 (142nmol/mol)
Glasgow Byres Road	19 June 2023	NOx	4156	-0.1	2.6	1.0823	3.50	99.7 (236nmol/mol)
		NO		2.8	2.6	1.0875	3.50	101.6 (144nmol/mol)
Glasgow Dumbarton Road	19 June 2023	NOx	4154	13.1	2.7	1.2929	3.50	98.6 (187nmol/mol)
		NO		9.7	2.7	1.2880	3.50	99.2 (107nmol/mol)
Glasgow Nithsdale Road	19 June 2023	NOx	1152030001	-1.2	2.6	1.1595	4.26	99.1 (249nmol/mol)
		NO		-1.3	2.6	1.1564	3.50	99.2 (145nmol/mol)
Glasgow Waulkmillglen Reservoir	20 June 2023	NOx	4155	2.6	2.5	1.0634	3.50	98.4 (247nmol/mol)
		NO		2.7	2.5	1.0551	3.50	99.5 (161nmol/mol)

#### FIDAS analysers

TID/ID dildiyacia								
Station	Date of audit	Analyser Serial no	Calculated ko⁵	Uncertainty %	Total flow⁴	Uncertainty %	Main flow	Uncertainty %
Glasgow Anderston	20 June 2023	10105			4.89	2.2		2.2
Glasgow Broomhill	20 June 2023	10106			4.76	2.2		2.2
Glasgow Burgher Street	21 June 2023	18904			4.66	2.2		2.2
Glasgow Byres Road	16 August 2023	8734			4.69	2.2		2.2
Glasgow Dumbarton Road	19 June 2023	8736			4.78	2.2		2.2
Glasgow Nithsdale Road	19 June 2023	6249			4.75	2.2		2.2
Glasgow Waulkmillglen Reservoir	20 June 2023	8735			4.80	2.2		2.2





Page 3 of 4

Date of issue: 17 August 2023

Certificate Number: 6412

Ricardo Energy & Environment ID: ED11194/6412

## O3 analysers

	Station	Date of Audit	Analyser Serial no	Zero Response <sup>1</sup>	Zero uncertainty ppb	Calibration Factor <sup>2</sup>	Factor uncertainty %
Glass	gow Waulkmillglen Reservoir	20 June 2023	3787	-1.1	3.0	0.9996	3.1





Page 4 of 4

Date of issue: 17 August 2023

Certificate Number: 6412

Ricardo Energy & Environment ID: ED11194/6412

The gaseous ambient analysers listed above have been tested for zero response, calibration factor, linearity and converter efficiency (NOx analysers) by documented methods. The factors have been calculated using certified gas standards. The particulate analysers listed above have been tested for sample flow rates and k0 (where appropriate) by documented methods. Note that the test results are valid on the day of test only, as analyser drift over time cannot be quantified. All results for gaseous species are reported in concentration units of nmol/mol or µmol/mol.

Concentration = F(Output - Zero Response)

Where F = Calibration Factor provided on this certificate

Output = Reading on the data logging system of the analyser

Zero Response = Zero Response provided on this certificate

The calibration results shaded are those that fall within our scope of accreditation, all other results on this certificate are not UKAS accredited, but have been included for completeness.

End of certificate

<sup>&</sup>lt;sup>1</sup> The zero response is the zero reading on the data logging system of the analyser when audit zero gas was introduced to the analysers under test.

 $<sup>^2</sup>$  The calibration factor is the multiplying factor required to scale the reading on the data logging system of the analyser into reported concentration units (nmol/mol for NO, NOx, SO2, O3 and  $\mu$ mol/mol for CO). It should be used in conjunction with the zero response. A corrected concentration is calculated using the following equation:

<sup>&</sup>lt;sup>3</sup> Converter eff. is the measured efficiency of the NO<sub>2</sub> to NO converter within the oxides of nitrogen analyser under test.

<sup>&</sup>lt;sup>4</sup> The measured main flow rate (where this is applicable) is the flow rate through the sensor unit of the TEOM particulate analyser under test. The measured aux flow rate (where this is applicable) is the flow rate through the bypass tubing of the TEOM particulate analyser under test. The measured total flow rate is the total flow rate through the particulate analyser under test. Units of flow are I.min-1, reported at prevailing ambient conditions unless otherwise specified. Where flow rates are highlighted in bold, it indicates that measurements were not made at the analyser sample inlet. These measurements therefore may not accurately reflect analyser performance in normal operation.

<sup>&</sup>lt;sup>5</sup> The calculated ko value (specifically for TEOM analysers) is the calculated ko spring constant based on tests undertaken with filters of known weight. The % deviation indicates the closeness of the calculated result to the manufacturer's specified value of ko.