



# CERTIFICATE OF CALIBRATION

Ricardo Energy & Environment 18 Blythswood Square, Glasgow, G2 4BG





Page 1 of 3

Approved Signatories:	S. Eato	or d	<ul><li>□ B Stacey</li><li>□ S Stratton</li><li>☑ S Telfer</li><li>□ S Gray</li></ul>				
Signed:	Stelk	1					
Date of issue:	29 July 2021						
Certificate Number:	5502						
Customer Name and Address:		Scottish Governmer Water, Air, Soils an Environmental Qual Scottish Governmer Victoria Quay Edinburgh EH6 6QQ	d Flooding Division lity Directorate	nc			
Description:		Calibration factors for the air monitoring station(s) at North Ayrshire Council					
Ricardo Energy & Environment ID:		ED11194/5502					
The reported expanded uncertainties are based on a level of confidence of approximately 95% The uncert requirements.  This certificate is issued in accordance with the labor Service. It provides traceability of measurement to the National Physical Laboratory or other recognised nat than in full, except with the prior written approval of	ainty evaluation has b atory accreditation re ne SI system of units a ional metrology institi	een carried out in accordance quirements of the United Kin nd/or to units of measureme utes. This certificate may not	e with UKAS  gdom Accreditation  nt realised at the				
Ricardo Energy & Environment  18 Blythswood Square (2 <sup>nd</sup> Floor), Glasgow, G2 4BG Tel: 01235 753205	pe nical Centre ea ngland No. on No.						

ee.**ricardo**.com



# **CERTIFICATE OF CALIBRATION**



Page 2 of 3

Date of issue: 29 July 2021

Certificate Number: 5502

Ricardo Energy & Environment ID: ED11194/5502

## North Ayrshire Council

NOx analysers

Station	Date of Audit	Species	Analyser Serial no	Zero Response <sup>1</sup>	Zero uncertainty ppb	Calibration Factor <sup>2</sup>	Factor uncertainty %	Converter eff. (%) <sup>3</sup>
North Ayrshire Irvine High Street	24 June 2021	NOx	19-2513	1.0	2.7	1.0481	3.50	100.9
		NO		0.0	2.5	1.0433	3.50	

## Fidas analysers

Station	Date of audit	Analyser Serial no	Calculated ko⁵	Uncertainty %	Total flow⁴	Uncertainty %	Main flow	Uncertainty %
North Ayrshire Irvine High Street	24 June 2021	6251			4.69	2.2		2.2

ee.**ricardo**.com



### **CERTIFICATE OF CALIBRATION**



Page 3 of 3

Date of issue: 29 July 2021

Certificate Number: 5502

Ricardo Energy & Environment ID: ED11194/5502

The gaseous ambient analysers listed above have been tested for zero response, calibration factor, linearity and converter efficiency (NOx analysers) by documented methods. The factors have been calculated using certified gas standards. The particulate analysers listed above have been tested for sample flow rates and ko(where appropriate) by documented methods. Note that the test results are valid on the day of test only, as analyser drift over time cannot be quantified. All results for gaseous species are given in ppb (parts per billion) mole fractions or ppm (parts per million) mole fractions.

Concentration = F(Output - Zero Response)

Where F = Calibration Factor provided on this certificate

Output = Reading on the data logging system of the analyser

Zero Response = Zero Response provided on this certificate

The calibration results shaded are those that fall within our scope of accreditation, all other results on this certificate are not UKAS accredited, but have been included for completeness.

ee.ricardo.com

<sup>&</sup>lt;sup>1</sup> The zero response is the zero reading on the data logging system of the analyser when audit zero gas was introduced to the analysers under test.

<sup>&</sup>lt;sup>2</sup> The calibration factor is the multiplying factor required to scale the reading on the data logging system of the analyser into reported concentration units (ppb for NO, NOx, SO<sub>2</sub>, O<sub>3</sub> and ppm for CO. Where 1ppm = 1000ppb). It should be used in conjunction with the zero response. A corrected concentration is calculated using the following equation:

<sup>&</sup>lt;sup>3</sup> Converter eff. is the measured efficiency of the NO<sub>2</sub> to NO converter within the oxides of nitrogen analyser under test.

<sup>&</sup>lt;sup>4</sup> The measured main flow rate (where this is applicable) is the flow rate through the sensor unit of the TEOM particulate analyser under test. The measured total flow rate is the total flow rate through the particulate analyser under test. Units of flow are l.min<sup>-1</sup>, reported at prevailing ambient conditions unless otherwise specified. Where flow rates are highlighted in bold, it indicates that measurements were not made at the analyser sample inlet. These measurements therefore may not accurately reflect analyser performance in normal operation.

<sup>&</sup>lt;sup>5</sup> The calculated ko value (specifically for TEOM analysers) is the calculated ko spring constant based on tests undertaken with filters of known weight. The % deviation indicates the closeness of the calculated result to the manufacturer's specified value of ko.