

## CERTIFICATE OF CALIBRATION





Page 1 of 3

Approved Signatories:			S. Eaton D Hector N Rand B Davies	☐ B Stacey ☐ S Stratton ☑ S Telfer ☐ S Gray
Signed:	Stelker			
Date of issue:	24 February 2021			
Certificate Number:	5276			
Customer Name and Address:			s and Flooding Div Quality Directorate	
Description:		Calibration fact North Lanarksh		nitoring station(s) at
Ricardo Energy & Environment ID:		ED11194/5276		
The reported expanded uncertainties are based on a standard unclevel of confidence of approximately 95% The uncertainty evaluative quirements.  This certificate is issued in accordance with the laboratory accrediscribed. It provides traceability of measurement to the SI system or National Physical Laboratory or other recognised national metrolothan in full, except with the prior written approval of the issuing laboratory.	ion has been carried out in acc tation requirements of the Uni of units and/or to units of mea gy institutes. This certificate m	ordance with UKAS ited Kingdom Accredita surement realised at the	tion e	
Ricardo Energy & Environment  18 Blythswood Square (2 <sup>nd</sup> Floor), Glasgow, G2 4BG  Tel: 01235 753205	Registered office Shoreham Technical Cen Shoreham-by-Sea West Sussex BN43 5FG Registered in England N 08229264 VAT Registration No. GB 212 8365 24			

ee.**ricardo.**com



## **CERTIFICATE OF CALIBRATION**



Page 2 of 3

Date of issue: 24 February 2021

5276 Certificate Number:

ED11194/5276 Ricardo Energy & Environment ID:

North Lanarkshire Council

NOx analysers								
Station	Date of Audit	Species	Analyser Serial no	Zero Response <sup>1</sup>	Zero uncertainty ppb	Calibration Factor <sup>2</sup>	Factor uncertainty %	Converter eff.
	07 January 2021	NOx	9L2FE9GJ	-0.9	2.5	0.9686	3.50	98.9
N Lanarkshire Airdrie Kenilsworth Drive		NO		-0.8	2.5	0.9758	3.50	
N Lanarkshire Chapelhall	06 January 2021	NOx	7NLHD0L8	-3.1	3.0	0.9882	3.50	102.0
		NO		-2.5	2.9	0.9918	3.50	
N Lanarkshire Coatbridge Sunnyside	06 January 2021	NOx	HUK14070019	0.1	2.7	1.2864	3.50	99.5
Road		NO		-0.6	2.7	1.3079	3.50	
N Lanarkshire Coatbridge Whifflet	12 February 2021	NOx	XDG8LYS0	0.3	2.7	1.1392	3.50	86.0
		NO		0.3	2.7	1.1594	3.50	
N Lanarkshire Croy	08 January 2021	NOx	AYKTCJU8	0.9	3.3	2.2538	3.50	101.8
		NO		-0.4	3.3	2.3256	3.50	
N Lanarkshire Motherwell	06 January 2021	NOx	YPB4FS4U	0.7	2.5	1.0631	3.50	98.3
		NO		0.0	2.6	1.0705	3.50	
N Lanarkshire Motherwell Adele Street 12 Febru	12 February 2021	NOx	EUGBA000	0.5	3.5	0.9938	3.50	100.7
		NO		0.8	3.2	0.9908	3.50	
N Lanarkshire Shawhead Coatbridge 05 Janua	05 January 2021	NOx	7NHSKHBC	-1.6	2.6	0.9783	3.50	99.6
		NO		-0.5	2.5	0.9859	3.50	
N Lanarkshire Kirkshaws 05 J	05 January 2021	NOx	HUK15020066	-0.8	2.6	1.0773	3.50	100.4
		NO		-0.6	2.6	1.0903	3.50	
N Lanarkshire Uddingston New	07 January 2021	NOx	-	-1.7	2.5	0.9536	3.50	103.2
Edinburgh Road		NO	(Inaccessible panel)	-0.9	2.5	0.9636	3.50	

PM10 analysers

Station	Date of audit	Analyser Serial no	Calculated ko <sup>5</sup>	Uncertainty %	Total flow⁴	Uncertainty %	Main flow	Uncertainty %
N Lanarkshire Airdrie Kenilsworth Drive	07 January 2021	R11772			12.61	2.2		2.2
N Lanarkshire Coatbridge Sunnyside Road	06 January 2021	R11774			15.16	2.2		2.2
N Lanarkshire Uddingston New Edinburgh Road	07 January 2021	P18029			0.00	2.2		2.2

Fidas analysers

ridas arialyscis								
Station	Date of audit	Analyser Serial no	Calculated ko <sup>5</sup>	Uncertainty %	Total flow⁴	Uncertainty %	Main flow	Uncertainty %
N Lanarkshire Chapelhall	06 January 2021	8323			4.42	2.2		2.2
N Lanarkshire Coatbridge Whifflet	05 January 2021	12143			4.49	2.2		2.2
N Lanarkshire Croy	08 January 2021	9552			4.40	2.2		2.2
N Lanarkshire Kirkshaws	05 January 2021	9554			4.46	2.2		2.2
N Lanarkshire Motherwell	06 January 2021	9551			4.44	2.2		2.2
N Lanarkshire Motherwell Adele Street	07 January 2021	9553			4.41	2.2		2.2
N Lanarkshire Shawhead Coatbridge	05 January 2021	9550			4.45	2.2		2.2

ee.**ricardo**.com



## **CERTIFICATE OF CALIBRATION**



Page 3 of 3

Date of issue: 24 February 2021

Certificate Number: 5276

Ricardo Energy & Environment ID: ED11194/5276

The gaseous ambient analysers listed above have been tested for zero response, calibration factor, linearity and converter efficiency (NOx analysers) by documented methods. The factors have been calculated using certified gas standards. The particulate analysers listed above have been tested for sample flow rates and ko (where appropriate) by documented methods. Note that the test results are valid on the day of test only, as analyser drift over time cannot be quantified. All results for gaseous species are given in ppb (parts per billion) mole fractions.

Concentration = F(Output - Zero Response)
Where F = Calibration Factor provided on this certificate

Output = Reading on the data logging system of the analyser Zero Response = Zero Response provided on this certificate

The calibration results shaded are those that fall within our scope of accreditation, all other results on this certificate are not UKAS accredited, but have been included for completeness.

ee.**ricardo**.com

<sup>&</sup>lt;sup>1</sup> The zero response is the zero reading on the data logging system of the analyser when audit zero gas was introduced to the analysers under test.

<sup>&</sup>lt;sup>2</sup> The calibration factor is the multiplying factor required to scale the reading on the data logging system of the analyser into reported concentration units (ppb for NO, NOx, SO2, O3 and ppm for CO. Where 1ppm = 1000ppb). It should be used in conjunction with the zero response. A corrected concentration is calculated using the following equation:

<sup>&</sup>lt;sup>3</sup> Converter eff. is the measured efficiency of the NO<sub>2</sub> to NO converter within the oxides of nitrogen analyser under test.

<sup>&</sup>lt;sup>4</sup> The measured main flow rate (where this is applicable) is the flow rate through the sensor unit of the TEOM particulate analyser under test. The measured total flow rate is the total flow rate through the particulate analyser under test. Units of flow are l.min<sup>-1</sup>, reported at prevailing ambient conditions unless otherwise specified. Where flow rates are highlighted in bold, it indicates that measurements were not made at the analyser sample inlet. These measurements therefore may not accurately reflect analyser performance in normal operation.

<sup>&</sup>lt;sup>5</sup> The calculated ko value (specifically for TEOM analysers) is the calculated ko spring constant based on tests undertaken with filters of known weight. The % deviation indicates the closeness of the calculated result to the manufacturer's specified value of ko.