



CERTIFICATE OF CALIBRATION

Ricardo Energy & Environment 18 Blythswood Square, Glasgow, G2 4BG

Telephone 01235 753434



Page 1 of 3

Approved Signatories:			S. Eaton D Hector N Rand B Davies	☐ B Stacey ☐ S Stratton ☑ S Telfer ☐ S Gray			
Signed: Date of issue:	Stelker 04 August 2022						
Certificate Number:	5941						
Customer Name and Address:		Scottish Government Water, Air, Soils and Flooding Division Environmental Quality Directorate Scottish Government Victoria Quay Edinburgh EH6 6QQ					
Description:	Calibration factors for the air monitoring station(s) at North Lanarkshire Council						
Ricardo Energy & Environment ID:		ED11194/5941					
The reported expanded uncertainties are based on a st level of confidence of approximately 95% The uncertain requirements. This certificate is issued in accordance with the laborat Service. It provides traceability of measurement to the National Physical Laboratory or other recognised nation than in full, except with the prior written approval of the Ricardo Energy & Environment Ricardo Energy & Environment 18 Blythswood Square (2 nd Floor), Glasgow, G2 4BG Tel: 01235 753205	nty evaluation has been carr ory accreditation requireme SI system of units and/or to nal metrology institutes. This	ied out in accordance wi nts of the United Kingdo units of measurement r s certificate may not be i Centre	om Accreditation				

ee.**ricardo**.com



CERTIFICATE OF CALIBRATION



Page 2 of 3

Date of issue: 04 August 2022

Certificate Number: 5941

Ricardo Energy & Environment ID: ED11194/5941

North Lanarkshire Council

NOx analysers

NOx analysers								
Station	Date of Audit	Species	Analyser Serial no	Zero Response ¹	Zero uncertainty nmol/mol	Calibration Factor ²	Factor uncertainty %	Converter eff. (%) ³
N Lanarkshire Chapelhall	22 June 2022	NOx	7NLHD0L8	-3.5	2.7	0.9469	3.50	98.4
		NO		-4.4		0.9550		
N Lanarkshire Croy	23 June 2022	NOx	AYKTCJU8	-0.1	2.6	0.9783	3.50	100.0
		NO		-0.2	2.6	0.9717	3.50	
N Lanarkshire Kirkshaws	20 June 2022	NOx	P8GT9WHE	-0.7	2.5	0.7975	3.50	99.4
		NO		-0.2	2.5	0.7886	3.50	
N Lanarkshire Shawhead Coatbridge	20 June 2022	NOx	7NHSKHBC	-0.1	2.6	1.0292	3.50	99.7
		NO		-0.2	2.6	1.0480	3.50	

Fidas analysers

Station	Date of audit	Analyser Serial no	Calculated ko⁵	Uncertainty %	Total flow⁴	Uncertainty %	Main flow	Uncertainty %
N Lanarkshire Chapelhall	22 June 2022	8323			4.75	2.2		2.2
N Lanarkshire Croy	23 June 2022	9552			4.75	2.2		2.2
N Lanarkshire Kirkshaws	20 June 2022	9554			4.88	2.2		2.2
N Lanarkshire Motherwell	21 June 2022	9551			4.74	2.2		2.2
N Lanarkshire Ravenscraig Plantation Road	22 June 2022	12143			4.84	2.2		2.2
N Lanarkshire Shawhead Coatbridge	20 June 2022	9550			4.79	2.2		2.2

ee.**ricardo**.com



CERTIFICATE OF CALIBRATION



Page 3 of 3

Date of issue: 04 August 2022

Certificate Number: 5941

Ricardo Energy & Environment ID: ED11194/5941

The gaseous ambient analysers listed above have been tested for zero response, calibration factor, linearity and converter efficiency (NOx analysers) by documented methods. The factors have been calculated using certified gas standards. The particulate analysers listed above have been tested for sample flow rates and k0 (where appropriate) by documented methods. Note that the test results are valid on the day of test only, as analyser drift over time cannot be quantified. All results for gaseous species are reported in concentration units of nmol/mol or $\mu mol/mol$.

Concentration = F(Output - Zero Response)

Where F = Calibration Factor provided on this certificate

Output = Reading on the data logging system of the analyser

Zero Response = Zero Response provided on this certificate

- ⁴ The measured main flow rate (where this is applicable) is the flow rate through the sensor unit of the TEOM particulate analyser under test. The measured aux flow rate (where this is applicable) is the flow rate through the bypass tubing of the TEOM particulate analyser under test. The measured total flow rate is the total flow rate through the particulate analyser under test. Units of flow are l.min-1, reported at prevailing ambient conditions unless otherwise specified. Where flow rates are highlighted in bold, it indicates that measurements were not made at the analyser sample inlet. These measurements therefore may not accurately reflect analyser performance in normal operation.
- ⁵ The calculated ko value (specifically for TEOM analysers) is the calculated ko spring constant based on tests undertaken with filters of known weight. The % deviation indicates the closeness of the calculated result to the manufacturer's specified value of ko.

The calibration results shaded are those that fall within our scope of accreditation, all other results on this certificate are not UKAS accredited, but have been included for completeness.

ee.ricardo.com

¹ The zero response is the zero reading on the data logging system of the analyser when audit zero gas was introduced to the analysers under test.

² The calibration factor is the multiplying factor required to scale the reading on the data logging system of the analyser into reported concentration units (nmol/mol for NO, NOx, SO2, O3 and μmol/mol for CO). It should be used in conjunction with the zero response. A corrected concentration is calculated using the following equation:

³ Converter eff. is the measured efficiency of the NO₂ to NO converter within the oxides of nitrogen analyser under test.