



CERTIFICATE OF CALIBRATION

Ricardo Energy & Environment 18 Blythswood Square, Glasgow, G2 4BG

Telephone 01235 753434



Page 1 of 3

Approved Signatories:			S. Eaton N Rand B Davies	□ B Stacey□ S Stratton☑ S Telfer□ S Gray		
Signed:	Stelki					
Date of issue:	17 August 2023					
Certificate Number:	6415					
Customer Name and Address:			Soils and Flooding Ital Quality Director vernment			
Description:		Calibration factors for the air monitoring station(s) at North Lanarkshire Council				
Ricardo Energy & Environment ID:		ED11194/64	415			
The reported expanded uncertainties are based on a stand level of confidence of approximately 95% The uncertainty requirements. This certificate is issued in accordance with the laboratory Service. It provides traceability of measurement to the SIs National Physical Laboratory or other recognised national than in full, except with the prior written approval of the is	evaluation has been carrie accreditation requiremen ystem of units and/or to u metrology institutes. This	ed out in accordants ts of the United Ki	ngdom Accreditation			
Ricardo Energy & Environment 18 Blythswood Square (2 nd Floor), Glasgow, G2 4BG Tel: 01235 753205	Registered office Shoreham Technical O Shoreham-by-Sea West Sussex BN43 5FG Registered in Englan 08229264 VAT Registration No. GB 212 8365 24	d No.				

ee.**ricardo**.com



CERTIFICATE OF CALIBRATION



Page 2 of 3

Date of issue: 17 August 2023

Certificate Number: 6415

Ricardo Energy & Environment ID: ED11194/6415

North Lanarkshire Council

NOx analysers

non analysers								
Station	Date of Audit	Species	Analyser Serial no	Zero Response ¹	Zero uncertainty nmol/mol	Calibration Factor ²	Factor uncertainty %	Converter eff. (%) ³
N Lanarkshire Chapelhall	04 July 2023	NOx	23-0185	-1.0	2.5	1.0139	3.50	99.8 (249nmol/mol)
		NO		1.5	2.5	1.0146	3.50	99.8 (120nmol/mol)
N Lanarkshire Croy	06 July 2023	NOx	23-0158	0.3	2.5	1.0476	3.50	100.4 (264nmol/mol)
		NO		-0.4	2.5	1.0412	3.50	99.2 (121nmol/mol)
N Lanarkshire Kirkshaws	03 July 2023	NOx	23-0155	-0.4	2.9	1.6661	3.50	100.7 (253nmol/mol)
		NO		2.7	2.9	1.6595	3.50	100.5 (123nmol/mol)
N Lanarkshire Shawhead Coatbridge	03 July 2023	NOx	23-0160	-0.7	2.6	1.0903	3.50	99.9 (260nmol/mol)
		NO		0.3	2.6	1.0846	3.50	100.9 (131nmol/mol)

FIDAS analysers

Station	Date of audit	Analyser Serial no	Calculated ko⁵	Uncertainty %	Total flow⁴	Uncertainty %	Main flow	Uncertainty %
N Lanarkshire Chapelhall	04 July 2023	8323			5.13	2.2		2.2
N Lanarkshire Croy	06 July 2023	9552			5.01	2.2		2.2
N Lanarkshire Kirkshaws	03 July 2023	9554			5.15	2.2		2.2
N Lanarkshire Motherwell	05 July 2023	9551			5.14	2.2		2.2
N Lanarkshire Ravenscraig Plantation Road	05 July 2023	12143			4.87	2.2		2.2
N Lanarkshire Shawhead Coatbridge	03 July 2023	9550			5.23	2.2		2.2

ee.**ricardo**.com



CERTIFICATE OF CALIBRATION



Page 3 of 3

Date of issue:	17 August 2023
----------------	----------------

Certificate Number: 6415

Ricardo Energy & Environment ID: ED11194/6415

The gaseous ambient analysers listed above have been tested for zero response, calibration factor, linearity and converter efficiency (NOx analysers) by documented methods. The factors have been calculated using certified gas standards. The particulate analysers listed above have been tested for sample flow rates and k0 (where appropriate) by documented methods. Note that the test results are valid on the day of test only, as analyser drift over time cannot be quantified. All results for gaseous species are reported in concentration units of nmol/mol or μ mol/mol.

Concentration = F(Output - Zero Response)

Where F = Calibration Factor provided on this certificate

Output = Reading on the data logging system of the analyser

Zero Response = Zero Response provided on this certificate

The calibration results shaded are those that fall within our scope of accreditation, all other results on this certificate are not UKAS accredited, but have been included for completeness.

End of certificate

ee.ricardo.com

¹ The zero response is the zero reading on the data logging system of the analyser when audit zero gas was introduced to the analysers under test.

² The calibration factor is the multiplying factor required to scale the reading on the data logging system of the analyser into reported concentration units (nmol/mol for NO, NOx, SO2, O3 and µmol/mol for CO). It should be used in conjunction with the zero response. A corrected concentration is calculated using the following equation:

³ Converter eff. is the measured efficiency of the NO₂ to NO converter within the oxides of nitrogen analyser under test

⁴ The measured main flow rate (where this is applicable) is the flow rate through the sensor unit of the TEOM particulate analyser under test. The measured aux flow rate (where this is applicable) is the flow rate through the bypass tubing of the TEOM particulate analyser under test. The measured total flow rate is the total flow rate through the particulate analyser under test. Units of flow are I.min-1, reported at prevailing ambient conditions unless otherwise specified. Where flow rates are highlighted in bold, it indicates that measurements were not made at the analyser sample inlet. These measurements therefore may not accurately reflect analyser performance in normal operation.

⁵ The calculated ko value (specifically for TEOM analysers) is the calculated ko spring constant based on tests undertaken with filters of known weight. The % deviation indicates the closeness of the calculated result to the manufacturer's specified value of ko.