



CERTIFICATE OF CALIBRATION

Ricardo Energy & Environment 18 Blythswood Square, Glasgow, G2 4BG
Telephone 01235 753434



Page 1 of 3

Approved Signatories:			S. Eaton D Hector N Rand B Davies	☐ B Stacey ☐ S Stratton ☑ S Telfer ☐ S Gray			
Signed:	Steller						
Date of issue:	02 February 2021						
Certificate Number:	5278						
Customer Name and Address:			s and Flooding Di Quality Directorat				
Description:		Calibration factors for the air monitoring station(s) at Renfrewshire Council					
Ricardo Energy & Environment ID:		ED11194/5278					
The reported expanded uncertainties are based on a standard u level of confidence of approximately 95% The uncertainty evalu requirements. This certificate is issued in accordance with the laboratory accreservice. It provides traceability of measurement to the SI system National Physical Laboratory or other recognised national metro than in full, except with the prior written approval of the issuing	ation has been carried out in ditation requirements of the nof units and/or to units of n ology institutes. This certifical laboratory	accordance with UKAS United Kingdom Accredineasurement realised at	itation the				
Ricardo Energy & Environment 18 Blythswood Square (2 nd Floor), Glasgow, G2 4BG Tel: 01235 753205	Registered office Shoreham Technical C. Shoreham-by-Sea West Sussex BN43 5FG Registered in England 08229264 VAT Registration No. GB 212 8365 24						

ee.**ricardo**.com



CERTIFICATE OF CALIBRATION



Page 2 of 3

Date of issue: 02 February 2021

Certificate Number: 5278

Ricardo Energy & Environment ID: ED11194/5278

Renfrewshire Council

NOx analysers

NOX allalysers								
Station	Date of Audit	Species	Analyser Serial no	Zero Response ¹	Zero uncertainty ppb	Calibration Factor ²	Factor uncertainty %	Converter eff. (%) ³
Paisley Gordon Street	29 December 2020	NOx	M1486-M623	-1.0	2.8	1.0478	3.50	98.4
		NO		-1.0	2.5	1.0478	3.50	
Renfrew Cockles Loan	18 December 2020	NOx	1108947668	-5.0	2.6	1.1138	3.50	99.6
		NO		-3.5	2.6	1.1233	3.50	
Renfrewshire Inchinnan Road	18 December 2020	NOx	18-1174	6.0	2.8	1.0849	3.63	100.4
		NO		3.0	2.5	1.0773	3.63	

PM10 analysers

Station	Date of audit	Analyser Serial no	Calculated ko⁵	Uncertainty %	Total flow ⁴	Uncertainty %	Main flow	Uncertainty %
Paisley Gordon Street	29 December 2020	140AB233710012	12947	1.0	16.68	2.2	2.93	2.2

ee.**ricardo.**com



CERTIFICATE OF CALIBRATION



Page 3 of 3

Date of issue: 02 February 2021

Certificate Number: 5278

Ricardo Energy & Environment ID: ED11194/5278

The gaseous ambient analysers listed above have been tested for zero response, calibration factor, linearity and converter efficiency (NOx analysers) by documented methods. The factors have been calculated using certified gas standards. The particulate analysers listed above have been tested for sample flow rates and ko (vappropriate) by documented methods. Note that the test results are valid on the day of test only, as analyser drift over time cannot be quantified. All results for gaseous species are given in ppb (parts per billion) mole fractions or ppm (parts per million) mole fractions.

- ¹ The zero response is the zero reading on the data logging system of the analyser when audit zero gas was introduced to the analysers under test.
- ² The calibration factor is the multiplying factor required to scale the reading on the data logging system of the analyser into reported concentration units (ppb for NO, NOx, SO2, O3 and ppm for CO. Where 1ppm = 1000ppb). It should be used in conjunction with the zero response. A corrected concentration is calculated using the following equation:

Concentration = F(Output - Zero Response)

Where F = Calibration Factor provided on this certificate

Output = Reading on the data logging system of the analyser Zero Response = Zero Response provided on this certificate

The calibration results shaded are those that fall within our scope of accreditation, all other results on this certificate are not UKAS accredited, but have been included for completeness.

ee.**ricardo**.com

³ Converter eff. is the measured efficiency of the NO₂ to NO converter within the oxides of nitrogen analyser under test.

⁴ The measured main flow rate (where this is applicable) is the flow rate through the sensor unit of the TEOM particulate analyser under test. The measured total flow rate is the total flow rate through the particulate analyser under test. Units of flow are l.min⁻¹, reported at prevailing ambient conditions unless otherwise specified. Where flow rates are highlighted in bold, it indicates that measurements were not made at the analyser sample inlet. These measurements therefore may not accurately reflect analyser performance in normal operation.

⁵ The calculated ko value (specifically for TEOM analysers) is the calculated ko spring constant based on tests undertaken with filters of known weight. The % deviation indicates the closeness of the calculated result to the manufacturer's specified value of ko.