



CERTIFICATE OF CALIBRATION

Ricardo Energy & Environment 18 Blythswood Square, Glasgow, G2 4BG

Telephone 01235 753434



Page 1 of 3

Approved Signatories:			S. Eaton D Hector N Rand B Davies	☐ B Stacey☐ S Stratton☐ S Telfer☐ S Gray
Signed:	Stelki			
Date of issue:	04 August 2022			
Certificate Number:	5943			
Customer Name and Address:			oils and Flooding of Quality Directo prnment	
Description:		Calibration fac Renfrewshire		nonitoring station(s) at
Ricardo Energy & Environment ID:		ED11194/594	3	
The reported expanded uncertainties are based level of confidence of approximately 95% The unrequirements. This certificate is issued in accordance with the I Service. It provides traceability of measurement National Physical Laboratory or other recognise than in full, except with the prior written approximately.	aboratory accreditation has been of aboratory accreditation require to the SI system of units and/od national metrology institutes.	arried out in accordar ments of the United K r to units of measuren	nce with UKAS lingdom Accreditation nent realised at the	
Ricardo Energy & Environment 18 Blythswood Square (2 nd Floor), Glasgow, G2 4BG Tel: 01235 753205	Registered office Shoreham Technical Shoreham-by-Sea West Sussex BN43 SFG Registered in Engla 08229264 VAT Registration No GB 212 8365 24	nd No.		

ee.**ricardo**.com







Page 2 of 3

Date of issue: 04 August 2022

Certificate Number: 5943

Ricardo Energy & Environment ID: ED11194/5943

Renfrewshire Council

NOx analysers

NOX allalysels								
Station	Date of Audit	Species	Analyser Serial no	Zero Response ¹	Zero uncertainty nmol/mol	Calibration Factor ²	Factor uncertainty %	Converter eff. (%) ³
Renfrew Cockels Loan	09 June 2022	NOx	11089447888	-7.7	2.5	1.0613	3.54	100.5
		NO		-7.4	2.5	1.0622	3.50	
Renfrewshire Inchinnan Road	09 June 2022	NOx	18-1174	-2.0	2.5	0.9956	3.50	99.6
		NO		0.0	2.7	0.9934	3.59	

Fidas analysers

Station	Date of audit	Analyser Serial no	Calculated ko ^s	Uncertainty %	Total flow⁴	Uncertainty %	Main flow	Uncertainty %
Renfrewshire Johnstone	08 June 2022	7735			4.74	2.2		2.2

ee.**ricardo**.com



CERTIFICATE OF CALIBRATION



Page 3 of 3

Date of issue: 04 August 2022

Certificate Number: 5943

Ricardo Energy & Environment ID: ED11194/5943

The gaseous ambient analysers listed above have been tested for zero response, calibration factor, linearity and converter efficiency (NOx analysers) by documented methods. The factors have been calculated using certified gas standards. The particulate analysers listed above have been tested for sample flow rates and k0 (where appropriate) by documented methods. Note that the test results are valid on the day of test only, as analyser drift over time cannot be quantified. All results for gaseous species are reported in concentration units of nmol/mol or µmol/mol.

Concentration = F(Output - Zero Response)

Where F = Calibration Factor provided on this certificate

Output = Reading on the data logging system of the analyser Zero Response = Zero Response provided on this certificate

The calibration results shaded are those that fall within our scope of accreditation, all other results on this certificate are not UKAS accredited, but have been included for completeness.

ee.ricardo.com

¹ The zero response is the zero reading on the data logging system of the analyser when audit zero gas was introduced to the analysers under test.

² The calibration factor is the multiplying factor required to scale the reading on the data logging system of the analyser into reported concentration units (nmol/mol for NO, NOx, SO2, O3 and µmol/mol for CO). It should be used in conjunction with the zero response. A corrected concentration is calculated using the following equation:

³ Converter eff. is the measured efficiency of the NO₂ to NO converter within the oxides of nitrogen analyser under test.

⁴ The measured main flow rate (where this is applicable) is the flow rate through the sensor unit of the TEOM particulate analyser under test. The measured aux flow rate (where this is applicable) is the flow rate through the bypass tubing of the TEOM particulate analyser under test. The measured total flow rate is the total flow rate through the particulate analyser under test. Units of flow are I.min-1, reported at prevailing ambient conditions unless otherwise specified. Where flow rates are highlighted in bold, it indicates that measurements were not made at the analyser sample inlet. These measurements therefore may not accurately reflect analyser performance in normal operation.

⁵ The calculated ko value (specifically for TEOM analysers) is the calculated ko spring constant based on tests undertaken with filters of known weight. The % deviation indicates the closeness of the calculated result to the manufacturer's specified value of ko.