	CERTIFICATE C Ricardo Energy & Environment 18 Tel: 01	DF CALIBRATION Blythswood Square, Glasgow, G2 4BG, UK 12357753205	RICARDO			
			Page 1 of 3			
Approved Signatories:		 S. Eaton D Hector N Rand B Davies 	 □ B Stacey □ S Stratton ☑ S Telfer □ S Gray 			
Signed:	Stelfer					
Date of issue:	28 July 2020					
Certificate Number:	5089					
Customer Name and Address		Scottish Government Water, Air, Soils and Flooding Di Environmental Quality Directora Scottish Government Victoria Quay Edinburgh EH6 6QQ	ivision te			
Description:		Calibration factors for the air mo South Lanarkshire Council	nitoring station(s) at			
Ricardo Energy & Environmer	nt ID:	ED11194/5089				
The reported expanded uncertainties are based on a standard uncertainty multiplied by a coverage factor k=2 providing a level of confidence of approximately 95% The uncertainty evaluation has been carried out in accordance with UKAS requirements. This certificate is issued in accordance with the laboratory accreditation requirements of the United Kingdom Accreditation Service. It provides traceability of measurement to the SI system of units and/or to units of measurement realised at the National Physical Laboratory or other recognised national metrology institutes. This certificate may not be reproduced other than in full, except with the prior written approval of the issuing laboratory						
Ricardo Energy & Environment 18 Blythswood Square (2 nd Floor), Glasgow, G2 4BG Tel: 01235 753205	Registered off Shoreham Tect Shoreham-by-S West Sussex BN43 5FG Registered in I 08229264 VAT Registrati GB 212 8365 24	ice innical Centre ea England No. on No. 4				
			ee. ricardo .com			



CERTIFICATE OF CALIBRATION



Page 2 of 3

Date of issue:	28 July 2020	
Certificate Number:	5089	
Ricardo Energy & Environment ID:	ED11194/5089	

South Lanarkshire Council NOx analysers

Station	Date of Audit	Species	Analyser Serial no	Zero Response ¹	Zero uncertainty ppb	Calibration Factor ²	Factor uncertainty %	Converter eff. (%) ³
South Lanarkshire Blantyre	09 June 2020	NOx	18-0740	5.0	2.6	1.0891	3.50	99.7
		NO		1.0	2.5	1.0681	3.50	
South Lanarkshire Cambuslang	23 June 2020	NOx	1152590008	-0.2	2.6	1.2287	3.50	99.1
		NO		-0.1	2.6	1.2356	3.52	
South Lanarkshire East Kilbride	09 June 2020	NOx	CM07460075	2.4	3.6	1.0999	10.28	-
		NO		0.0	7.8	1.1198	18.17	
South Lanarkshire Hamilton	10 June 2020	NOx	CM7460073	-0.7	2.5	1.0116	3.50	98.4
		NO		0.0	2.5	1.0199	3.50	
South Lanarkshire Lanark	08 June 2020	NOx	CM10020067	17.0	2.5	1.0166	3.54	98.6
		NO		1.2	2.5	1.0547	3.50	
South Lanarkshire Uddingston	10 June 2020	NOx	CM10020068	-2.8	2.5	1.0728	3.50	100.8
		NO		-2.6	2.5	1.0714	3.50	

FIDAS analysers

Station	Date of audit	Analyser	Calculated	Uncertainty	Total flow ^₄	Uncertainty	Main flow	Uncertainty
		Serial no	ko⁵	%	l.min-1	%	l.min-1	%
South Lanarkshire Blantyre	09 June 2020	9750			4.48	2.2		2.2
South Lanarkshire Cambuslang	10 June 2020	8256			4.84	2.2		2.2
South Lanarkshire East Kilbride	09 June 2020	5557			5.31	2.2		2.2
South Lanarkshire Hamilton	10 June 2020	8258			4.56	2.2		2.2
South Lanarkshire Lanark	08 June 2020	6248			5.24	2.2		2.2
South Lanarkshire Raith Interchange	09 June 2020	8257			4.97	2.2		2.2
South Lanarkshire Rutherglen	09 June 2020	8140			4.85	2.2		2.2
South Lanarkshire Uddingston	10 June 2020	6247			4.71	2.2		2.2

ee.**ricardo**.com



CERTIFICATE OF CALIBRATION



Page 3 of 3

Date of issue:	28 July 2020
Certificate Number:	5089
Ricardo Energy & Environment ID:	ED11194/5089

The gaseous ambient analysers listed above have been tested for zero response, calibration factor, linearity and converter efficiency (NOx analysers) by documented methods. The factors have been calculated using certified gas standards. The particulate analysers listed above have been tested for sample flow rates and ko(where appropriate) by documented methods. Note that the test results are valid on the day of test only, as analyser drift over time cannot be quantified. All results for gaseous species are given in ppb (parts per billion) mole fractions.

¹ The zero response is the zero reading on the data logging system of the analyser when audit zero gas was introduced to the analysers under test.

² The calibration factor is the multiplying factor required to scale the reading on the data logging system of the analyser into reported concentration units (ppb for NO, NOx, SO₂, O₃ and ppm for CO. Where 1ppm = 1000ppb). It should be used in conjunction with the zero response. A corrected concentration is calculated using the following equation:

Concentration = F(Output - Zero Response)

Where F = Calibration Factor provided on this certificate Output = Reading on the data logging system of the analyser Zero Response = Zero Response provided on this certificate

³ Converter eff. is the measured efficiency of the NO₂ to NO converter within the oxides of nitrogen analyser under test.

⁴ The measured main flow rate (where this is applicable) is the flow rate through the sensor unit of the TEOM particulate analyser under test. The measured total flow rate is the total flow rate through the particulate analyser under test. Units of flow are l.min⁻¹, reported at prevailing ambient conditions unless otherwise specified. Where flow rates are highlighted in bold, it indicates that measurements were not made at the analyser sample inlet. These measurements therefore may not accurately reflect analyser performance in normal operation.

⁵ The calculated ko value (specifically for TEOM analysers) is the calculated ko spring constant based on tests undertaken with filters of known weight. The % deviation indicates the closeness of the calculated result to the manufacturer's specified value of ko.

The calibration results shaded are those that fall within our scope of accreditation, all other results on this certificate are not UKAS accredited, but have been included for completeness.

ee.ricardo.com