	CERTIFICATE OF CALIBRATION ardo Energy & Environment 18 Blythswood Square, Glasgow, G2 4BG Telephone 01235 753434
Approved Signatories:	Page 1 of 3 S. Eaton B Stacey D Hector S Stratton N Rand S S Telfer B Davies S Gray
Signed:	Stelfer
Date of issue:	02 July 2021
Certificate Number:	5486
Customer Name and Address:	Scottish Government Water, Air, Soils and Flooding Division Environmental Quality Directorate Scottish Government Victoria Quay Edinburgh EH6 6QQ
Description:	Calibration factors for the air monitoring station(s) at South Lanarkshire Council
Ricardo Energy & Environment ID:	ED11194/5486
level of confidence of approximately 95% The uncerta requirements. This certificate is issued in accordance with the labora Service. It provides traceability of measurement to th	standard uncertainty multiplied by a coverage factor k=2 providing a inty evaluation has been carried out in accordance with UKAS story accreditation requirements of the United Kingdom Accreditation e Si system of units and/or to units of measurement realised at the onal metrology institutes. This certificate may not be reproduced other the issuing laboratory
Ricardo Energy & Environment 18 Blythswood Square (2 nd Floor). Glasgow. G2 4BG Tel: 01235 753205	Registered office Shoreham Technical Centre Shoreham-by-Sea West Sussex BN43 6FG Registered in England No. 08229264 VAT Registration No. GB 212 8366 24 ee.ricardo.com



CERTIFICATE OF CALIBRATION



Page 2 of 3

Date of issue:	02 July 2021	
Certificate Number:	5486	
Ricardo Energy & Environment ID:	ED11194/5486	

South Lanarkshire Council NOx analysers

Station	Date of Audit	Species	Analyser Serial no	Zero Response ¹	Zero uncertainty ppb	Calibration Factor ²	Factor uncertainty %	Converter eff. $(\%)^3$
South Lanarkshire Blantyre	08 July 2021	NOx	18-0740	-2.0	2.7	1.1309	3.50	100.0
		NO		0.0	2.7	1.1198	3.50	
South Lanarkshire Cambuslang	22 June 2021	NOx	1152590008	0.1	2.5	0.8709	3.55	99.5
		NO		0.0	2.5	0.8757	3.50	
South Lanarkshire East Kilbride	24 June 2021	NOx	CM07460075	0.9	2.5	1.0131	3.50	98.3
		NO		1.2	2.5	1.0137	3.50	
South Lanarkshire Hamilton	22 June 2021	NOx	CM07460073	-0.8	2.5	0.9896	3.50	100.0
		NO		-0.2	2.5	0.9974	3.50	
South Lanarkshire Lanark	24 June 2021	NOx	CM10020067	0.5	2.5	0.9337	3.50	98.2
		NO		0.1	2.5	0.9406	3.50	
South Lanarkshire Raith Interchange 2	08 July 2021	NOx	cm07460076	-2.3	2.5	1.0449	3.50	99.1
		NO		0.4	2.5	1.0466	3.50	
South Lanarkshire Rutherglen	09 July 2021	NOx	cm01220001	-9.9	2.6	1.1039	3.50	98.3
		NO		0.0	2.6	1.1036	3.50	
South Lanarkshire Uddingston	22 June 2021	NOx	CM10020068	-0.8	2.7	0.9109	3.50	101.1
		NO		0.0	2.5	0.9142	3.50	

PM10 analysers

Station	Date of audit	Analyser Serial no	Calculated ko⁵	Uncertainty %	Total flow ^₄	Uncertainty %	Main flow	Uncertainty %
South Lanarkshire Blantyre	08 July 2021	9750			4.77	2.2		2.2
South Lanarkshire Cambuslang	22 June 2021	8256			4.90	2.2		2.2
South Lanarkshire East Kilbride	24 June 2021	8257			4.95	2.2		2.2
South Lanarkshire Hamilton	22 June 2021	8258			5.01	2.2		2.2
South Lanarkshire Lanark	24 June 2021	6248			4.78	2.2		2.2
South Lanarkshire Raith Interchange 2	08 July 2021	9719			4.91	2.2		2.2
South Lanarkshire Rutherglen	09 July 2021	8140			4.68	2.2		2.2
South Lanarkshire Uddingston	22 June 2021	6247			4.86	2.2		2.2

ee.**ricardo**.com



CERTIFICATE OF CALIBRATION



Page 3 of 3

Date of issue:

Certificate Number:

Ricardo Energy & Environment ID:

ED11194/5486

02 July 2021

5486

The gaseous ambient analysers listed above have been tested for zero response, calibration factor, linearity and converter efficiency (NOx analysers) by documented methods. The factors have been calculated using certified gas standards. The particulate analysers listed above have been tested for sample flow rates and ko(where appropriate) by documented methods. Note that the test results are valid on the day of test only, as analyser drift over time cannot be quantified. All results for gaseous species are given in ppb (parts per billion) mole fractions.

¹ The zero response is the zero reading on the data logging system of the analyser when audit zero gas was introduced to the analysers under test.

² The calibration factor is the multiplying factor required to scale the reading on the data logging system of the analyser into reported concentration units (ppb for NO, NOx, SO₂, O₃ and ppm for CO. Where 1ppm = 1000ppb). It should be used in conjunction with the zero response. A corrected concentration is calculated using the following equation:

Concentration = F(Output - Zero Response)

Where F = Calibration Factor provided on this certificate Output = Reading on the data logging system of the analyser Zero Response = Zero Response provided on this certificate

³ Converter eff. is the measured efficiency of the NO₂ to NO converter within the oxides of nitrogen analyser under test.

⁴ The measured main flow rate (where this is applicable) is the flow rate through the sensor unit of the TEOM particulate analyser under test. The measured total flow rate is the total flow rate through the particulate analyser under test. Units of flow are l.min⁻¹, reported at prevailing ambient conditions unless otherwise specified. Where flow rates are highlighted in bold, it indicates that measurements were not made at the analyser sample inlet. These measurements therefore may not accurately reflect analyser performance in normal operation.

⁵ The calculated ko value (specifically for TEOM analysers) is the calculated ko spring constant based on tests undertaken with filters of known weight. The % deviation indicates the closeness of the calculated result to the manufacturer's specified value of ko.

The calibration results shaded are those that fall within our scope of accreditation, all other results on this certificate are not UKAS accredited, but have been included for completeness.

ee.ricardo.com