

# **CERTIFICATE OF CALIBRATION**

Ricardo Energy and Environment, Gemini Building, Fermi Avenue Harwell, Didcot, Oxfordshire OX11 0QR. Telephone 01235 753692



Page 1 of 3

Approved Signatories:			S. Eaton D Hector N Rand E Marshall- Padkin B Davies	<ul> <li>B Stacey</li> <li>S Stratton</li> <li>S Telfer</li> <li>S Gray</li> </ul>
Signed:	Al Ca			
Date of issue:	25 Apr 18			
Certificate Number:	3918			
Customer Name and Address:	W En Sc Vid Ed	ottish Governme ater, Air, Soils an vironmental Qua ottish Governme ctoria Quay inburgh I6 6QQ	d Flooding Division lity Directorate	
Description:		Calibration fact Aberdeen City	ors for the air moni Council	toring stations at
Ricardo Energy & Environment ID:		ED61598/3918		
The reported expanded uncertaint level of confidence of approximate requirements. This certificate is issued in accordan Service. It provides traceability of r	ely 95% The uncertaint	y evaluation has y accreditation	s been carried out in requirements of the	accordance with UKAS United Kingdom Accreditatio

This certificate is issued in accordance with the laboratory accreditation requirements of the United Kingdom Accreditation Service. It provides traceability of measurement to the SI system of units and/or to units of measurement realised at the National Physical Laboratory or other recognised national metrology institutes. This certificate may not be reproduced other than in full, except with the prior written approval of the issuing laboratory

Ricardo Energy & Environment Head Office Gemini Building, Fermi Avenue, Harwell, Oxon Registered office Shoreham Technical Centre Shoreham-by-Sea West Sussex BN43 5FG

5FG

OX11 0QR

Tel: +44 (0)1235 753 000

Registered in England No. 08229264

VAT Registration No. GB 212 8365 24



ee.ricardo.com

**CERTIFICATE OF CALIBRATION** 





Page 2 of 3

Date of issue:	25 Apr 18
Certificate Number:	3918
Ricardo Energy & Environment ID:	ED61598/3918

## Aberdeen City Council

#### NOx analysers

Station	Date of Audit	Species	Analyser Serial no	Zero Response <sup>1</sup>	Zero uncertainty ppb	Calibration Factor <sup>2</sup>	Factor uncertainty %	Converter eff. (%) <sup>3</sup>
Aberdeen Anderson Drive	02 Aug 17	NOx	697	3.7	2.6	1.2084	3.50	99.2
		NO		2.1	2.6	1.1953	3.50	
Aberdeen King Street	03 Aug 17	NOx	2640	10.5	2.5	1.0560	3.50	100.8
		NO		5.9	2.5	1.0662	3.50	
Aberdeen Market Street	03 Aug 17	NOx	3507	-7.8	2.5	0.9741	3.50	104.8
		NO		-3.4	2.5	0.9978	3.50	

#### PM10 analysers

Station	Date of audit	Analyser Serial no	Calculated ko	Uncertainty %	Total flow	Uncertainty %	Main flow	Uncertainty %
Aberdeen Anderson Drive	02 Aug 17	24832	13475	1.0	16.41	2.2	3.15	2.2
Aberdeen King Street	03 Aug 17	8374			4.58	2.2		2.2
Aberdeen Market Street	03 Aug 17	6653			4.64	2.2		2.2
Aberdeen Union Street	03 Aug 17	1405A227711402	16813	1.0	15.00	2.2	4.75	2.2
Aberdeen Wellington Road	02 Aug 17	7451			4.18	2.2		2.2

### PM2.5 analysers

Station	Date of audit	Analyser Serial no	Calculated ko	Uncertainty %	Total flow	Uncertainty %	Main flow	Uncertainty %
Aberdeen Union Street	03 Aug 17	1405A227711402	15654	1.0	15.00	2.2	4.75	2.2



ee.ricardo.com



## **CERTIFICATE OF CALIBRATION**



Page 3 of 3

Date of issue:	25 Apr 18
Certificate Number:	3918
Ricardo Energy & Environment ID:	ED61598/3918

The gaseous ambient analysers listed above have been tested for zero response, calibration factor, linearity and converter efficiency (NOx analysers) by documented methods. The factors have been calculated using certified gas standards. The particulate analysers listed above have been tested for sample flow rates and ko(where appropriate) by documented methods. Note that the test results are valid on the day of test only, as analyser drift over time cannot be quantified. All results for gaseous species are given in ppb (parts per billion) mole fractions or ppm (parts per million) mole fractions.

<sup>1</sup> The zero response is the zero reading on the data logging system of the analyser when audit zero gas was introduced to the analysers under test.

<sup>2</sup> The calibration factor is the multiplying factor required to scale the reading on the data logging system of the analyser into reported concentration units (ppb for NO, NOx, SO<sub>2</sub>, O<sub>3</sub> and ppm for CO. Where 1ppm = 1000ppb). It should be used in conjunction with the zero response. A corrected concentration is calculated using the following equation:

Concentration = F(Output - Zero Response)

Where F = Calibration Factor provided on this certificate

Output = Reading on the data logging system of the analyser

Zero Response = Zero Response provided on this certificate

<sup>3</sup> Converter eff. is the measured efficiency of the NO<sub>2</sub> to NO converter within the oxides of nitrogen analyser under test.

<sup>4</sup> The measured main flow rate (where this is applicable) is the flow rate through the sensor unit of the TEOM particulate analyser under test. The measured total flow rate is the total flow rate through the particulate analyser under test. Units of flow are l.min<sup>-1</sup>, reported at prevailing ambient conditions unless otherwise specified. Where flow rates are highlighted in bold, it indicates that measurements were not made at the analyser sample inlet. These measurements therefore may not accurately reflect analyser performance in normal operation.

<sup>5</sup> The calculated ko value (specifically for TEOM analysers) is the calculated ko spring constant based on tests undertaken with filters of known weight. The % deviation indicates the closeness of the calculated result to the manufacturer's specified value of ko.

The calibration results shaded are those that fall within our scope of accreditation, all other results on this certificate are not UKAS accredited, but have been included for completeness.



