

CERTIFICATE OF CALIBRATION

Ricardo Energy and Environment, Gemini Building, Fermi Avenue Harwell, Didcot, Oxfordshire OX11 0QR. Telephone 01235 753692



Page 1 of 3

| Approved Signatories: | | | S. Eaton D Hector N Rand E Marshall- Padkin B Davies | ☐ B Stacey ☐ S Stratton ☐ S Telfer ☑ S Gray |
|----------------------------|----------------|--|--|--|
| Signed: | <i>M</i> 1 (2) | | | |
| Date of issue: | 26 Apr 18 | | | |
| Certificate Number: | 3942 | | | |
| Customer Name and Address: | | Soils and Floo ntal Quality Di overnment | | |
| Description: | | Calibration fa | ctors for the air monit | toring stations at |
| | | | | |

level of confidence of approximately 95% The uncertainty evaluation has been carried out in accordance with UKAS requirements.

This certificate is issued in accordance with the laboratory accreditation requirements of the United Kingdom Accreditation Service. It provides traceability of measurement to the SI system of units and/or to units of measurement realised at the National Physical Laboratory or other recognised national metrology institutes. This certificate may not be reproduced other than in full, except with the prior written approval of the issuing laboratory

Ricardo Energy & Environment

Head Office Gemini Building, Fermi Avenue, Harwell, Oxon OX11 0QR

Tel: +44 (0)1235 753 000

Registered office

Shoreham Technical Centre Shoreham-by-Sea West Sussex

Registered in England No. 08229264

VAT Registration No. GB 212 8365 24



CERTIFICATE OF CALIBRATION



Page 2 of 3

Date of issue: 26 Apr 18

Certificate Number: 3942

Ricardo Energy & Environment ID: ED61598/3942

Aberdeen City Council

NOx analysers

| NOX dilalyseis | | | | | | | | |
|-------------------------|---------------|---------|-----------------------|----------------------------|----------------------------|------------------------------------|----------------------------|---------------------------------|
| Station | Date of Audit | Species | Analyser Serial no | Zero Response ¹ | Zero uncertainty ppb | Calibration Factor ² | Factor uncertainty % | Converter eff. (%) ³ |
| Aberdeen Anderson Drive | 20 Feb 18 | NOx | 697 | 1.6 | 2.6 | 1.0860 | 3.50 | 87.5 |
| | | NO | | 0.4 | 2.6 | 1.0996 | 3.50 | |
| Aberdeen King St | 20 Feb 18 | NOx | 2640 | 2.9 | 2.7 | 1.3728 | 3.50 | 100.0 |
| | | NO | | 1.2 | 2.7 | 1.3533 | 3.50 | |
| Aberdeen Market Street | 22 Feb 18 | NOx | 3507 | -1.2 | 2.5 | 1.0004 | 3.50 | 100.7 |
| | | NO | | -2.5 | 2.5 | 1.0058 | 3.50 | |

PM10 analysers

| Station | Date of audit | Analyser Serial no | Calculated ko | Uncertainty % | Total flow | Uncertaint y % | Main flow | Uncertaint y % |
|-------------------------|---------------|--------------------|---------------|---------------|------------|-------------------|-----------|-------------------|
| Aberdeen Anderson Drive | 20 Feb 18 | 24832 | 13091 | 1.0 | 16.69 | 2.2 | 3.07 | 2.2 |
| Aberdeen King St | 20 Feb 18 | 8374 | | | 4.59 | 2.2 | | 2.2 |
| Aberdeen Market Street | 22 Feb 18 | 6653 | | | 4.68 | 2.2 | | 2.2 |
| Aberdeen Union Street | 20 Feb 18 | 145AA227711402 | 16872 | 1.0 | 15.22 | 2.2 | 4.31 | 2.2 |

PM2.5 analysers

| Station | Date of audit | Analyser Serial no | Calculated ko | Uncertainty % | Total flow | Uncertaint y % | Main flow | Uncertaint y % |
|-----------------------|---------------|--------------------|---------------|---------------|------------|-------------------|-----------|-------------------|
| Aberdeen Union Street | 20 Feb 18 | 145AA227711402 | 15506 | 1.0 | 15.22 | 2.2 | 4.31 | 2.2 |



CERTIFICATE OF CALIBRATION



Page 3 of 3

| Date of issue: | 26 Apr 18 |
|----------------|-----------|

Certificate Number: 3942

Ricardo Energy & Environment ID: ED61598/3942

The gaseous ambient analysers listed above have been tested for zero response, calibration factor, linearity and converter efficiency (NOx analysers) by documented methods. The factors have been calculated using certified gas standards. The particulate analysers listed above have been tested for sample flow rates and ko (where appropriate) by documented methods. Note that the test results are valid on the day of test only, as analyser drift over time cannot be quantified. All results for gaseous species are given in ppb (parts per billion) mole fractions or ppm (parts per million) mole fractions.

- ¹ The zero response is the zero reading on the data logging system of the analyser when audit zero gas was introduced to the analysers under test.
- ² The calibration factor is the multiplying factor required to scale the reading on the data logging system of the analyser into reported concentration units (ppb for NO, NOx, SO₂, O₃ and ppm for CO. Where 1ppm = 1000ppb). It should be used in conjunction with the zero response. A corrected concentration is calculated using the following equation:

Concentration = F(Output - Zero Response)

Where F = Calibration Factor provided on this certificate

Output = Reading on the data logging system of the analyser

Zero Response = Zero Response provided on this certificate

- ³ Converter eff. is the measured efficiency of the NO₂ to NO converter within the oxides of nitrogen analyser under test.
- ⁴ The measured main flow rate (where this is applicable) is the flow rate through the sensor unit of the TEOM particulate analyser under test. The measured total flow rate is the total flow rate through the particulate analyser under test. Units of flow are l.min⁻¹, reported at prevailing ambient conditions unless otherwise specified. Where flow rates are highlighted in bold, it indicates that measurements were not made at the analyser sample inlet. These measurements therefore may not accurately reflect analyser performance in normal operation.
- ⁵ The calculated k₀ value (specifically for TEOM analysers) is the calculated k₀ spring constant based on tests undertaken with filters of known weight. The % deviation indicates the closeness of the calculated result to the manufacturer's specified value of k₀.

The calibration results shaded are those that fall within our scope of accreditation, all other results on this certificate are not UKAS accredited, but have been included for completeness.