

CERTIFICATE OF CALIBRATION

Ricardo Energy and Environment, Gemini Building, Fermi Avenue Harwell, Didcot, Oxfordshire OX11 OQR. Telephone 01235 753692



Page 1 of 3

Approved Signatories:			S. Eaton D Hector N Rand E Marshall- Padkin B Davies	□ B Stacey□ S Stratton□ S Telfer☑ S Gray
Signed: Date of issue:	25 Apr 18			
Certificate Number:	3921			
Customer Name and Address:	Water, Enviro Scottis	nmental Qua h Governmei a Quay irgh	d Flooding Division lity Directorate	
Description:		bration fact dee City Co		nitoring stations at
Ricardo Energy & Environment ID:	ED6	1598/3921		

The reported expanded uncertainties are based on a standard uncertainty multiplied by a coverage factor k=2 providing a level of confidence of approximately 95% The uncertainty evaluation has been carried out in accordance with UKAS requirements.

This certificate is issued in accordance with the laboratory accreditation requirements of the United Kingdom Accreditation Service. It provides traceability of measurement to the SI system of units and/or to units of measurement realised at the National Physical Laboratory or other recognised national metrology institutes. This certificate may not be reproduced other than in full, except with the prior written approval of the issuing laboratory

Ricardo Energy & Environment

Head Office Gemini Building, Fermi Avenue, Harwell, Oxon OX11 0QR

Tel: +44 (0)1235 753 000

Registered office

Shoreham Technical Centre Shoreham-by-Sea West Sussex BN43 5FG

Registered in England No.

VAT Registration No.

GB 212 8365 24



CERTIFICATE OF CALIBRATION



Page 2 of 3

Date of issue: 25 Apr 18

Certificate Number: 3921

Ricardo Energy & Environment ID: ED61598/3921

Dundee City Council

NOx analysers

NOX analysers								
Station	Date of Audit	Species	Analyser Serial no	Zero Response ¹	Zero uncertainty ppb	Calibration Factor ²	Factor uncertainty %	Converter eff. (%) ³
Dundee Broughty Ferry Road	19-Jul-17	NOx	607	3.8	2.6	1.0917	3.50	100.0
		NO		1.7	2.5	1.0767	3.50	
Dundee Lochee Road	28-Aug-17	NOx	727	25.4	2.5	1.0209	3.50	100.9
		NO		25.3	2.5	1.0162	3.50	
Dundee Mains Loan	08-Aug-17	NOx	cm10490031	8.5	2.4	0.7756	4.03	97.4
		NO		4.2	2.4	0.7731	3.94	
Dundee Meadowside	21-Jul-17	NOx	2211692	3.0	2.5	1.0690	3.50	102.0
		NO		0.0	2.5	1.0616	3.50	
Dundee Seagate	20-Jul-17	NOx	726	9.8	2.5	1.0622	3.50	101.3
		NO		8.4	2.5	1.0581	3.50	
Dundee Whitehall Street	20-Jul-17	NOx	725	13.8	2.6	1.0830	3.50	98.9
		NO		12.5	2.6	1.0890	3.50	

PM10 analysers

1 IVIIO dilalyseis								
Station	Date of audit	Analyser Serial no	Calculated ko	Uncertainty %	Total flow	Uncertainty %	Main flow	Uncertainty %
Dundee Broughty Ferry Road	19-Jul-17	23739	15400	1.0	15.61	2.2	2.70	2.2
Dundee Lochee Road	28-Aug-17	m2080			16.04	2.2		2.2
Dundee Mains Loan	08-Aug-17	25750	13430	1.0	16.71	2.2	3.04	2.2
Dundee Meadowside	21-Jul-17	m2079			9.53	2.2		2.2
Dundee Seagate	20-Jul-17	m2816			14.28	2.2		2.2
Dundee Whitehall Street	20-Jul-17	N14537			16.92	2.2		2.2



CERTIFICATE OF CALIBRATION



Page 3 of 3

Date of issue:	25 Apr 18

Certificate Number: 3921

Ricardo Energy & Environment ID: ED61598/3921

The gaseous ambient analysers listed above have been tested for zero response, calibration factor, linearity and converter efficiency (NOx analysers) by documented methods. The factors have been calculated using certified gas standards. The particulate analysers listed above have been tested for sample flow rates and ko(where appropriate) by documented methods. Note that the test results are valid on the day of test only, as analyser drift over time cannot be quantified. All results for gaseous species are given in ppb (parts per billion) mole fractions or ppm (parts per million) mole fractions.

- ¹ The zero response is the zero reading on the data logging system of the analyser when audit zero gas was introduced to the analysers under test.
- ² The calibration factor is the multiplying factor required to scale the reading on the data logging system of the analyser into reported concentration units (ppb for NO, NOx, SO₂, O₃ and ppm for CO. Where 1ppm = 1000ppb). It should be used in conjunction with the zero response. A corrected concentration is calculated using the following equation:

Concentration = F(Output - Zero Response)

Where F = Calibration Factor provided on this certificate

Output = Reading on the data logging system of the analyser

Zero Response = Zero Response provided on this certificate

- ³ Converter eff. is the measured efficiency of the NO₂ to NO converter within the oxides of nitrogen analyser under test.
- ⁴ The measured main flow rate (where this is applicable) is the flow rate through the sensor unit of the TEOM particulate analyser under test. The measured total flow rate is the total flow rate through the particulate analyser under test. Units of flow are l.min⁻¹, reported at prevailing ambient conditions unless otherwise specified. Where flow rates are highlighted in bold, it indicates that measurements were not made at the analyser sample inlet. These measurements therefore may not accurately reflect analyser performance in normal operation.
- ⁵ The calculated k₀ value (specifically for TEOM analysers) is the calculated k₀ spring constant based on tests undertaken with filters of known weight. The % deviation indicates the closeness of the calculated result to the manufacturer's specified value of k₀.

The calibration results shaded are those that fall within our scope of accreditation, all other results on this certificate are not UKAS accredited, but have been included for completeness.