

CERTIFICATE OF CALIBRATION

Ricardo Energy and Environment, Gemini Building, Fermi Avenue Harwell, Didcot, Oxfordshire OX11 OQR. Telephone 01235 753692



Page 1 of 3

Approved Signatories:			S. Eaton D Hector N Rand E Marshall- Padkin B Davies	□ B Stacey□ S Stratton□ S Telfer☑ S Gray			
Signed:	Agrico.						
Date of issue:	26 Apr 18						
Certificate Number:	3945						
Customer Name and Address:	\ E S \ E	Scottish Government Water, Air, Soils and Flooding Division Environmental Quality Directorate Scottish Government Victoria Quay Edinburgh EH6 6QQ					
Description:		Calibration factors for the air monitoring stations at Dundee City Council					
Ricardo Energy & Environment ID:		ED61598/3945					
level of confidence of approx requirements. This certificate is issued in ac Service. It provides traceabili	imately 95% The uncert cordance with the labor ity of measurement to th	rainty evaluation ha ratory accreditation he SI system of uni	as been carried out in n requirements of the ts and/or to units of r	e United Kingdom Accreditation			

Ricardo Energy & Environment

Head Office Gemini Building, Fermi Avenue, Harwell, Oxon OX11 0QR

Tel: +44 (0)1235 753 000

Registered office

Shoreham Technical Centre Shoreham-by-Sea West Sussex BN43 5FG

Registered in England No. 08229264

than in full, except with the prior written approval of the issuing laboratory

VAT Registration No. GB 212 8365 24



CERTIFICATE OF CALIBRATION



Page 2 of 3

Date of issue: 26 Apr 18

Certificate Number: 3945

Ricardo Energy & Environment ID: ED61598/3945

Dundee City Council

NOx analysers

NOX alialysels								
Station	Date of Audit	Species	Analyser Serial no	Zero Response ¹	Zero uncertainty ppb	Calibration Factor ²	Factor uncertainty %	Converter eff. (%) ³
Dundee Broughty Ferry Road	12-Dec-17	NOx	607	2.3	2.6	1.2034	3.50	100.0
		NO		1.9	2.6	1.1871	3.50	
Dundee Lochee Road	12-Dec-17	NOx	727	6.1	2.6	1.1781	3.50	101.4
		NO		3.5	2.6	1.1533	3.50	
Dundee Meadowside	13-Dec-17	NOx	2211692	2.0	2.6	1.1135	3.50	98.1
		NO		0.0	2.8	1.1124	3.50	
Dundee Seagate	13-Dec-17	NOx	726	10.1	2.6	1.2395	3.50	98.4
		NO		8.4	2.6	1.2106	3.50	
Dundee Whitehall Street	12-Dec-17	NOx	725	15.7	2.6	1.2111	3.50	97.9
		NO		12.9	2.6	1.2094	3.50	

PM10 analysers

I WITO dilalysers								
Station	Date of audit	Analyser Serial no	Calculated ko	Uncertainty %	Total flow	Uncertainty %	Main flow	Uncertainty %
Dundee Broughty Ferry Road	25-Jan-18	23739	15123	1.0	17.05	2.2	3.03	2.2
Dundee Lochee Road	25-Jan-18	M2080			15.47	2.2		2.2
Dundee Mains Loan	02-Nov-17	8379			4.81	2.2		2.2
Dundee Meadowside	25-Jan-18	M2079			15.68	2.2		2.2
Dundee Seagate	25-Jan-18	M2816			16.22	2.2		2.2
Dundee Whitehall Street	25-Jan-18	14537			16.49	2.2		2.2



CERTIFICATE OF CALIBRATION



Page 3 of 3

Date of issue:	26 Apr 18
----------------	-----------

Certificate Number: 3945

Ricardo Energy & Environment ID: ED61598/3945

The gaseous ambient analysers listed above have been tested for zero response, calibration factor, linearity and converter efficiency (NOx analysers) by documented methods. The factors have been calculated using certified gas standards. The particulate analysers listed above have been tested for sample flow rates and ko(where appropriate) by documented methods. Note that the test results are valid on the day of test only, as analyser drift over time cannot be quantified. All results for gaseous species are given in ppb (parts per billion) mole fractions or ppm (parts per million) mole fractions.

- ¹ The zero response is the zero reading on the data logging system of the analyser when audit zero gas was introduced to the analysers under test.
- ² The calibration factor is the multiplying factor required to scale the reading on the data logging system of the analyser into reported concentration units (ppb for NO, NOx, SO₂, O₃ and ppm for CO. Where 1ppm = 1000ppb). It should be used in conjunction with the zero response. A corrected concentration is calculated using the following equation:

Concentration = F(Output - Zero Response)

Where F = Calibration Factor provided on this certificate

Output = Reading on the data logging system of the analyser

Zero Response = Zero Response provided on this certificate

- ³ Converter eff. is the measured efficiency of the NO₂ to NO converter within the oxides of nitrogen analyser under test.
- ⁴ The measured main flow rate (where this is applicable) is the flow rate through the sensor unit of the TEOM particulate analyser under test. The measured total flow rate is the total flow rate through the particulate analyser under test. Units of flow are l.min⁻¹, reported at prevailing ambient conditions unless otherwise specified. Where flow rates are highlighted in bold, it indicates that measurements were not made at the analyser sample inlet. These measurements therefore may not accurately reflect analyser performance in normal operation.
- ⁵ The calculated k₀ value (specifically for TEOM analysers) is the calculated k₀ spring constant based on tests undertaken with filters of known weight. The % deviation indicates the closeness of the calculated result to the manufacturer's specified value of k₀.

The calibration results shaded are those that fall within our scope of accreditation, all other results on this certificate are not UKAS accredited, but have been included for completeness.