

## **CERTIFICATE OF CALIBRATION**

Ricardo Energy and Environment, Gemini Building, Fermi Avenue Harwell, Didcot, Oxfordshire OX11 0QR. Telephone 01235 753692



Page 1 of 3

Appro	oved Signatories:			S. Eaton D Hector N Rand B Davies			B Stacey S Stratton S Telfer S Gray	
Signe	ed:	Stelker						
Date	of issue:	27 May 20						
Certif	icate Number:	4975						
Custo	omer Name and Address:			Soils and Floodin ntal Quality Directory		on		
Desci	ription:	Calibration factors for the air monitoring station(s) at Dundee City Council						
Ricar	do Energy & Environment ID:	ED11194 / 4975						
	The reported expanded uncertainties are based on level of confidence of approximately 95% The uncerequirements.  This certificate is issued in accordance with the lab Service. It provides traceability of measurement to National Physical Laboratory or other recognised of than in full, except with the prior written approval	been carried out in equirements of the and/or to units of tutes. This certific	n accordance with UKAS e United Kingdom Accre measurement realised a	editation at the				

Ricardo Energy & Environment

18 Blythswood Square (2<sup>nd</sup> Floor), Glasgow, G2 4BG

Tel: 01235 753205

Registered office Shoreham Technical Centre Shoreham-by-Sea West Sussex BN43 5FG

Registered in England No. 08229264

VAT Registration No. GB 212 8365 24



# **CERTIFICATE OF CALIBRATION**



Page 2 of 3

Date of issue: 27 May 20

Certificate Number: 4975

Ricardo Energy & Environment ID: ED11194 / 4975

#### Dundee City Council NOx analysers

Station	Date of Audit	Species	Analyser Serial no	Zero Response <sup>1</sup>	Zero uncertainty ppb	Calibration Factor <sup>2</sup>	Factor uncertainty %	Converter eff. (%) <sup>3</sup>
Dundee Broughty Ferry Road	16-Dec	NOx	607	3.1	2.6	1.1101	3.50	98.5
		NO		2.1	2.6	1.1307	3.50	
Dundee Lochee Road	16-Dec	NOx	727	2.7	2.5	1.0497	3.50	98.2
		NO		1.0	2.5	1.0645	3.50	
Dundee Meadowside	17-Dec	NOx	2211692	4.0	2.6	1.1394	3.50	99.1
		NO		1.0	2.6	1.1206	3.64	
Dundee Seagate	17-Dec	NOx	726	13.6	2.6	1.1198	3.50	97.3
		NO		8.9	2.6	1.1264	3.50	
Dundee Whitehall Street	17-Dec	NOx	725	-3.3	2.5	1.0642	3.50	82.6
		NO		0.1	2.6	1.1340	3.50	

#### PM10 analysers

Station	Date of audit	Analyser Serial no	Calculated ko	Uncertainty %	Total flow	Uncertainty %	Main flow	Uncertainty %
Dundee Broughty Ferry Road	16-Dec	1200C184890506	13044	1.0	15.36	2.2	2.60	2.2
Dundee Lochee Road	16-Dec	8732			4.41	2.2		2.2
Dundee Mains Loan	25-Feb	8379			4.60	2.2		2.2
Dundee Meadowside	17-Dec	10883			4.47	2.2		2.2
Dundee Seagate	17-Dec	10881			4.58	2.2		2.2
Dundee Whitehall Street	17-Dec	10882			4.57	2.2		2.2

#### PM2.5 analysers

Station	Date of audit	Analyser Serial no	Calculated ko Uncertainty %	Total flow	Uncertainty %	Main flow	Uncertainty %
Dundee Lochee Road	16-Dec	8732		4.41	2.2		2.2
Dundee Mains Loan	25-Feb	8379		4.60	2.2		2.2
Dundee Meadowside	17-Dec	10883		4.47	2.2		2.2
Dundee Seagate	17-Dec	10881		4.58	2.2		2.2
Dundee Whitehall Street	17-Dec	10882		4.57	2.2		2.2

ee.**ricardo**.com



### **CERTIFICATE OF CALIBRATION**



Page 3 of 3

Date of issue: 27 May 20

Certificate Number: 4975

Ricardo Energy & Environment ID: ED11194 / 4975

The gaseous ambient analysers listed above have been tested for zero response, calibration factor, linearity and converter efficiency (NOx analysers) by documented methods. The factors have been calculated using certified gas standards. The particulate analysers listed above have been tested for sample flow rates and ko(where appropriate) by documented methods. Note that the test results are valid on the day of test only, as analyser drift over time cannot be quantified. All results for gaseous species are given in ppb (parts per billion) mole fractions or ppm (parts per million) mole fractions.

Concentration = F(Output - Zero Response)

Where F = Calibration Factor provided on this certificate

Output = Reading on the data logging system of the analyser

Zero Response = Zero Response provided on this certificate

The calibration results shaded are those that fall within our scope of accreditation, all other results on this certificate are not UKAS accredited, but have been included for completeness.

<sup>&</sup>lt;sup>1</sup> The zero response is the zero reading on the data logging system of the analyser when audit zero gas was introduced to the analysers under test.

<sup>&</sup>lt;sup>2</sup> The calibration factor is the multiplying factor required to scale the reading on the data logging system of the analyser into reported concentration units (ppb for NO, NOx, SO<sub>2</sub>, O<sub>3</sub> and ppm for CO. Where 1ppm = 1000ppb). It should be used in conjunction with the zero response. A corrected concentration is calculated using the following equation:

<sup>&</sup>lt;sup>3</sup> Converter eff. is the measured efficiency of the NO<sub>2</sub> to NO converter within the oxides of nitrogen analyser under test.

<sup>&</sup>lt;sup>4</sup> The measured main flow rate (where this is applicable) is the flow rate through the sensor unit of the TEOM particulate analyser under test. The measured total flow rate is the total flow rate through the particulate analyser under test. Units of flow are l.min<sup>-1</sup>, reported at prevailing ambient conditions unless otherwise specified. Where flow rates are highlighted in bold, it indicates that measurements were not made at the analyser sample inlet. These measurements therefore may not accurately reflect analyser performance in normal operation.

<sup>&</sup>lt;sup>5</sup> The calculated ko value (specifically for TEOM analysers) is the calculated ko spring constant based on tests undertaken with filters of known weight. The % deviation indicates the closeness of the calculated result to the manufacturer's specified value of ko.