

CERTIFICATE OF CALIBRATION

Ricardo Energy and Environment, Gemini Building, Fermi Avenue Harwell, Didcot, Oxfordshire OX11 OQR. Telephone 01235 753692



Page 1 of 3

Approved Signatories:		☐ S. Eaton ☐ D Hector ☐ N Rand ☐ B Davies	☐ B Stacey ☐ S Stratton ☐ S Telfer ☑ S Gray
Signed:	Step 6	_	
Date of issue: Certificate Number:	29 Apr 19 4473		
Customer Name and Address:		Scottish Government Water, Air, Soils and Flooding Divi Environmental Quality Directorate Scottish Government Victoria Quay Edinburgh EH6 6QQ	
Description:		Calibration factors for the air r East Dunbartonshire Council	monitoring station(s) at
Ricardo Energy & Environment ID:		ED61598/4473	
The reported expanded uncertainties are based on level of confidence of approximately 95% The unce requirements. This certificate is issued in accordance with the lab Service. It provides traceability of measurement to National Physical Laboratory or other recognised in than in full, except with the prior written approval	ortainty evaluation has been oratory accreditation requing the SI system of units and/ational metrology institutes	carried out in accordance with UKAS rements of the United Kingdom Accreditatic or to units of measurement realised at the	on
Ricardo Energy & Environment Head Office Gemini Building, Fermi Avenue, Harwell, Oxon OX11 0QR Tel: +44 (0)1235 753 000	Registered office Shoreham Technic Shoreham Horen S	nical Centre Ingland No.	

ee.**ricardo**.com



CERTIFICATE OF CALIBRATION



Page 2 of 3

Date of issue: 29 Apr 19

Certificate Number: 4473

Ricardo Energy & Environment ID: ED61598/4473

East Dunbartonshire Council

NOx analysers

Tron analysers								
Station	Date of Audit	Species	Analyser Serial no	Zero Response ¹	Zero uncertainty ppb	Calibration Factor ²	Factor uncertainty %	Converter eff. (%) ³
East Dunbartonshire Bearsden	12-Dec-18	NOx	YEPTA800	-0.5	2.5	1.0244	3.52	98.6
		NO		-2.5	2.5	1.0278	3.57	
East Dunbartonshire Bishopbriggs	12-Dec-18	NOx	B8BVW9XY	-1.0	2.6	1.0789	3.67	99.6
		NO		-3.5	2.6	1.0838	3.60	
East Dunbartonshire Kirkintilloch	12-Dec-18	NOx	CM07010003	-0.6	2.5	1.0232	3.63	99.6
		NO		-0.2	2.5	1.0084	3.58	
East Dunbartonshire Milngavie	13-Dec-18	NOx	CM10020066	-1.3	2.6	1.0871	3.50	98.6
		NO		-0.1	2.6	1.0831	3.50	

PM10 analysers

Station	Date of audit	Analyser Serial no	Calculated ko	Uncertainty %	Total flow	Uncertainty %	Main flow	Uncertainty %
East Dunbartonshire Bearsden	12-Dec-18	EDC000239			16.42	2.2		2.2
East Dunbartonshire Bishopbriggs	12-Dec-18	EDC000248			15.86	2.2		2.2
East Dunbartonshire Kirkintilloch	12-Dec-18	8150			4.67	2.2		2.2
East Dunbartonshire Milngavie	13-Dec-18	1200C204311001	15186	1.0	16.27	2.2	3.01	2.2

PM2.5 analysers

Station	Date of audit	Analyser Serial no	Calculated ko	Uncertainty %	Total flow	Uncertainty %	Main flow	Uncertainty %
East Dunbartonshire Kirkintilloch	12-Dec	8150			4.67	2.2		2.2

ee.**ricardo**.com



CERTIFICATE OF CALIBRATION



Page 3 of 3

Date of issue:

29 Apr 19

- ¹ The zero response is the zero reading on the data logging system of the analyser when audit zero gas was introduced to the analysers under test.
- ² The calibration factor is the multiplying factor required to scale the reading on the data logging system of the analyser into reported concentration units (ppb for NO, NOx, SO2, O3 and ppm for CO. Where 1ppm = 1000ppb). It should be used in conjunction with the zero response. A corrected concentration is calculated using the following equation:

Concentration = F(Output - Zero Response)

Where F = Calibration Factor provided on this certificate $Output = Reading \ on \ the \ data \ logging \ system \ of \ the \ analyser$

Zero Response = Zero Response provided on this certificate

- 3 Converter eff. is the measured efficiency of the NO2 to NO converter within the oxides of nitrogen analyser under test.
- ⁴ The measured main flow rate (where this is applicable) is the flow rate through the sensor unit of the TEOM particulate analyser under test. The measured total flow rate is the total flow rate through the particulate analyser under test. Units of flow are l.min⁻¹, reported at prevailing ambient conditions unless otherwise specified. Where flow rates are highlighted in bold, it indicates that measurements were not made at the analyser sample inlet. These measurements therefore may not accurately reflect analyser performance in normal operation.
- ⁵ The calculated ko value (specifically for TEOM analysers) is the calculated ko spring constant based on tests undertaken with filters of known weight.

The calibration results shaded are those that fall within our scope of accreditation, all other results on this certificate are not UKAS accredited, but have been included for completeness.

ee.ricardo.com