

## **CERTIFICATE OF CALIBRATION**

Ricardo Energy and Environment, Gemini Building, Fermi Avenue Harwell, Didcot, Oxfordshire OX11 OQR. Telephone 01235 753692



Page 1 of 3

Approved Signatories:		S. Eaton D Hector N Rand B Davies	☐ B Stacey ☐ S Stratton ☑ S Telfer ☐ S Gray
Signed:	Stelke		
Date of issue:	20 May 20		
Certificate Number:	4949		
Customer Name and Address:		Scottish Government Water, Air, Soils and Flooding Environmental Quality Director Scottish Government Victoria Quay Edinburgh EH6 6QQ	
Description:		Calibration factors for the air Edinburgh City Council	monitoring station(s) at
Ricardo Energy & Environment I	D:	ED11194 / 4949	
level of confidence of approximately requirements.  This certificate is issued in accordanc Service. It provides traceability of me National Physical Laboratory or other	95% The uncertainty evaluation has b e with the laboratory accreditation re- asurement to the SI system of units ar	multiplied by a coverage factor k=2 providing of een carried out in accordance with UKAS quirements of the United Kingdom Accreditation Id/orto units of measurement realised at the tess. This certificate may not be reproduced ot	on

Ricardo Energy & Environment

18 Blythswood Square (2<sup>nd</sup> Floor), Glasgow, G2 4BG

Tel: 01235 753205

Registered office

Shoreham Technical Centre Shoreham-by-Sea West Sussex BN43 5FG

Registered in England No. 08229264

VAT Registration No. GB 212 8365 24



# **CERTIFICATE OF CALIBRATION**



Page 2 of 3

Date of issue: 20 May 20

Certificate Number: 4949

Ricardo Energy & Environment ID: ED11194 / 4949

### Edinburgh City Council

#### NOx analysers

NOX unarysers								
Station	Date of Audit	Species	Analyser Serial no	Zero Response <sup>1</sup>	Zero uncertainty ppb	Calibration Factor <sup>2</sup>	Factor uncertainty %	Converter eff. (%) <sup>3</sup>
Edinburgh Currie	26-Aug	NOx	1877	0.5	3.2	2.2191	3.50	98.2
		NO		0.2	3.2	2.2316	3.50	
Edinburgh Glasgow Road	27-Aug	NOx	M1780-M722	3.0	3.0	0.9576	3.50	99.6
		NO		0.0	2.6	0.9461	3.50	
Edinburgh Gorgie Road	27-Aug	NOx	0601915008	-6.3	2.6	1.2302	3.50	99.0
		NO		-6.1	2.6	1.2308	3.50	
Edinburgh Queensferry Road	26-Aug	NOx	4180	4.6	2.6	1.1502	3.50	101.0
		NO		2.5	2.6	1.1447	3.50	
Edinburgh Salamander St	26-Aug	NOx	660b-292	1.0	6.2	1.2441	4.51	99.0
		NO		1.0	4.4	1.2312	4.42	
Edinburgh St Johns Road	28-Aug	NOx	5555	5.6	2.6	1.0785	3.50	98.2
		NO		2.5	2.6	1.0797	3.50	

#### PM10 analysers

Station	Date of audit	Analyser Serial no	Calculated ko	Uncertainty %	Total flow	Uncertainty %	Main flow	Uncertainty %
Edinburgh Currie	26-Aug	1200C203110903	11600	1.0	16.44	2.2	2.99	2.2
Edinburgh Glasgow Road	27-Aug	1200C167410207	14009	1.0	17.21	2.2	2.99	2.2
Edinburgh Salamander St	26-Aug	1200B133769603	17245	1.0	16.40	2.2	2.98	2.2
Edinburgh Tower Street	26-Aug	9634			4.74	2.2		2.2

## PM2.5 analysers

I	Station	Date of audit	Analyser Serial no	Calculated ko	Uncertainty %	Total flow	Uncertainty %	Main flow	Uncertainty %
	Edinburgh Tower Street	26-Aug	9634			4.74	2.2		2.2



## **CERTIFICATE OF CALIBRATION**



Page 3 of 3

Date of issue: 20 May 20

Certificate Number: 4949

Ricardo Energy & Environment ID: ED11194 / 4949

The gaseous ambient analysers listed above have been tested for zero response, calibration factor, linearity and converter efficiency (NOx analysers) by documented methods. The factors have been calculated using certified gas standards. The particulate analysers listed above have been tested for sample flow rates and ko(where appropriate) by documented methods. Note that the test results are valid on the day of test only, as analyser drift over time cannot be quantified. All results for gaseous species are given in ppb (parts per billion) mole fractions or ppm (parts per million) mole fractions.

Concentration = F(Output - Zero Response)

Where F = Calibration Factor provided on this certificate

Output = Reading on the data logging system of the analyser Zero Response = Zero Response provided on this certificate

The calibration results shaded are those that fall within our scope of accreditation, all other results on this certificate are not UKAS accredited, but have been included for completeness.

<sup>&</sup>lt;sup>1</sup> The zero response is the zero reading on the data logging system of the analyser when audit zero gas was introduced to the analysers under test.

<sup>&</sup>lt;sup>2</sup> The calibration factor is the multiplying factor required to scale the reading on the data logging system of the analyser into reported concentration units (ppb for NO, NOx, SO2, O3 and ppm for CO. Where 1ppm = 1000ppb). It should be used in conjunction with the zero response. A corrected concentration is calculated using the following equation:

<sup>&</sup>lt;sup>3</sup> Converter eff. is the measured efficiency of the NO<sub>2</sub> to NO converter within the oxides of nitrogen analyser under test.

<sup>&</sup>lt;sup>4</sup> The measured main flow rate (where this is applicable) is the flow rate through the sensor unit of the TEOM particulate analyser under test. The measured aux flow rate (where this is applicable) is the flow rate through the bypass tubing of the TEOM particulate analyser under test. The measured total flow rate is the total flow rate through the particulate analyser under test. Units of flow are l.min<sup>-1</sup>, reported at prevailing ambient conditions unless otherwise specified. Where flow rates are highlighted in bold, it indicates that measurements were not made at the analyser sample inlet. These measurements therefore may not accurately reflect analyser performance in normal operation.

<sup>&</sup>lt;sup>5</sup> The calculated ko value (specifically for TEOM analysers) is the calculated ko spring constant based on tests undertaken with filters of known weight. The % deviation indicates the closeness of the calculated result to the manufacturer's specified value of ko.