

# **CERTIFICATE OF CALIBRATION**

Ricardo Energy and Environment, Gemini Building, Fermi Avenue Harwell, Didcot, Oxfordshire OX11 OQR. Telephone 01235 753692



Page 1 of 3

Approved Signatories:		S. Eaton D Hector N Rand B Davies	☐ B Stacey ☐ S Stratton ☐ S Telfer ☑ S Gray
Signed: Date of issue: Certificate Number:	29 Apr 19 4477		
Customer Name and Address:		Scottish Government Water, Air, Soils and Flooding Div Environmental Quality Directora Scottish Government Victoria Quay Edinburgh EH6 6QQ	
Description:		Calibration factors for the air Fife Council	monitoring station(s) at
Ricardo Energy & Environment ID:		ED61598/4477	
The reported expanded uncertainties are based on a st level of confidence of approximately 95% The uncertain requirements.  This certificate is issued in accordance with the laborat Service. It provides traceability of measurement to the National Physical Laboratory or other recognised natio than in full, except with the prior written approval of the second	nty evaluation has b ory accreditation re SI system of units a nal metrology instit	been carried out in accordance with UKAS equirements of the United Kingdom Accred and/or to units of measurement realised at tutes. This certificate may not be reproduce	itation the
Ricardo Energy & Environment Head Office Gemini Building, Fermi Avenue, Harwell, Oxon OX11 0QR Tel: +44 (0)1235 753 000	Registered off Shoreham Tech Shoreham-by-S West Sussex BN43 5FG Registered in 1 08229264 VAT Registrati GB 212 8365 2-	nnical Centre iea England No. ion No.	

ee.**ricardo**.com



# **CERTIFICATE OF CALIBRATION**



Page 2 of 3

Date of issue: 29 Apr 19

Certificate Number: 4477

Ricardo Energy & Environment ID: ED61598/4477

#### Fife Council NOx analysers

Station	Date of Audit	Species	Analyser Serial no	Zero Response <sup>1</sup>	Zero uncertainty ppb	Calibration Factor <sup>2</sup>	Factor uncertainty %	Converter eff. (%) <sup>3</sup>
Fife Cupar	17-Dec-18	NOx	1172410005	-0.8	2.5	1.0105	3.50	100.0
		NO		-0.2	2.5	1.0078	3.50	
Fife Dunfermline	17-Dec-18	NOx	1151310002	-0.2	2.6	1.1932	3.50	98.6
		NO		-0.4	2.6	1.1925	3.50	
Fife Kirkcaldy	17-Dec-18	NOx	1007841312	-0.2	2.5	0.9412	3.50	98.5
		NO		-0.1	2.5	0.9407	3.50	
Fife Rosyth	17-Dec-18	NOx	1172410006	-0.5	2.6	1.0813	3.50	100.0
		NO		-0.5	2.6	1.0847	3.50	

#### PM10 analysers

Station	Date of audit	Analyser Serial no	Calculated ko	Uncertainty %	Total flow	Uncertainty %	Main flow	Uncertainty %
Fife Cupar	17-Dec-18	7663			4.73	2.2		2.2
Fife Dunfermline	17-Dec-18	7449			4.73	2.2		2.2
Fife Kirkcaldy	17-Dec-18	6655			4.43	2.2		2.2
Fife Rosyth	17-Dec-18	6552			4.62	2.2		2.2

## PM2.5 analysers

Station	Date of audit	Analyser Serial no	Calculated ko	Uncertainty %	Total flow	Uncertainty %	Main flow	Uncertainty %
Fife Cupar	17-Dec-18	7663			4.73	2.2		2.2
Fife Dunfermline	17-Dec-18	7449			4.73	2.2		2.2
Fife Kirkcaldy	17-Dec-18	6655			4.43	2.2		2.2
Fife Rosyth	17-Dec-18	6552			4.62	2.2		2.2

ee.**ricardo.**com



## **CERTIFICATE OF CALIBRATION**



Page 3 of 3

Date of issue: 29 Apr 19

Certificate Number: 4477

Ricardo Energy & Environment ID: ED61598/4477

The gaseous ambient analysers listed above have been tested for zero response, calibration factor, linearity and converter efficiency (NOx analysers) by documented methods. The factors have been calculated using certified gas standards. The particulate analysers listed above have been tested for sample flow rates and ko(where appropriate) by documented methods. Note that the test results are valid on the day of test only, as analyser drift over time cannot be quantified. All results for gaseous species are given in ppb (parts per billion) mole fractions or ppm (parts per million) mole fractions.

Concentration = F(Output - Zero Response)

Where F = Calibration Factor provided on this certificate

Output = Reading on the data logging system of the analyser

Zero Response = Zero Response provided on this certificate

The calibration results shaded are those that fall within our scope of accreditation, all other results on this certificate are not UKAS accredited, but have been included for completeness.

ee.**ricardo**.com

<sup>&</sup>lt;sup>1</sup> The zero response is the zero reading on the data logging system of the analyser when audit zero gas was introduced to the analysers under test.

<sup>&</sup>lt;sup>2</sup> The calibration factor is the multiplying factor required to scale the reading on the data logging system of the analyser into reported concentration units (ppb for NO, NOx, SO2, O3 and ppm for CO. Where 1ppm = 1000ppb). It should be used in conjunction with the zero response. A corrected concentration is calculated using the following equation:

<sup>&</sup>lt;sup>3</sup> Converter eff. is the measured efficiency of the NO<sub>2</sub> to NO converter within the oxides of nitrogen analyser under test.

<sup>&</sup>lt;sup>4</sup> The measured main flow rate (where this is applicable) is the flow rate through the sensor unit of the TEOM particulate analyser under test. The measured total flow rate is the total flow rate through the particulate analyser under test. Units of flow are l.min<sup>-1</sup>, reported at prevailing ambient conditions unless otherwise specified. Where flow rates are highlighted in bold, it indicates that measurements were not made at the analyser sample inlet. These measurements therefore may not accurately reflect analyser performance in normal operation.

<sup>&</sup>lt;sup>5</sup> The calculated ko value (specifically for TEOM analysers) is the calculated ko spring constant based on tests undertaken with filters of known weight.