

CERTIFICATE OF CALIBRATION

Ricardo Energy and Environment, Gemini Building, Fermi Avenue Harwell, Didcot, Oxfordshire OX11 OQR. Telephone 01235 753692



Page 1 of 3

| Approved Signatories: | | | S. Eaton D Hector N Rand B Davies | ☐ B Stacey ☐ S Stratton ☑ S Telfer ☐ S Gray |
|---|--|--|--|---|
| Signed: | Stelke | | | |
| Date of issue: | 20 May 20 | | | |
| Certificate Number: | 4951 | | | |
| Customer Name and Address: | ! ! ! | | oils and Flooding Divisional Quality Directorate ernment | on |
| Description: | | Calibration fa Fife Council | ctors for the air monito | ring station(s) at |
| Ricardo Energy & Environment ID: | E | ED11194 / 49 | 951 | |
| The reported expanded uncertainties are based on a level of confidence of approximately 95% The uncertequirements. This certificate is issued in accordance with the labor Service. It provides traceability of measurement to to National Physical Laboratory or other recognised nathan in full, except with the prior written approval or | tainty evaluation has be ratory accreditation req he SI system of units an tional metrology institu | en carried out in a uirements of the L d/or to units of me | ccordance with UKAS United Kingdom Accreditation easurement realised at the | |

Ricardo Energy & Environment

18 Blythswood Square (2nd Floor), Glasgow, G2 4BG

Tel: 01235 753205

Registered office Shoreham Technical Centre Shoreham-by-Sea West Sussex BN43 5FG

Registered in England No. 08229264

VAT Registration No. GB 212 8365 24



CERTIFICATE OF CALIBRATION



Page 2 of 3

Date of issue: 20 May 20

Certificate Number: 4951

Ricardo Energy & Environment ID: ED11194 / 4951

Fife Council NOx analysers

| 110% dilaiyacia | | | | | | | | |
|------------------|---------------|---------|-----------------------|-------------------------------|----------------------------|------------------------------------|-------------------------|---------------------------------|
| Station | Date of Audit | Species | Analyser Serial no | Zero Response ¹ | Zero uncertainty ppb | Calibration Factor ² | Factor uncertainty % | Converter eff. (%) ³ |
| Fife Cupar | 26-Jun | NOx | 1172410005 | -0.5 | 2.5 | 1.0161 | 3.50 | 95.7 |
| | | NO | | -0.5 | 2.5 | 1.0271 | 3.50 | |
| Fife Cupar | 07-Aug | NOx | 1172410005 | -1.0 | | 1.0608 | | 95.4 |
| | | NO | | -0.9 | | 1.0634 | | |
| Fife Dunfermline | 26-Jun | NOx | 1151310002 | -0.8 | 2.5 | 1.0111 | 3.50 | 98.3 |
| | | NO | | -0.2 | 2.5 | 1.0124 | 3.50 | |
| Fife Kirkcaldy | 26-Jun | NOx | 1007841312 | -1.2 | 2.6 | 1.0576 | 3.50 | 99.6 |
| | | NO | | -1.2 | 2.5 | 1.0599 | 3.50 | |
| Fife Rosyth | 26-Jun | NOx | 1172410006 | -0.9 | 2.5 | 1.0284 | 3.50 | 100.0 |
| | | NO | | -0.6 | 2.5 | 1.0336 | 3.50 | |

PM10 analysers

| Station | Date of audit | Analyser Serial no | Calculated ko | Uncertainty % | Total flow | Uncertainty % | Main flow | Uncertainty % |
|------------------|---------------|-----------------------|---------------|------------------|------------|------------------|-----------|------------------|
| Fife Cupar | 26-Jun | 7663 | | | 4.73 | 2.2 | | 2.2 |
| Fife Dunfermline | 26-Jun | 7449 | | | 4.62 | 2.2 | | 2.2 |
| Fife Kirkcaldy | 26-Jun | 6655 | | | 4.53 | 2.2 | | 2.2 |
| Fife Rosyth | 26-Jun | 6552 | | | 4.63 | 2.2 | | 2.2 |

PM2.5 analysers

| TITIZIS dilaiyseis | | | | | | | | |
|--------------------|---------------|-----------------------|---------------|------------------|------------|------------------|-----------|------------------|
| Station | Date of audit | Analyser Serial no | Calculated ko | Uncertainty % | Total flow | Uncertainty % | Main flow | Uncertainty % |
| Fife Cupar | 26-Jun | 7663 | | | 4.73 | 2.2 | | 2.2 |
| Fife Dunfermline | 26-Jun | 7449 | | | 4.62 | 2.2 | | 2.2 |
| Fife Kirkcaldy | 26-Jun | 6655 | | | 4.53 | 2.2 | | 2.2 |
| Fife Rosyth | 26-Jun | 6552 | | | 4.63 | 2.2 | | 2.2 |



CERTIFICATE OF CALIBRATION



Page 3 of 3

Date of issue: 20 May 20

Certificate Number: 4951

Ricardo Energy & Environment ID: ED11194 / 4951

The gaseous ambient analysers listed above have been tested for zero response, calibration factor, linearity and converter efficiency (NOx analysers) by documented methods. The factors have been calculated using certified gas standards. The particulate analysers listed above have been tested for sample flow rates and ko(where appropriate) by documented methods. Note that the test results are valid on the day of test only, as analyser drift over time cannot be quantified. All results for gaseous species are given in ppb (parts per billion) mole fractions or ppm (parts per million) mole fractions.

Concentration = F(Output - Zero Response)

Where F = Calibration Factor provided on this certificate

Output = Reading on the data logging system of the analyser

Zero Response = Zero Response provided on this certificate

The calibration results shaded are those that fall within our scope of accreditation, all other results on this certificate are not UKAS accredited, but have been included for completeness.

¹ The zero response is the zero reading on the data logging system of the analyser when audit zero gas was introduced to the analysers under test.

² The calibration factor is the multiplying factor required to scale the reading on the data logging system of the analyser into reported concentration units (ppb for NO, NOx, SO₂, O₃ and ppm for CO. Where 1ppm = 1000ppb). It should be used in conjunction with the zero response. A corrected concentration is calculated using the following equation:

 $^{^{3}}$ Converter eff. is the measured efficiency of the NO2 to NO converter within the oxides of nitrogen analyser under test.

⁴ The measured main flow rate (where this is applicable) is the flow rate through the sensor unit of the TEOM particulate analyser under test. The measured total flow rate is the total flow rate through the particulate analyser under test. Units of flow are l.min⁻¹, reported at prevailing ambient conditions unless otherwise specified. Where flow rates are highlighted in bold, it indicates that measurements were not made at the analyser sample inlet. These measurements therefore may not accurately reflect analyser performance in normal operation.

⁵ The calculated ko value (specifically for TEOM analysers) is the calculated ko spring constant based on tests undertaken with filters of known weight. The % deviation indicates the closeness of the calculated result to the manufacturer's specified value of ko.