	RTIFICATE OF CA rdo Energy and Environment, Gemini Buil Didcot, Oxfordshire OX11 OQR. Telepi	ding, Fermi Avenue Harwell,	RICARDO
			Page 1 of 3
Approved Signatories:		 S. Eaton D Hector N Rand B Davies 	 □ B Stacey □ S Stratton □ S Telfer ☑ S Gray
Signed:	- Ster Sto		
Date of issue:	09 May 19		
Certificate Number:	4509		
Customer Name and Address		Scottish Government Water, Air, Soils and Floodin Environmental Quality Direc Scottish Government Victoria Quay Edinburgh EH6 6QQ	-
Description:		Calibration factors for the North Ayrshire Council	air monitoring station(s) at
Ricardo Energy & Environmen	t ID:	ED61598/4509	
level of confidence of approximat requirements. This certificate is issued in accord Service. It provides traceability of National Physical Laboratory or o	ties are based on a standard uncertainty r ely 95% The uncertainty evaluation has be ance with the laboratory accreditation req measurement to the SI system of units an ther recognised national metrology institu written approval of the issuing laboratory	en carried out in accordance with U uirements of the United Kingdom Ad d/or to units of measurement realis tes. This certificate may not be repro	ccreditation ed at the
Ricardo Energy & Environment Head Office Gemini Building, Fermi Avenue, Harwell, Oxon OX11 0QR Tel: +44 (0)1235 753 000	Registered offic Shoreham Techn Shoreham-by-Se West Sussex BN43 5FG Registered in Er 08229264 VAT Registratio GB 212 8365 24	ical Centre a rgland No .	
			ee. ricardo .com



CERTIFICATE OF CALIBRATION



Page 2 of 3

Date of issue:	09 May 19	
Certificate Number:	4509	
Ricardo Energy & Environment ID:	ED61598/4509	

North Ayrshire Council NOx analysers

Station	Date of Audit	Species	Analyser Serial no	Zero Response ¹	Zero uncertainty ppb	Calibration Factor ²	Factor uncertainty %	Converter eff. $(\%)^3$
North Ayrshire Irvine High St	27-Jun-18	NOx	2981873	7.0	2.7	0.9978	3.50	100.9
		NO		-1.0	2.7	0.9800	3.50	

PM10 analysers

Station	Date of audit	Analyser Serial no	Calculated ko	Uncertainty %	Total flow	Uncertainty %	Main flow	Uncertainty %
North Ayrshire Irvine High St	21-Aug-18	6251			4.68	2.2		2.2

PM2.5 analysers

Station	Date of audit	Analyser Serial no	Calculated ko	Uncertainty %	Total flow	Uncertainty %	Main flow	Uncertainty %
North Ayrshire Irvine High St	21-Aug-18	6251			4.68	2.2		2.2

ee.**ricardo**.com



CERTIFICATE OF CALIBRATION



0401	
Date of issue:	Page 3 of 3 09 May 19
Certificate Number:	4509
Ricardo Energy & Environme	ent ID: ED61598/4509
	The gaseous ambient analysers listed above have been tested for zero response, calibration factor, linearity and converter efficiency (NOx analysers) by documented methods. The factors have been calculated using certified gas standards. The particulate analysers listed above have been tested for sample flow rates and ko(where appropriate) by documented methods. Note that the test results are valid on the day of test only, as analyser drift over time cannot be quantified. All results for gaseous species are given in ppb (parts per billion) mole fractions or ppm (parts per million) mole fractions.
	¹ The zero response is the zero reading on the data logging system of the analyser when audit zero gas was introduced to the analysers under test.
	 ² The calibration factor is the multiplying factor required to scale the reading on the data logging system of the analyser into reported concentration units (ppb for NO, NOx, SO₂, O₃ and ppm for CO. Where 1ppm = 1000ppb). It should be used in conjunction with the zero response. A corrected concentration is calculated using the following equation: Concentration = F(Output - Zero Response) Where F = Calibration Factor provided on this certificate Output = Reading on the data logging system of the analyser Zero Response = Zero Response provided on this certificate
	³ Converter eff. is the measured efficiency of the NO2 to NO converter within the oxides of nitrogen analyser under test.
	⁴ The measured main flow rate (where this is applicable) is the flow rate through the sensor unit of the TEOM particulate analyser under test. The measured total flow rate is the total
	flow rate through the particulate analyser under test. Units of flow are I.min ⁻¹ , reported at prevailing ambient conditions unless otherwise specified. Where flow rates are highlighted in bold, it indicates that measurements were not made at the analyser sample inlet. These measurements therefore may not accurately reflect analyser performance in normal operation.
	⁵ The calculated ko value (specifically for TEOM analysers) is the calculated ko spring constant based on tests undertaken with filters of known weight.
	The calibration results shaded are those that fall within our scope of accreditation, all other results on this certificate are not UKAS accredited, but have been included for completeness.
	ee. ricardo .com