



Ricardo Energy and Environment, Gemini Building, Fermi Avenue Harwell, Didcot, Oxfordshire OX11 OQR. Telephone 01235 753692



Page 1 of 3

Approved Signatories:			S. Eaton D Hector N Rand E Marshall- Padkin B Davies	 B Stacey S Stratton S Telfer S Gray 	
Signed:	Stor S				
Date of issue:	25 Apr 18				
Certificate Number:	3932				
Customer Name and Address: Customer Name and Address: Customer Name and Address: Customental Quality Directorate Scottish Government Victoria Quay Edinburgh EH6 6QQ					
Description: North Lanarkshire Council					
Ricardo Energy & Environment ID:	ED6	51598/3932			
The reported expanded uncertainties level of confidence of approximately requirements. This certificate is issued in accordance Service. It provides traceability of me	95% The uncertainty ev e with the laboratory a	valuation has	s been carried out in requirements of the	accordance with UKAS United Kingdom Accreditation	

Service. It provides traceability of measurement to the SI system of units and/or to units of measurement realised at the National Physical Laboratory or other recognised national metrology institutes. This certificate may not be reproduced other than in full, except with the prior written approval of the issuing laboratory

Ricardo Energy & Environment

Head Office Gemini Building, Fermi Avenue, Harwell, Oxon OX11 0QR

Tel: +44 (0)1235 753 000

Registered office

Shoreham Technical Centre Shoreham-by-Sea West Sussex BN43 5FG

Registered in England No. 08229264

VAT Registration No. GB 212 8365 24



ee.ricardo.com



CERTIFICATE OF CALIBRATION



 Page 2 of 3

 Date of issue:
 25 Apr 18

 Certificate Number:
 3932

 Ricardo Energy & Environment ID:
 ED61598/3932

North Lanarkshire Council

NOx analysers

Station	Date of Audit	Species	Analyser Serial no	Zero Response ¹	Zero uncertainty ppb	Calibration Factor ²	Factor uncertainty %	Converter eff. (%) ³
N Lanarkshire Chapelhall	30-Aug-17	NOx	at4dak5y	4.4	2.5	0.9922	3.50	100.3
		NO		4.1	2.5	0.9980	3.50	
N Lanarkshire Croy	21-Sep-17	NOx	ayktcju8	-0.4	2.5	0.9970	3.50	99.6
		NO		0.1	2.5	1.0248	3.83	
N Lanarkshire Kirkshaws	22-Sep-17	NOx	P8GT9WHE	2.4	2.5	1.0141	3.50	100.4
		NO		0.6	2.5	1.0191	3.50	
N Lanarkshire Shawhead Coatbridge (retest)	21-Sep-17	NOx	7NHSKHBC	0.8	2.5	1.0039	3.50	99.6
		NO		0.8	2.5	1.0039	3.53	

PM10 analysers

Station	Date of audit	Analyser Serial no	Calculated ko	Uncertainty %	Total flow	Uncertainty %	Main flow	Uncertainty %
N Lanarkshire Chapelhall	21-Sep-17	8323			4.67	2.2		2.2
N Lanarkshire Coatbridge Whifflet	30-Aug-17	25385	12989	1.0	17.24	2.2	3.14	2.2
N Lanarkshire Croy	21-Sep-17	140ab217699710	14908	1.0	16.47	2.2	3.03	2.2
N Lanarkshire Kirkshaws	22-Sep-17	p15543			15.77	2.2		2.2
N Lanarkshire Motherwell	30-Aug-17	24903	13242	1.0	17.06	2.2	3.00	2.2
N Lanarkshire Shawhead Coatbridge	30-Aug-17	j2657			15.77	2.2		2.2



ee.ricardo.com



CERTIFICATE OF CALIBRATION



Page 3 of 3

Date of issue:	25 Apr 18
Certificate Number:	3932
Ricardo Energy & Environment ID:	ED61598/3932

The gaseous ambient analysers listed above have been tested for zero response, calibration factor, linearity and converter efficiency (NOx analysers) by documented methods. The factors have been calculated using certified gas standards. The particulate analysers listed above have been tested for sample flow rates and ko(where appropriate) by documented methods. Note that the test results are valid on the day of test only, as analyser drift over time cannot be quantified. All results for gaseous species are given in ppb (parts per billion) mole fractions or ppm (parts per million) mole fractions.

¹ The zero response is the zero reading on the data logging system of the analyser when audit zero gas was introduced to the analysers under test.

² The calibration factor is the multiplying factor required to scale the reading on the data logging system of the analyser into reported concentration units (ppb for NO, NOx, SO₂, O₃ and ppm for CO. Where 1ppm = 1000ppb). It should be used in conjunction with the zero response. A corrected concentration is calculated using the following equation:

Concentration = F(Output - Zero Response) Where F = Calibration Factor provided on this certificate Output = Reading on the data logging system of the analyser Zero Response = Zero Response provided on this certificate

³ Converter eff. is the measured efficiency of the NO₂ to NO converter within the oxides of nitrogen analyser under test.

⁴ The measured main flow rate (where this is applicable) is the flow rate through the sensor unit of the TEOM particulate analyser under test. The measured total flow rate is the total flow rate through the particulate analyser under test. Units of flow are l.min⁻¹, reported at prevailing ambient conditions unless otherwise specified. Where flow rates are highlighted in bold, it indicates that measurements were not made at the analyser sample inlet. These measurements therefore may not accurately reflect analyser performance in normal operation.

⁵ The calculated ko value (specifically for TEOM analysers) is the calculated ko spring constant based on tests undertaken with filters of known weight. The % deviation indicates the closeness of the calculated result to the manufacturer's specified value of ko.

The calibration results shaded are those that fall within our scope of accreditation, all other results on this certificate are not UKAS accredited, but have been included for completeness.



ee.ricardo.com