

CERTIFICATE OF CALIBRATION

Ricardo Energy and Environment, Gemini Building, Fermi Avenue Harwell, Didcot, Oxfordshire OX11 OQR. Telephone 01235 753692



Page 1 of 3

Approved Signatories:			S. Eaton D Hector N Rand E Marshall- Padkin B Davies	□ B Stacey□ S Stratton□ S Telfer☑ S Gray
Signed:	Alexander -			
Date of issue:	25 Apr 18			
Certificate Number:	3934			
	Envir Scott	onmental Qua ish Governme ria Quay ourgh	d Flooding Division ality Directorate nt	
Description:		alibration fac enfrewshire (tors for the air monil Council	toring stations at
Ricardo Energy & Environment ID:	EC	061598/3934	4	
The reported expanded uncertaintie level of confidence of approximately requirements. This certificate is issued in accordance Service. It provides traceability of me	95% The uncertainty e with the laboratory	evaluation h	nas been carried out in on requirements of the	accordance with UKAS United Kingdom Accreditation

Ricardo Energy & Environment

Head Office Gemini Building, Fermi Avenue, Harwell, Oxon OX11 0QR

Tel: +44 (0)1235 753 000

Registered office

than in full, except with the prior written approval of the issuing laboratory

Shoreham Technical Centre Shoreham-by-Sea West Sussex BN43 5FG

Registered in England No. 08229264

VAT Registration No. GB 212 8365 24



CERTIFICATE OF CALIBRATION



Page 2 of 3

Date of issue: 25 Apr 18

Certificate Number: 3934

Ricardo Energy & Environment ID: ED61598/3934

Renfrewshire Council

NOx analysers

NOX analysers								
Station	Date of Audit	Species	Analyser Serial no	Zero Response ¹	Zero uncertainty ppb	Calibration Factor ²	Factor uncertainty %	Converter eff. (%) ³
Paisley Gordon Street	14-Jul-17	NOx	M1486-M623	5.0	2.7	1.0370	3.50	98.8
		NO		0.0	2.7	1.0022	3.50	
Renfrew Cockles Loan	14-Sep-17	NOx	1108947668	0.0	2.6	1.2202	3.50	101.4
		NO		0.0	2.6	1.2181	3.50	

PM10 analysers

i ivi±0 dilalyscis								
Station	Date of audit	Analyser Serial no	Calculated ko	Uncertainty %	Total flow	Uncertainty %	Main flow	Uncertainty %
Paisley Gordon Street	14-Jul-17	1400AB233710012	13141	1.0	16.14	2.2	3.11	2.2
Paisley St James St	11-Jul-17	27583	14752	1.0	16.75	2.2	3.11	2.2
Renfrew Cockles Loan	11-Jul-17	25662	13519	1.0	15.63	2.2	3.02	2.2
Renfrewshire Johnstone	14-Sep-17	7735			4.65	2.2		2.2



CERTIFICATE OF CALIBRATION



Page 3 of 3

Date of issue:	25 Apr 18
sate of issue.	23 /\pi 10

Certificate Number: 3934

Ricardo Energy & Environment ID: ED61598/3934

The gaseous ambient analysers listed above have been tested for zero response, calibration factor, linearity and converter efficiency (NOx analysers) by documented methods. The factors have been calculated using certified gas standards. The particulate analysers listed above have been tested for sample flow rates and ko(where appropriate) by documented methods. Note that the test results are valid on the day of test only, as analyser drift over time cannot be quantified. All results for gaseous species are given in ppb (parts per billion) mole fractions or ppm (parts per million) mole fractions.

- ¹ The zero response is the zero reading on the data logging system of the analyser when audit zero gas was introduced to the analysers under test.
- ² The calibration factor is the multiplying factor required to scale the reading on the data logging system of the analyser into reported concentration units (ppb for NO, NOx, SO₂, O₃ and ppm for CO. Where 1ppm = 1000ppb). It should be used in conjunction with the zero response. A corrected concentration is calculated using the following equation:

Concentration = F(Output - Zero Response)

Where F = Calibration Factor provided on this certificate

Output = Reading on the data logging system of the analyser

Zero Response = Zero Response provided on this certificate

- ³ Converter eff. is the measured efficiency of the NO₂ to NO converter within the oxides of nitrogen analyser under test.
- ⁴ The measured main flow rate (where this is applicable) is the flow rate through the sensor unit of the TEOM particulate analyser under test. The measured total flow rate is the total flow rate through the particulate analyser under test. Units of flow are l.min⁻¹, reported at prevailing ambient conditions unless otherwise specified. Where flow rates are highlighted in bold, it indicates that measurements were not made at the analyser sample inlet. These measurements therefore may not accurately reflect analyser performance in normal operation.
- ⁵ The calculated ko value (specifically for TEOM analysers) is the calculated ko spring constant based on tests undertaken with filters of known weight. The % deviation indicates the closeness of the calculated result to the manufacturer's specified value of ko.

The calibration results shaded are those that fall within our scope of accreditation, all other results on this certificate are not UKAS accredited, but have been included for completeness.