	CERTIFICATE OF C. Ricardo Energy and Environment, Gemini Bu Didcot, Oxfordshire OX11 OQR. Tele	ilding, Fermi Avenue Harwell,	RICARDO
			Page 1 of 3
Approved Signatories:		<ul> <li>S. Eaton</li> <li>D Hector</li> <li>N Rand</li> <li>B Davies</li> </ul>	<ul> <li>□ B Stacey</li> <li>□ S Stratton</li> <li>□ S Telfer</li> <li>☑ S Gray</li> </ul>
Signed:	- Star Clas		
Date of issue:	09 May 19		
Certificate Number:	4512		
Customer Name and Ado	lress:	Scottish Government Water, Air, Soils and Floodin Environmental Quality Direc Scottish Government Victoria Quay Edinburgh EH6 6QQ	-
Description:		Calibration factors for the Renfrewshire Council	air monitoring station(s) at
Ricardo Energy & Enviro	nment ID:	ED61598/4512	
level of confidence of appr requirements. This certificate is issued in Service. It provides traceal National Physical Laborato	accertainties are based on a standard uncertainty coximately 95% The uncertainty evaluation has accordance with the laboratory accreditation r bility of measurement to the SI system of units ary or other recognised national metrology insti e prior written approval of the issuing laborato	been carried out in accordance with U equirements of the United Kingdom A and/or to units of measurement realis tutes. This certificate may not be repro	CCTEDITATION ed at the
Ricardo Energy & Environm Head Office Gemini Building, Fermi Avenue, Harwell, Oxon OX11 0QR Tel: +44 (0)1235 753 000	ent Registered off Shoreham Tecl Shoreham-by-5 West Sussex BN43 5FG Registered in 08229264 VAT Registrat GB 212 8365 2	nnical Centre iea England No. ion No.	
			ee. <b>ricardo</b> .com



## **CERTIFICATE OF CALIBRATION**



Page 2 of 3

Date of issue:	09 May 19	ruge z
Certificate Number:	4512	
Ricardo Energy & Environment ID:	ED61598/4512	

Renfrewshire Council NOx analysers

Station	Date of Audit	Species	Analyser Serial no	Zero Response <sup>1</sup>	Zero uncertainty ppb	Calibration Factor <sup>2</sup>	Factor uncertainty %	Converter eff. (%) <sup>3</sup>
Paisley Gordon Street	21-Aug-18	NOx	m1486-m623	-1.0	2.6	1.1153	3.50	98.6
		NO		0.0	2.5	1.0574	3.55	
Renfrew Cockels Loan	20-Aug-18	NOx	108947668	-0.2	2.6	1.1797	3.50	99.5
		NO		-0.2	2.6	1.1780	3.51	

PM10 analysers

Station	Date of audit	Analyser Serial no	Calculated ko	Uncertainty %	Total flow	Uncertainty %	Main flow	Uncertainty %
Paisley Gordon Street	21-Aug-18	140ab233710012	12731	1.0	16.36	2.2	3.00	2.2
Renfrew Cockels Loan	20-Aug-18	140ab256620505	13133	1.0	16.43	2.2	3.05	2.2
Renfrewshire Johnstone	20-Aug-18	7735			4.75	2.2		2.2

## PM2.5 analysers

Station	Date of audit	Analyser Serial no	Calculated ko	Uncertainty %	Total flow	Uncertainty %	Main flow	Uncertainty %
Renfrewshire Johnstone	20-Aug-18	7735			4.75	2.2		2.2
Paisley St James St	20-Aug-18	140ab275831004	14287	1.0	16.52	2.2	3.01	2.2

ee.**ricardo**.com



## **CERTIFICATE OF CALIBRATION**



Page 3 of 3

Date of issue:	09 May 19	Page
Certificate Number:	4512	
Ricardo Energy & Environment ID:	ED61598/4512	

The gaseous ambient analysers listed above have been tested for zero response, calibration factor, linearity and converter efficiency (NOx analysers) by documented methods. The factors have been calculated using certified gas standards. The particulate analysers listed above have been tested for sample flow rates and ko(where appropriate) by documented methods. Note that the test results are valid on the day of test only, as analyser drift over time cannot be quantified. All results for gaseous species are given in ppb (parts per billion) mole fractions.

<sup>1</sup> The zero response is the zero reading on the data logging system of the analyser when audit zero gas was introduced to the analysers under test.

<sup>2</sup> The calibration factor is the multiplying factor required to scale the reading on the data logging system of the analyser into reported concentration units (ppb for NO, NOx, SO<sub>2</sub>, O<sub>3</sub> and ppm for CO. Where 1ppm = 1000ppb). It should be used in conjunction with the zero response. A corrected concentration is calculated using the following equation:

Concentration = F(Output - Zero Response)

Where F = Calibration Factor provided on this certificate Output = Reading on the data logging system of the analyser Zero Response = Zero Response provided on this certificate

<sup>3</sup> Converter eff. is the measured efficiency of the NO<sub>2</sub> to NO converter within the oxides of nitrogen analyser under test.

<sup>4</sup> The measured main flow rate (where this is applicable) is the flow rate through the sensor unit of the TEOM particulate analyser under test. The measured total flow rate is the total flow rate through the particulate analyser under test. Units of flow are I.min<sup>-1</sup>, reported at prevailing ambient conditions unless otherwise specified. Where flow rates are highlighted in bold, it indicates that measurements were not made at the analyser sample inlet. These measurements therefore may not accurately reflect analyser performance in normal operation.

<sup>5</sup> The calculated k<sub>0</sub> value (specifically for TEOM analysers) is the calculated k<sub>0</sub> spring constant based on tests undertaken with filters of known weight.

The calibration results shaded are those that fall within our scope of accreditation, all other results on this certificate are not UKAS accredited, but have been included for completeness.

ee.ricardo.com