

CERTIFICATE OF CALIBRATION

Ricardo Energy and Environment, Gemini Building, Fermi Avenue Harwell, Didcot, Oxfordshire OX11 OQR. Telephone 01235 753692



Page 1 of 3

Approved Signatories:			S. Eaton D Hector N Rand E Marshall- Padkin B Davies	□ B Stacey□ S Stratton□ S Telfer☑ S Gray
Signed:	Alex Co			
Date of issue:	25 Apr 18			
Certificate Number:	3937			
		Environmental Qua Scottish Governme Victoria Quay Edinburgh EH6 6QQ	•	
Description:		Calibration fact South Lanarks	tors for the air moni hire Council	itoring stations at
Ricardo Energy & Environ	ment ID:	ED61598/3937	,	
level of confide requirements. This certificate	ence of approximately 95% The u	Incertainty evaluation	on has been carried o ation requirements o	y a coverage factor k=2 providing a out in accordance with UKAS of the United Kingdom Accreditation s of measurement realised at the

National Physical Laboratory or other recognised national metrology institutes. This certificate may not be reproduced other

Ricardo Energy & Environment

Head Office Gemini Building, Fermi Avenue, Harwell, Oxon OX11 0QR

Tel: +44 (0)1235 753 000

Registered office

than in full, except with the prior written approval of the issuing laboratory

Shoreham Technical Centre Shoreham-by-Sea West Sussex BN43 5FG

Registered in England No. 08229264

10229204

VAT Registration No. GB 212 8365 24



CERTIFICATE OF CALIBRATION



Page 2 of 3

Date of issue: 25 Apr 18

Certificate Number: 3937

Ricardo Energy & Environment ID: ED61598/3937

South Lanarkshire Council

NOx analysers

NOX analysers								
Station	Date of Audit	Species	Analyser Serial no	Zero Response ¹	Zero uncertainty ppb	Calibration Factor ²	Factor uncertainty %	Converter eff. (%) ³
South Lanarkshire East Kilbride	17-Jul-17	NOx	CM07460075	4.3	2.6	1.1641	3.50	99.2
		NO		4.2	2.6	1.1612	3.50	
South Lanarkshire Hamilton	18-Jul-17	NOx	CM07460073	-22.8	2.5	0.9557	3.50	98.2
		NO		-22.8	2.5	0.9536	3.50	
South Lanarkshire Lanark	18-Jul-17	NOx	CM10020067	0.3	2.5	1.0235	3.50	101.3
		NO		-0.1	2.5	1.0226	3.50	
South Lanarkshire Rutherglen	17-Jul-17	NOx	CM07460076	-5.6	2.6	1.0650	3.50	99.3
		NO		-7.0	2.5	1.0616	3.50	
South Lanarkshire Uddingston	17-Jul-17	NOx	CM10020068	-0.8	2.6	1.1316	3.50	100.0
		NO		-1.3	2.6	1.1333	3.50	
South Lanarkshire Cambuslang	18-Jul-17	NOx	1152590008	-1.6	3.1	2.0171	3.50	99.0
		NO		-1.3	3.1	2.0244	3.50	
South Lanarkshire Raith Interchange	17-Jul-17	NOx	CM10220001	-1.0	2.6	1.1197	3.50	98.7
		NO		-0.4	2.6	1.1161	3.50	

PM10 analysers

PIVITO analysers								
Station	Date of audit	Analyser Serial no	Calculated ko	Uncertainty %	Total flow	Uncertainty %	Main flow	Uncertainty %
South Lanarkshire Cambuslang	18-Jul-17	8256			4.83	2.2		2.2
South Lanarkshire East Kilbride	17-Jul-17	8257			4.60	2.2		2.2
South Lanarkshire Lanark	18-Jul-17	6248			4.82	2.2		2.2
South Lanarkshire Rutherglen	17-Jul-17	8140			4.77	2.2		2.2
South Lanarkshire Uddingston	17-Jul-17	6247			4.70	2.2		2.2
South Lanarkshire Raith Interchange	17-Jul-17	27186	15263	1.0	15.31	2.2	3.06	2.2



CERTIFICATE OF CALIBRATION



Page 3 of 3

Date of issue:	25 Apr 18
Date of Issael	23 / tp: 10

Certificate Number: 3937

Ricardo Energy & Environment ID: ED61598/3937

The gaseous ambient analysers listed above have been tested for zero response, calibration factor, linearity and converter efficiency (NOx analysers) by documented methods. The factors have been calculated using certified gas standards. The particulate analysers listed above have been tested for sample flow rates and ko(where appropriate) by documented methods. Note that the test results are valid on the day of test only, as analyser drift over time cannot be quantified. All results for gaseous species are given in ppb (parts per billion) mole fractions or ppm (parts per million) mole fractions.

² The calibration factor is the multiplying factor required to scale the reading on the data logging system of the analyser into reported concentration units (ppb for NO, NOx, SO₂, O₃ and ppm for CO. Where 1ppm = 1000ppb). It should be used in conjunction with the zero response. A corrected concentration is calculated using the following equation:

Concentration = F(Output - Zero Response)

Where F = Calibration Factor provided on this certificate

Output = Reading on the data logging system of the analyser

Zero Response = Zero Response provided on this certificate

The calibration results shaded are those that fall within our scope of accreditation, all other results on this certificate are not UKAS accredited, but have been included for completeness.

¹ The zero response is the zero reading on the data logging system of the analyser when audit zero gas was introduced to the analysers under test.

³ Converter eff. is the measured efficiency of the NO₂ to NO converter within the oxides of nitrogen analyser under test.

⁴ The measured main flow rate (where this is applicable) is the flow rate through the sensor unit of the TEOM particulate analyser under test. The measured total flow rate is the total flow rate through the particulate analyser under test. Units of flow are l.min⁻¹, reported at prevailing ambient conditions unless otherwise specified. Where flow rates are highlighted in bold, it indicates that measurements were not made at the analyser sample inlet. These measurements therefore may not accurately reflect analyser performance in normal operation.

⁵ The calculated ko value (specifically for TEOM analysers) is the calculated ko spring constant based on tests undertaken with filters of known weight. The % deviation indicates the closeness of the calculated result to the manufacturer's specified value of ko.