



CERTIFICATE OF CALIBRATION

Ricardo Energy & Environment 18 Blythswood Square, Glasgow, G2 4BG
Telephone 01225 75233



Page 1 of 3

Approved Signatories:)))	S. Eaton S Copsey N Rand B Davies D Lane A Nash	□ B Stacey □ S Stratton □ S Telfer □ S Gray □ T Green		
Signed:	3456	-			
Date of issue:	01 April 2025				
Certificate Number:	7378				
Customer Name and Address:		n Government	a Division		
	Enviror	rgh	_		
Description: Calibration factors for the air monitoring station(Clackmannanshire Council					
Ricardo Energy & Environment ID:	ED190	50/7378			
The reported expanded uncertainties are base level of confidence of approximately 95% The requirements. This certificate is issued in accordance with the Service. It provides traceability of measurements National Physical Laboratory or other recognists than in full, except with the prior written approximately.	uncertainty evaluation ha e laboratory accreditatior nt to the SI system of unit ed national metrology ins	as been carried out in accord n requirements of the United is and/or to units of measur stitutes. This certificate may	dance with UKAS d Kingdom Accreditation rement realised at the		
Ricardo Energy & Environment 18 Blythswood Square (2 nd Floor), Glasgow, G2 4BG Tel: 01235 753205	Registered office Shoreham Technical Shoreham-by-Sea West Sussex BN43 5FG Registered in Engla 08229264				

VAT Registration No. GB 212 8365 24

ee.**ricardo**.com



CERTIFICATE OF CALIBRATION



Page 2 of 3

Date of issue:

01 April 2025

Certificate Number:

7378

Ricardo Energy & Environment ID:

ED19050/7378

Clackmannanshire Council

NOx analysers

Station	Date of Audit	Species	Analyser Serial no	Zero Response ¹	Zero uncertainty nmol/mol	Calibration Factor ²	Factor uncertainty %	Converter eff. (%) ³	Converter uncertainty (%)
Alloa A907	13 December 2024	NOx	22-0333	3.0	2.8	1.0465	3.50	100.4 (276nmol/mol)	1.9
		NO		3.0	2.7	1.0350	3.50	101.5 (135nmol/mol)	1.9

Fidas analysers

Station	Date of audit	Analyser Serial no	Zero (µg/m³)	Caldust channel deviation	Total flow ⁴	Uncertainty %	Deviation %
Alloa A907	13 December 2024	8790	0	0.32	4.74	2.25	-1.32

ee.**ricardo**.com



CERTIFICATE OF CALIBRATION



Page 3 of 3

Date of issue: 01 April 2025

Certificate Number: 7378

Ricardo Energy & Environment ID: ED19050/7378

The gaseous ambient analysers listed above have been tested for zero response, calibration factor, linearity and converter efficiency (NOx analysers) by documented methods. The factors have been calculated using certified gas standards. The particulate analysers listed above have been tested for sample flow rates and k0 (where appropriate) by documented methods. Note that the test results are valid on the day of test only, as analyser drift over time cannot be quantified. All results for gaseous species are reported in composition units of nmol/mol or $\mu mol/mol$.

composition = F(Output - Zero Response)

Where F = Calibration Factor provided on this certificate

Output = Reading on the data logging system of the analyser

Zero Response = Zero Response provided on this certificate

- ⁴ The measured main flow rate (where this is applicable) is the flow rate through the sensor unit of the TEOM particulate analyser under test. The measured aux flow rate (where this is applicable) is the flow rate through the bypass tubing of the TEOM particulate analyser under test. The measured total flow rate is the total flow rate through the particulate analyser under test. Units of flow are l.min-1, reported at prevailing ambient conditions unless otherwise specified. Where flow rates are highlighted in bold, it indicates that measurements were not made at the analyser sample inlet. These measurements therefore may not accurately reflect analyser performance in normal operation.
- 5 The calculated k0 value (specifically for TEOM analysers) is the calculated k0 spring constant based on tests undertaken with filters of known weight. The % deviation indicates the closeness of the calculated result to the manufacturer's specified value of $\rm k0$

The calibration results shaded are those that fall within our scope of accreditation, all other results on this certificate are not UKAS accredited, but have been included for completeness.

*****END OF CERTIFICATE*****

ee.**ricardo**.com

¹ The zero response is the zero reading on the data logging system of the analyser when audit zero gas was introduced to the analysers under test.

² The calibration factor is the multiplying factor required to scale the reading on the data logging system of the analyser into reported composition units (nmol/mol for NO, NO_x SO₂, O₃ and µmol/mol for CO). It should be used in conjunction with the zero response. A corrected composition is calculated using the following equation:

³ Converter eff. is the measured efficiency of the NO2 to NO converter within the oxides of nitrogen analyser under test.