



### **CERTIFICATE OF CALIBRATION**

Ricardo Energy & Environment 18 Blythswood Square, Glasgow, G2 4BG

Telephone 01235 753434



Page 1 of 3

Approved Signatories:		S. Eaton S Copsey N Rand B Davies D Lane A Nash	□ B Stacey □ S Stratton □ S Telfer □ S Gray □ T Green				
Signed:	Seg (5)						
Date of issue:	01 April 2025						
Certificate Number:	7380						
Customer Name and Address:	Water, Ai Environm	, 1					
Description:		Calibration factors for the air monitoring station(s) at East Ayrshire Council					
Ricardo Energy & Environment ID:	ED19050	)/7380					
The reported expanded uncertainties are based level of confidence of approximately 95% The unrequirements.  This certificate is issued in accordance with the Service. It provides traceability of measuremen National Physical Laboratory or other recognise than in full, except with the prior written approximately approximatel	laboratory accreditation req it to the SI system of units an ed national metrology institu	en carried out in accordance uirements of the United Kin, d/or to units of measuremeites. This certificate may not	e with UKAS gdom Accreditation nt realised at the				

VAT Registration No. GB 212 8365 24

ee.**ricardo**.com



## **CERTIFICATE OF CALIBRATION**



Page 2 of 3

Date of issue: 01 April 2025

Certificate Number: 7380

Ricardo Energy & Environment ID: ED19050/7380

# East Ayrshire Council

NOx analysers

Station	Date of Audit	Species	Analyser Serial no	Zero Response <sup>1</sup>	Zero uncertainty nmol/mol	Calibration Factor <sup>2</sup>	Factor uncertainty %	Converter eff. (%) <sup>3</sup>	Converter uncertainty (%)
East Ayrshire Kilmarnock St	09 December 2024	NOx	24-0786	-0.7	2.5	1.0251	3.50	98.6 (272nmol/mol)	0.7
Marnock Street		NO		-0.2	2.5	1.0236	3.50	98.5 (132nmol/mol)	0.7

### Fidas analysers

Station	Date of audit	Analyser Serial no	Zero (µg/m³)	Caldust channel deviation	Total flow⁴	Uncertaint y %	Deviation %
East Ayrshire Kilmarnock St Marnock Street	06 March 2025	7476	0	0.00	4.82	2.25	0.45

ee.**ricardo**.com



#### **CERTIFICATE OF CALIBRATION**



Page 3 of 3

Date of issue: 01 April 2025

Certificate Number: 7380

Ricardo Energy & Environment ID: ED19050/7380

The gaseous ambient analysers listed above have been tested for zero response, calibration factor, linearity and converter efficiency (NOx analysers) by documented methods. The factors have been calculated using certified gas standards. The particulate analysers listed above have been tested for sample flow rates and k0 (where appropriate) by documented methods. Note that the test results are valid on the day of test only, as analyser drift over time cannot be quantified. All results for gaseous species are reported in composition units of nmol/mol or  $\mu mol/mol$ .

composition = F(Output - Zero Response)

Where F = Calibration Factor provided on this certificate

Output = Reading on the data logging system of the analyser

Zero Response = Zero Response provided on this certificate

The calibration results shaded are those that fall within our scope of accreditation, all other results on this certificate are not UKAS accredited, but have been included for completeness.

\*\*\*\*\*END OF CERTIFICATE\*\*\*\*\*

ee.**ricardo**.com

<sup>&</sup>lt;sup>1</sup> The zero response is the zero reading on the data logging system of the analyser when audit zero gas was introduced to the analysers under test.

 $<sup>^2</sup>$  The calibration factor is the multiplying factor required to scale the reading on the data logging system of the analyser into reported composition units (nmol/mol for NO, NOx SO2, O3 and µmol/mol for CO). It should be used in conjunction with the zero response. A corrected composition is calculated using the following equation:

<sup>&</sup>lt;sup>3</sup> Converter eff. is the measured efficiency of the NO2 to NO converter within the oxides of nitrogen analyser under test.

<sup>&</sup>lt;sup>4</sup> The measured main flow rate (where this is applicable) is the flow rate through the sensor unit of the TEOM particulate analyser under test. The measured aux flow rate (where this is applicable) is the flow rate through the bypass tubing of the TEOM particulate analyser under test. The measured total flow rate is the total flow rate through the particulate analyser under test. Units of flow are l.min-1, reported at prevailing ambient conditions unless otherwise specified. Where flow rates are highlighted in bold, it indicates that measurements were not made at the analyser sample inlet. These measurements therefore may not accurately reflect analyser performance in normal operation.

<sup>&</sup>lt;sup>5</sup> The calculated k0 value (specifically for TEOM analysers) is the calculated k0 spring constant based on tests undertaken with filters of known weight. The % deviation indicates the closeness of the calculated result to the manufacturer's specified value of k0.