



CERTIFICATE OF CALIBRATION

Ricardo Energy & Environment 18 Blythswood Square, Glasgow, G2 4BG
Telephone 01235 753434



Page 1 of 3

Approved Signat	ories:			S. Eaton S Copsey N Rand B Davies D Lane	\ 	B Stacey S Stratton S Telfer S Gray T Green			
Signed:		Stelke							
Date of issue: Certificate Numb	per:	20 March 2024 6707							
Customer Name	and Address:			Soils and Flooding Soils and Flo					
Description:			Calibration factors for the air monitoring station(s) at Edinburgh City Council						
Ricardo Energy 8	& Environment ID:		ED11194/6707						
level of confide requirements. This certificate Service. It prov National Physi	expanded uncertainties are based on a ence of approximately 95% The uncert is issued in accordance with the labor vides traceability of measurement to tical Laboratory or other recognised nat cept with the prior written approval of	rainty evaluation has been of ratory accreditation require the SI system of units and/o tional metrology institutes. It the issuing laboratory	arried out in acco	rdance with UKAS ed Kingdom Accreditation prement realised at the	on				
Shoreham: 18 Blythswood Square (2 nd Floor),			hnical Centre Sea England No.						

ee.**ricardo**.com



CERTIFICATE OF CALIBRATION



Page 2 of 3

Date of issue: 20 March 2024

Certificate Number: 6707

Ricardo Energy & Environment ID: ED11194/6707

Edinburgh City Council NOx analysers

NOX allalysers								
Station	Date of Audit	Species	Analyser Serial no	Zero Response ¹	Zero uncertainty nmol/mol	Calibration Factor ²	Factor uncertainty %	Converter eff. (%) ³
Edinburgh Currie	23 February 2024	NOx	6232	2.4	2.5	1.0715	3.50	98 (234nmol/mol)
		NO		1.3	2.5	1.0679	3.50	100.3 (135nmol/mol)
Edinburgh Gorgie Road	19 February 2024	NOx	6234	7.0	2.6	1.0822	3.50	99.1 (248nmol/mol)
		NO		3.9	2.6	1.0939	3.50	99.7 (154nmol/mol)
Edinburgh Queensferry Road	22 February 2024	NOx	4180	11.8	2.6	1.2203	3.50	98 (246nmol/mol)
		NO		10.6	2.6	1.2162	3.52	98.3 (148nmol/mol)
Edinburgh Salamander Street	07 March 2024	NOx	6233	2.1	2.6	1.1613	3.50	99.6 (249nmol/mol)
		NO		0.7	2.6	1.1743	3.50	98.7 (151nmol/mol)
Edinburgh St John's Road	22 February 2024	NOx	5555	2.3	2.6	1.2206	3.50	98.7 (241nmol/mol)
		NO		0.3	2.6	1.2266	3.50	99.4 (155nmol/mol)

FIDAS analysers

Station	Date of audit	Analyser Serial no	Calculated ko⁵	Uncertainty %	Total flow⁴	Uncertainty %	Main flow	Uncertainty %
Edinburgh Currie	23 February 2024	13873			5.44	2.2		2.2
Edinburgh Queensferry Road	22 February 2024	11391			5.42	2.2		2.2
Edinburgh Nicolson Street	20 February 2024	11955			4.94	2.2		2.2
Edinburgh Salamander Street	19 February 2024	13874			4.86	2.2		2.2
Edinburgh St John's Road	22 February 2024	7749			5.26	2.2		2.2
Edinburgh Tower Street	19 February 2024	9635			4.74	2.2		2.2

ee.**ricardo**.com



CERTIFICATE OF CALIBRATION



Page 3 of 3

Date of issue: 20 March 2024

Certificate Number: 6707

Ricardo Energy & Environment ID: ED11194/6707

The gaseous ambient analysers listed above have been tested for zero response, calibration factor, linearity and converter efficiency (NOx analysers) by documented methods. The factors have been calculated using certified gas standards. The particulate analysers listed above have been tested for sample flow rates and k0 (where appropriate) by documented methods. Note that the test results are valid on the day of test only, as analyser drift over time cannot be quantified. All results for gaseous species are reported in concentration units of nmol/mol or μ mol/mol.

Concentration = F(Output - Zero Response)

Where F = Calibration Factor provided on this certificate

Output = Reading on the data logging system of the analyser

Zero Response = Zero Response provided on this certificate

The calibration results shaded are those that fall within our scope of accreditation, all other results on this certificate are not UKAS accredited, but have been included for completeness.

*****END OF CERTIFICATE*****

ee.**ricardo**.com

¹ The zero response is the zero reading on the data logging system of the analyser when audit zero gas was introduced to the analysers under test.

 $^{^2}$ The calibration factor is the multiplying factor required to scale the reading on the data logging system of the analyser into reported concentration units (nmol/mol for NO, NOx, SO2, O3 and μ mol/mol for CO). It should be used in conjunction with the zero response. A corrected concentration is calculated using the following equation:

³ Converter eff. is the measured efficiency of the NO₂ to NO converter within the oxides of nitrogen

⁴ The measured main flow rate (where this is applicable) is the flow rate through the sensor unit of the TEOM particulate analyser under test. The measured aux flow rate (where this is applicable) is the flow rate through the bypass tubing of the TEOM particulate analyser under test. The measured total flow rate is the total flow rate through the particulate analyser under test. Units of flow are l.min-1, reported at prevailing ambient conditions unless otherwise specified. Where flow rates are highlighted in bold, it indicates that measurements were not made at the analyser sample inlet. These measurements therefore may not accurately reflect analyser performance in normal operation.

⁵ The calculated ko value (specifically for TEOM analysers) is the calculated ko spring constant based on tests undertaken with filters of known weight. The % deviation indicates the closeness of the calculated result to the manufacturer's specified value of ko.