



CERTIFICATE OF CALIBRATION

Ricardo Energy & Environment 18 Blythswood Square, Glasgow, G2 4BG





Page 1 of 3

Approved Signatories:	□ S. Eaton □ B Stacey □ S Copsey □ S Stratton □ N Rand □ S Telfer □ B Davies □ S Gray □ D Lane □ F. Elmer □ A Nash							
Signed:	Jag Es							
Date of issue:	04 September 2025							
Certificate Number:	7606							
Customer Name and Address:	Scottish Government Water, Air, Soils and Flooding Division Environmental Quality Directorate Scottish Government Victoria Quay Edinburgh EH6 6QQ							
Description:	Calibration factors for the air monitoring station(s) at Fife Council							
Ricardo Energy & Environment ID:	ED19050 /7606							
level of confidence of approximately 95% The u requirements. This certificate is issued in accordance with the Service. It provides traceability of measuremen National Physical Laboratory or other recognise than in full, except with the prior written appro	Registered office							
Ricardo Energy & Environment 18 Blythswood Square (2 nd Floor), Glasgow, G2 4BG Tel: 01235 753205	Shoreham Technical Centre Shoreham-by-Sea West Sussex BN43 6FG Registered in England No. 08229264							

VAT Registration No. GB 212 8365 24

ee.**ricardo**.com



CERTIFICATE OF CALIBRATION



Page 2 of 3

Date of issue: 04 September 2025

Certificate Number: 7606

Ricardo Energy & Environment ID: ED19050 /7606

Fife Council NOx analysers

TTOX undry sers									
Station	Date of Audit	Species	Analyser Serial no	Zero Response ¹	Zero uncertainty nmol/mol	Calibration Factor ²	Factor uncertainty %	Converter eff. (%) ³	Converter uncertainty (%)
Fife Cupar	20 June 2025	NOx	8249	1.6	2.6	1.1049	3.50	97.1 (270 nmol/mol)	0.9
		NO		1.7	2.6	1.1057	3.50	97.5 (131 nmol/mol)	0.9
Fife Dunfermline	19 June 2025	NOx	8247	4.3	2.5	1.0460	3.50	99 (257 nmol/mol)	0.6
		NO		1.6	2.5	1.0355	3.50	98.7 (123 nmol/mol)	0.6
Fife Kirkcaldy	20 June 2025	NOx	8248	2.7	2.5	1.0522	3.50	97.2 (262 nmol/mol)	2.8
		NO		1.1	2.5	1.0601	3.56	98.4 (124 nmol/mol)	2.8
Fife Rosyth	08 August 2025	NOx	7842	3.0	2.5	1.0483	3.50	101.4 (265 nmol/mol)	1.5
		NO		1.5	2.5	1.0432	3.50	98.4 (134 nmol/mol)	1.5

Fidas analysers

Station	Date of audit	Analyser Serial no	Zero (µg/m³)	Caldust channel deviation	Total flow⁴	Uncertaint y %	Deviation %
Fife Cupar	20 June 2025	7663	0	0.91	4.76	2.25	-0.88
Fife Dunfermline	19 June 2025	7449	0	1.15	4.70	2.25	-2.18
Fife Kirkcaldy	20 June 2025	6655	0	0.25	4.92	2.25	2.55
Fife Rosyth	08 August 2025	6552	0	0.20	4.73	2.25	-1.38

ee.**ricardo.**com



CERTIFICATE OF CALIBRATION



Page 3 of 3

Date of issue: 04 September 2025

Certificate Number: 7606

Ricardo Energy & Environment ID: ED19050 /7606

The gaseous ambient analysers listed above have been tested for zero response, calibration factor, linearity and converter efficiency (NOx analysers) by documented methods. The factors have been calculated using certified gas standards. The particulate analysers listed above have been tested for sample flow rates and k0 (where appropriate) by documented methods. Note that the test results are valid on the day of test only, as analyser drift over time cannot be quantified. All results for gaseous species are reported in concentration units of nmol/mol or $\mu mol/mol$.

Concentration = F(Output - Zero Response)

Where F = Calibration Factor provided on this certificate

Output = Reading on the data logging system of the analyser

Zero Response = Zero Response provided on this certificate

The calibration results shaded are those that fall within our scope of accreditation, all other results on this certificate are not UKAS accredited, but have been included for completeness.

*****END OF CERTIFICATE*****

ee.ricardo.com

¹ The zero response is the zero reading on the data logging system of the analyser when audit zero gas was introduced to the analysers under test.

² The calibration factor is the multiplying factor required to scale the reading on the data logging system of the analyser into reported concentration units (nmol/mol for NO, NOx, SO2, O3 and µmol/mol for CO). It should be used in conjunction with the zero response. A corrected concentration is calculated using the following equation:

³ Converter eff. is the measured efficiency of the NO2 to NO converter within the oxides of nitrogen analyser under test.

⁴ The measured main flow rate (where this is applicable) is the flow rate through the sensor unit of the TEOM particulate analyser under test. The measured aux flow rate (where this is applicable) is the flow rate through the bypass tubing of the TEOM particulate analyser under test. The measured total flow rate is the total flow rate through the particulate analyser under test. Units of flow are l.min-1, reported at prevailing ambient conditions unless otherwise specified. Where flow rates are highlighted in bold, it indicates that measurements were not made at the analyser sample inlet. These measurements therefore may not accurately reflect analyser performance in normal operation.

⁵ The calculated k0 value (specifically for TEOM analysers) is the calculated k0 spring constant based on tests undertaken with filters of known weight. The % deviation indicates the closeness of the calculated result to the manufacturer's specified value of k0.