



CERTIFICATE OF CALIBRATION



Page 2 of 4

Date of issue:	20 March 2024	10902011
Certificate Number:	6710	
Ricardo Energy & Environment ID:	ED11194/6710	

Glasgow City Council NOx analysers

Analyser Serial no Calibration Converter eff. Zero uncertainty ppb 0.0 1.0121 Glasgow Anderston 05 December 2023 NOx 18-0383 2.5 3.50 99.9 (245nmol/mol) NO 0.6 2.5 0.9991 3.50 99.7 (129nmol/mol) NOx 22-1532 0.6 2.5 1.0771 3.60 101.1 (247nmol/mol) Glasgow Burgher Street 04 December 2023 99.7 (148nmol/mol) NO 0.7 2.6 1.0832 3.53 Glasgow Byres Road 05 December 2023 NOx 4156 -2.4 2.7 1.3026 3.50 99.7 (242nmol/mol) NO 3.1 2.7 1.3181 3.50 98.2 (173nmol/mol) -10.2 2.6 1.1441 3.50 99.6 (203nmol/mol) Glasgow Dumbarton Road 04 December 2023 NOx 4154 2.6 1.1658 3.50 101.8 (129nmol/mol) NO -4.1 Glasgow Nithsdale Road 04 December 2023 NOx 1152030001 -0.8 2.6 1.1603 3.50 100.4 (276nmol/mol) NO -0.4 1.1707 100.6 (201nmol/mol) 2.6 3.50 4155 Glasgow Waulkmillglen Reservoir 06 December 2023 NOx -0.2 2.6 1.1477 3.50 99.2 (261nmol/mol) NO 0.1 2.6 1.1353 3.67 98.4 (157nmol/mol)

## **FIDAS** analysers

Station	Date of audit	Analyser Serial no	Calculated ko⁵	Uncertainty %	Total flow <sup>₄</sup>	Uncertainty %	Main flow	Uncertainty %
Glasgow Anderston	05 December 2023	10105			4.75	2.2		2.2
Glasgow Broomhill	05 December 2023	10106			4.83	2.2		2.2
Glasgow Burgher Street	04 December 2023	18904			5.12	2.2		2.2
Glasgow Dumbarton Road	04 December 2023	8736			4.96	2.2		2.2
Glasgow Nithsdale Road	04 December 2023	6249			4.76	2.2		2.2
Glasgow Waulkmillglen Reservoir	06 December 2023	8735			4.75	2.2		2.2

ee.ricardo.com

IBC-MRA	UKAS CALIBRATION 0401	ERTIFICATE O	F CALIBRA		RICARDO	
Date of issue:			20 March 202	24		Page 3 of 4
Certificate Number:			6710			
Ricardo Energy & Environmen	t ID:		ED11194/67	10		
Glasgow City Council O3 analysers						
Station	Date of Audit	Analyser Serial no	Zero Response <sup>1</sup>	Zero uncertainty ppb	Calibration Factor <sup>2</sup>	Factor uncertainty %
Glasgow Waulkmillglen Reservoir	06 December 2023	3787	0.0	3.0	1.0055	3.3

ee.**ricardo**.com



## **CERTIFICATE OF CALIBRATION**



Page 4 of 4

Date of issue:20 March 2024Certificate Number:6710Ricardo Energy & Environment ID:ED11194/6710

The gaseous ambient analysers listed above have been tested for zero response, calibration factor, linearity and converter efficiency (NOx analysers) by documented methods. The factors have been calculated using certified gas standards. The particulate analysers listed above have been tested for sample flow rates and k0 (where appropriate) by documented methods. Note that the test results are valid on the day of test only, as analyser drift over time cannot be quantified. All results for gaseous species are reported in concentration units of nmol/mol or µmol/mol.

<sup>1</sup> The zero response is the zero reading on the data logging system of the analyser when audit zero gas was introduced to the analysers under test.

 $^2$  The calibration factor is the multiplying factor required to scale the reading on the data logging system of the analyser into reported concentration units (nmol/mol for NO, NOx, SO2, O3 and µmol/mol for CO). It should be used in conjunction with the zero response. A corrected concentration is calculated using the following equation:

Concentration = F(Output - Zero Response)

Where F = Calibration Factor provided on this certificate Output = Reading on the data logging system of the analyser

Zero Response = Zero Response provided on this certificate

<sup>3</sup> Converter eff. is the measured efficiency of the NO<sub>2</sub> to NO converter within the oxides of nitrogen analyser under test.

<sup>4</sup> The measured main flow rate (where this is applicable) is the flow rate through the sensor unit of the TEOM particulate analyser under test. The measured aux flow rate (where this is applicable) is the flow rate through the bypass tubing of the TEOM particulate analyser under test. The measured total flow rate is the total flow rate through the particulate analyser under test. Units of flow are l.min-1, reported at prevailing ambient conditions unless otherwise specified. Where flow rates are highlighted in bold, it indicates that measurements were not made at the analyser sample inlet. These measurements therefore may not accurately reflect analyser performance in normal operation.

<sup>5</sup> The calculated ko value (specifically for TEOM analysers) is the calculated ko spring constant based on tests undertaken with filters of known weight. The % deviation indicates the closeness of the calculated result to the manufacturer's specified value of ko.

The calibration results shaded are those that fall within our scope of accreditation, all other results on this certificate are not UKAS accredited, but have been included for completeness.

\*\*\*\*\*\*END OF CERTIFICATE\*\*\*\*\*

ee.ricardo.com