



CERTIFICATE OF CALIBRATION

Ricardo Energy & Environment 18 Blythswood Square, Glasgow, G2 4BG
Telephone 01225 75233



Page 1 of 3

Approved Signatories:	 □ S. Eaton □ B Stacey □ S Copsey □ S Stratton □ S Telfer □ B Davies □ D Lane □ T Green □ A Nash 							
Signed:	Sey &							
Date of issue:	20 September 2024							
Certificate Number:	7002							
Customer Name and Address:	Scottish Government Water, Air, Soils and Flooding Division Environmental Quality Directorate Scottish Government Victoria Quay Edinburgh EH6 6QQ							
Description:	Calibration factors for the air monitoring station(s) at North Ayrshire Council							
Ricardo Energy & Environment ID:	ED19050 / 7002							
level of confidence of approximately 95% The requirements. This certificate is issued in accordance with the Service. It provides traceability of measureme	ed on a standard uncertainty multiplied by a coverage factor k=2 providing a uncertainty evaluation has been carried out in accordance with UKAS e laboratory accreditation requirements of the United Kingdom Accreditation into the SI system of units and/or to units of measurement realised at the sed national metrology institutes. This certificate may not be reproduced other roval of the issuing laboratory Registered office Shoreham Technical Centre Shoreham-by-Sea West Sussex BN43 5FG Registered in England No. 08229264							

VAT Registration No. GB 212 8365 24

ee.**ricardo**.com



CERTIFICATE OF CALIBRATION



Page 2 of 3

Date of issue: 20 September 2024

Certificate Number: 7002

Ricardo Energy & Environment ID: ED19050 / 7002

North Ayrshire Council

NOx analysers

Station	Date of Audit	Species	Analyser Serial no	Zero Response ¹	Zero uncertainty	Calibration Factor ²	Factor uncertainty	Converter eff.	Converter uncertainty
North Ayrshire Irvine High Street	10 June 2024	NOx NO	19-2513	0.0	nmol/mol 2.6 2.6	1.0988	3.50 3.50	100.6 (191nmol/mol) 101 (112nmol/mol)	(%) 0.4 0.4

Fidas analysers

Station	Date of audit	Analyser Serial no	Zero (µg/m³)	Caldust channel deviation	Total flow⁴	Uncertainty %	Deviation %
North Ayrshire Irvine High Street	10 June 2024	6251	0	0.49	4.50	2.25	-6.23

ee.**ricardo**.com



CERTIFICATE OF CALIBRATION



Page 3 of 3

Date of issue: 20 September 2024

Certificate Number: 7002

Ricardo Energy & Environment ID: ED19050 / 7002

The gaseous ambient analysers listed above have been tested for zero response, calibration factor, linearity and converter efficiency (NOx analysers) by documented methods. The factors have been calculated using certified gas standards. The particulate analysers listed above have been tested for sample flow rates and (where appropriate) by documented methods. Note that the test results are valid on the day of test only, as analyser drift over time cannot be quantified. All results for gaseous species are reported in composition units of nmol/mol or μ mol/mol.

composition = F(Output - Zero Response)

Where F = Calibration Factor provided on this certificate

Output = Reading on the data logging system of the analyser

Zero Response = Zero Response provided on this certificate

The calibration results shaded are those that fall within our scope of accreditation, all other results on this certificate are not UKAS accredited, but have been included for completeness.

*****END OF CERTIFICATE*****

ee.ricardo.com

¹ The zero response is the zero reading on the data logging system of the analyser when audit zero gas was introduced to the analysers under test.

² The calibration factor is the multiplying factor required to scale the reading on the data logging system of the analyser into reported composition units (nmol/mol for NO, NO_x, SO₂, O₃ and μmol/mol for CO). It should be used in conjunction with the zero response. A corrected composition is calculated using the following equation:

 $^{^{3}}$ Converter eff. is the measured efficiency of the NO2 to NO converter within the oxides of nitrogen analyser under test.

⁴ The measured main flow rate (where this is applicable) is the flow rate through the sensor unit of the TEOM particulate analyser under test. The measured aux flow rate (where this is applicable) is the flow rate through the bypass tubing of the TEOM particulate analyser under test. The measured total flow rate is the total flow rate through the particulate analyser under test. Units of flow are l.min-1, reported at prevailing ambient conditions unless otherwise specified. Where flow rates are highlighted in bold, it indicates that measurements were not made at the analyser sample inlet. These measurements therefore may not accurately reflect analyser performance in normal operation.

⁵ The calculated k0 value (specifically for TEOM analysers) is the calculated k0 spring constant based on tests undertaken with filters of known weight. The % deviation indicates the closeness of the calculated result to the manufacturer's specified value of k0.