



CERTIFICATE OF CALIBRATION

Ricardo Energy & Environment 18 Blythswood Square, Glasgow, G2 4BG

Telephone 01235 753434



Page 1 of 3

| Approved Signatories: | | N Rand B Davies | □ B Stacey□ S Stratton□ S Telfer☑ S Gray□ F. Elmer | | | | |
|---|---|---|--|--|--|--|--|
| Signed: | Sep 8 | | | | | | |
| Date of issue: | 04 September 2025 | | | | | | |
| Certificate Number: | 7619 | | | | | | |
| Customer Name and Address: | | | | | | | |
| Description: | | on factors for the a narkshire Council | ir monitoring station(s) at | | | | |
| Ricardo Energy & Environment ID: | ED1905 |) /7619 | | | | | |
| The reported expanded uncertainties are based on a standard uncertainty multiplied by a coverage factor k=2 providing a level of confidence of approximately 95% The uncertainty evaluation has been carried out in accordance with UKAS requirements. This certificate is issued in accordance with the laboratory accreditation requirements of the United Kingdom Accreditation Service. It provides traceability of measurement to the SI system of units and/or to units of measurement realised at the National Physical Laboratory or other recognised national metrology institutes. This certificate may not be reproduced other than in full, except with the prior written approval of the issuing laboratory Registered office Ricardo Energy & Environment Shoreham Technical Centre | | | | | | | |
| 18 Blythswood Square (2 nd Floor), Glasgow, G2 4BG Tel: 01235 753205 | Shoreham-by-Sea West Sussex BN43 5FG Registered in England 08229264 | No. | | | | | |

VAT Registration No. GB 212 8365 24

ee.**ricardo**.com



CERTIFICATE OF CALIBRATION



Page 2 of 3

Date of issue: 04 September 2025

Certificate Number: 7619

Ricardo Energy & Environment ID: ED19050 /7619

North Lanarkshire Council

NOx analysers

| NOX analysers | | | | | | | | | |
|--|------------------|---------|-----------------------|-------------------------------|---------------------------------|------------------------------------|----------------------------|------------------------------------|---------------------------|
| Station | Date of Audit | Species | Analyser Serial no | Zero Response ¹ | Zero uncertainty nmol/mol | Calibration Factor ² | Factor uncertainty % | Converter eff. (%) ³ | Converter uncertainty (%) |
| N Lanarkshire Coatbridge Whifflet A725 | 24 June 2025 | NOx | 21-1547 | 6.4 | 2.6 | 1.0811 | 3.50 | 98.1 (288 nmol/mol) | 0.4 |
| | | NO | | 4.3 | 2.6 | 1.0726 | 3.50 | 96.8 (149 nmol/mol) | 0.4 |
| N Lanarkshire Airdrie Kenilworth Drive | 23 June 2025 | NOx | 23-0151 | -0.1 | 2.5 | 1.0450 | 3.55 | 99.5 (266 nmol/mol) | 2.9 |
| | | NO | | 0.5 | 2.5 | 1.0433 | 3.64 | 99.8 (146 nmol/mol) | 2.9 |
| N Lanarkshire Motherwell Adele Street | 23 June 2025 | NOx | 21-0951 | 1.0 | 2.5 | 0.8748 | 3.50 | 101.6 (272 nmol/mol) | 0.6 |
| | | NO | | 1.0 | 2.5 | 0.8687 | 3.50 | 100.8 (132 nmol/mol) | 0.6 |
| N Lanarkshire Motherwell 2 | 23 June 2025 | NOx | 23-0167 | 1.7 | 2.6 | 1.0992 | 3.50 | 100.5 (278 nmol/mol) | 1.4 |
| | | NO | | 1.4 | 2.6 | 1.0972 | 3.50 | 100.8 (146 nmol/mol) | 1.4 |
| N Lanarkshire Ravenscraig 26 Ju Plantation Road | 26 June 2025 | NOx | 23-0552 | 6.4 | 2.5 | 1.0205 | 3.50 | 100.4 (288 nmol/mol) | 1.3 |
| | | NO | | 6.9 | 2.5 | 1.0190 | 3.50 | 98.6 (171 nmol/mol) | 1.3 |
| N Lanarkshire Uddingston New 26 Edinburgh Road | 26 June 2025 | NOx | 22-2130 | 0.0 | 2.6 | 1.0787 | 3.50 | 100.1 (297 nmol/mol) | 1.4 |
| | | NO | | 0.5 | 2.6 | 1.0755 | 3.50 | 100.1 (157 nmol/mol) | 1.4 |

Fidas analysers

| Station | Date of audit | Analyser Serial no | Zero (µg/m³) | Caldust channel deviation | Total flow⁴ | Uncertaint y % | Deviation % |
|--|---------------|-----------------------|-----------------|---------------------------------|-------------|-------------------|-------------|
| N Lanarkshire Coatbridge Whifflet A725 | 24 June 2025 | 14213 | 0 | 0.45 | 4.77 | 2.25 | -0.55 |
| N Lanarkshire Motherwell Adele Street | 23 June 2025 | 9553 | 0 | 0.12 | 4.83 | 2.25 | 0.71 |
| N Lanarkshire Ravenscraig Plantation Road | 26 June 2025 | 12143 | 0 | 1.28 | 4.74 | 2.25 | -1.20 |
| N Lanarkshire Uddingston New Edinburgh Road | 26 June 2025 | 15863 | 0 | 0.17 | 4.92 | 2.25 | 2.43 |

ee.**ricardo**.com



CERTIFICATE OF CALIBRATION



Page 3 of 3

Date of issue: 04 September 2025

Certificate Number: 7619

Ricardo Energy & Environment ID: ED19050 /7619

The gaseous ambient analysers listed above have been tested for zero response, calibration factor, linearity and converter efficiency (NOx analysers) by documented methods. The factors have been calculated using certified gas standards. The particulate analysers listed above have been tested for sample flow rates and (where appropriate) by documented methods. Note that the test results are valid on the day of test only, as analyser drift over time cannot be quantified. All results for gaseous species are reported in concentration units of nmol/mol or µmol/mol.

Concentration = F(Output - Zero Response)

Where F = Calibration Factor provided on this certificate

Output = Reading on the data logging system of the analyser

Zero Response = Zero Response provided on this certificate

The calibration results shaded are those that fall within our scope of accreditation, all other results on this certificate are not UKAS accredited, but have been included for completeness.

*****END OF CERTIFICATE*****

ee.**ricardo**.com

¹ The zero response is the zero reading on the data logging system of the analyser when audit zero gas was introduced to the analysers under test.

² The calibration factor is the multiplying factor required to scale the reading on the data logging system of the analyser into reported concentration units (nmol/mol for NO, NOx, SO2, O3 and µmol/mol for CO). It should be used in conjunction with the zero response. A corrected concentration is calculated using the following equation:

³ Converter eff. is the measured efficiency of the NO2 to NO converter within the oxides of nitrogen analyser under test.

⁴ The measured main flow rate (where this is applicable) is the flow rate through the sensor unit of the TEOM particulate analyser under test. The measured aux flow rate (where this is applicable) is the flow rate through the bypass tubing of the TEOM particulate analyser under test. The measured total flow rate is the total flow rate through the particulate analyser under test. Units of flow are l.min-1, reported at prevailing ambient conditions unless otherwise specified. Where flow rates are highlighted in bold, it indicates that measurements were not made at the analyser sample inlet. These measurements therefore may not accurately reflect analyser performance in normal operation.

⁵ The calculated k0 value (specifically for TEOM analysers) is the calculated k0 spring constant based on tests undertaken with filters of known weight. The % deviation indicates the closeness of the calculated result to the manufacturer's specified value of k0.