UKAS		DF CALIBRATION 8 Blythswood Square, Glasgow, G2 4BG 235 753434	ARDO
0401			Page 1 of 3
Approved Signatories:		 S. Eaton S Copsey N Rand B Davies D Lane 	 B Stacey S Stratton S Telfer S Gray T Green
Signed:	Stelfer		
Date of issue:	20 March 2024		
Certificate Number:	6715		
Description:		Edinburgh EH6 6QQ Calibration factors for the air r Renfrewshire Council	nonitoring station(s) at
Ricardo Energy & Environment ID:		ED11194/6715	
The reported expanded uncertainties are based on a level of confidence of approximately 95% The uncert requirements. This certificate is issued in accordance with the labor Service. It provides traceability of measurement to t National Physical Laboratory or other recognised nat than in full, except with the prior written approval of	ainty evaluation has been carrie atory accreditation requiremen ne SI system of units and/or to u ional metrology institutes. This	d out in accordance with UKAS ts of the United Kingdom Accreditation nits of measurement realised at the	
Ricardo Energy & Environment 18 Blythswood Square (2 nd Floor), Glasgow, G2 49G Tel: 01235 753205	Registered office Shoreham Technica Shoreham-by-Sea West Sussex BN43 5FG Registered in Engl 06229264 VAT Registration N GB 212 8365 24	and No.	
		ee. ricardo .c	om



CERTIFICATE OF CALIBRATION



 Page 2 of 3

 Date of issue:
 20 March 2024

 Certificate Number:
 6715

 Ricardo Energy & Environment ID:
 ED11194/6715

Renfrewshire Council NOx analysers

Station	Date of Audit	Species	Analyser Serial no	Zero Response ¹	Zero uncertainty nmol/mol	Calibration Factor ²	Factor uncertainty %	Converter eff. (%) ³
Renfrew Cockels Loan	13 February 2024	NOx	1108947668	-1.1	2.5	0.8112	3.56	101.3 (255nmol/mol)
		NO		-1.2	2.5	0.8170	3.56	101.4 (120nmol/mol)
Renfrewshire Inchinnan Road	06 December 2023	NOx	18-1174	0.0	2.6	1.0238	3.50	100 (263nmol/mol)
		NO		1.0	2.5	1.0305	3.50	100 (126nmol/mol)

FIDAS analysers

Station	Date of audit	Analyser Serial no	Calculated ko⁵	Uncertainty %	Total flow ^₄	Uncertainty %	Main flow	Uncertainty %
Renfrewshire Johnstone	06 December 2023	7735			5.04	2.2		2.2

ee.**ricardo**.com



CERTIFICATE OF CALIBRATION



Page 3 of 3

Date of issue:	20 March 2024
Certificate Number:	6715
Ricardo Energy & Environment ID:	ED11194/6715

The gaseous ambient analysers listed above have been tested for zero response, calibration factor, linearity and converter efficiency (NOx analysers) by documented methods. The factors have been calculated using certified gas standards. The particulate analysers listed above have been tested for sample flow rates and k0 (where appropriate) by documented methods. Note that the test results are valid on the day of test only, as analyser drift over time cannot be quantified. All results for gaseous species are reported in concentration units of nmol/mol or µmol/mol.

¹ The zero response is the zero reading on the data logging system of the analyser when audit zero gas was introduced to the analysers under test.

² The calibration factor is the multiplying factor required to scale the reading on the data logging system of the analyser into reported concentration units (nmol/mol for NO, NOx, SO2, O3 and µmol/mol for CO). It should be used in conjunction with the zero response. A corrected concentration is calculated using the following equation:

Concentration = F(Output - Zero Response) Where F = Calibration Factor provided on this certificate Output = Reading on the data logging system of the analyser

Zero Response = Zero Response provided on this certificate

 $^{\rm 3}$ Converter eff. is the measured efficiency of the NO2 to NO converter within the oxides of nitrogen analyser under test.

⁴ The measured main flow rate (where this is applicable) is the flow rate through the sensor unit of the TEOM particulate analyser under test. The measured aux flow rate (where this is applicable) is the flow rate through the bypass tubing of the TEOM particulate analyser under test. The measured total flow rate is the total flow rate through the particulate analyser under test. Units of flow are l.min-1, reported at prevailing ambient conditions unless otherwise specified. Where flow rates are highlighted in bold, it indicates that measurements were not made at the analyser sample inlet. These measurements therefore may not accurately reflect analyser proformance in normal operation.

⁵ The calculated k0 value (specifically for TEOM analysers) is the calculated k0 spring constant based on tests undertaken with filters of known weight. The % deviation indicates the closeness of the calculated result to the manufacturer's specified value of k0.

The calibration results shaded are those that fall within our scope of accreditation, all other results on this certificate are not UKAS accredited, but have been included for completeness.

******END OF CERTIFICATE******

ee.ricardo.com