		F CALIBRATION lythswood Square, Glasgow, G2 5 753434	246G RICARDO	
				Page 1 of 3
Approved Signatories:		<ul> <li>S. E.</li> <li>S Co</li> <li>N Ra</li> <li>B Da</li> <li>D Lar</li> </ul>	npsey	<ul> <li>B Stacey</li> <li>S Stratton</li> <li>S Telfer</li> <li>S Gray</li> <li>T Green</li> </ul>
Signed:	Stelk			
Date of issue:	20 March 2024			
Certificate Number:	6717			
Customer Name and Address:		Scottish Governn Water, Air, Soils Environmental Qi Scottish Governn Victoria Quay Edinburgh EH6 6QQ	and Flooding Division uality Directorate	
Description:		Calibration factor South Ayrshire Co	s for the air monitorin ouncil	ng station(s) at
Ricardo Energy & Environment ID:		ED11194/6717		
The reported expanded uncertainties are based on a stand- level of confidence of approximately 95% The uncertainty of requirements. This certificate is issued in accordance with the laboratory. Service. It provides traceability of measurement to the SI sy National Physical Laboratory or other recognised national than in full, except with the prior written approval of the is	evaluation has been carrie accreditation requiremen ystem of units and/or to u metrology institutes. This	d out in accordance with UK ts of the United Kingdom Ac inits of measurement realise	AS creditation d at the	
<b>Ricardo Energy &amp; Environment</b> 18 Blythswood Square (2 <sup>nd</sup> Floor), Glasgow, G2 4BG Tel: 01235 763205	Registered office Shoreham Technica Shoreham-by-Sea West Sussex BN43 SFG Registered in Engla 08229264 VAT Registration N GB 212 8365 24	and No.		
			ee. <b>ricardo</b> .com	



CERTIFICATE OF CALIBRATION



Page 2 of 3

Date of issue:	20 March 2024
Certificate Number:	6717
Ricardo Energy & Environment ID:	ED11194/6717

South Ayrshire Council

NOx analysers

Station	Date of Audit	Species	Analyser Serial no	Zero Response <sup>1</sup>	Zero uncertainty ppb	Calibration Factor <sup>2</sup>	Factor uncertainty %	Converter eff. (%) <sup>3</sup>
South Ayrshire Ayr Harbour	12 December 2023	NOx	22-0933	2.0	2.5	0.9085	3.50	99.6 (258nmol/mol)
		NO		3.0	2.5	0.8918	3.58	100 (127nmol/mol)
South Ayrshire Ayr High Street	12 December 2023	NOx	22-0337	0.0	2.5	1.0363	3.50	100 (261nmol/mol)
		NO		1.0	2.5	1.0301	3.50	100 (127nmol/mol)

FIDAS analysers

Station	Date of audit	Analyser Serial no	Calculated ko⁵	Uncertainty %	Total flow⁴	Uncertainty %	Main flow	Uncertainty %
South Ayrshire Ayr Harbour	12 December 2023	15672			5.00	2.2		2.2
South Ayrshire Ayr High Street	12 December 2023	15673			5.07	2.2		2.2

ee.ricardo.com



Date of issue:

**CERTIFICATE OF CALIBRATION** 



Page 3 of 3

Certificate Number: 6717 Ricardo Energy & Environment ID: ED11194/6717

> The gaseous ambient analysers listed above have been tested for zero response, calibration factor, linearity and converter efficiency (NOx analysers) by documented methods. The factors have been calculated using certified gas standards. The particulate analysers listed above have been tested for sample flow rates and k0 (where appropriate) by documented methods. Note that the test results are valid on the day of test only, as analyser drift over time cannot be quantified. All results for gaseous species are reported in concentration units of nmol/mol or umol/mol.

20 March 2024

<sup>1</sup> The zero response is the zero reading on the data logging system of the analyser when audit zero gas was introduced to the analysers under test.

<sup>2</sup> The calibration factor is the multiplying factor required to scale the reading on the data logging system of the analyser into reported concentration units (nmol/mol for NO, NOx, SO2, O3 and µmol/mol for CO). It should be used in conjunction with the zero response. A corrected concentration is calculated using the following equation:

Concentration = F(Output - Zero Response)

Where F = Calibration Factor provided on this certificate

Output = Reading on the data logging system of the analyser

Zero Response = Zero Response provided on this certificate

<sup>3</sup> Converter eff. is the measured efficiency of the NO2 to NO converter within the oxides of nitrogen analyser under test.

<sup>4</sup> The measured main flow rate (where this is applicable) is the flow rate through the sensor unit of the TEOM particulate analyser under test. The measured aux flow rate (where this is applicable) is the flow rate through the bypass tubing of the TEOM particulate analyser under test. The measured total flow rate is the total flow rate through the particulate analyser under test. Units of flow are I.min-1, reported at prevailing ambient conditions unless otherwise specified. Where flow rates are highlighted in bold, it indicates that measurements were not made at the analyser sample inlet. These measurements therefore may not accurately reflect analyser performance in normal operation

<sup>5</sup> The calculated ko value (specifically for TEOM analysers) is the calculated ko spring constant based on tests undertaken with filters of known weight. The % deviation indicates the closeness of the calculated result to the manufacturer's specified value of ko.

The calibration results shaded are those that fall within our scope of accreditation, all other results on this certificate are not UKAS accredited, but have been included for completeness.

\*\*\*\*\*\*END OF CERTIFICATE\*\*\*\*\*\*

ee.ricardo.com