



CERTIFICATE OF CALIBRATION

Ricardo Energy & Environment 18 Blythswood Square, Glasgow, G2 4BG

Telephone 01235 753434



Page 1 of 3

Approved Signatories:			S. Eaton S Copsey N Rand B Davies D Lane	□ B Stacey □ S Stratton ☑ S Telfer □ S Gray □ T Green			
Signed:	Stelker						
Date of issue:	20 March 2024						
Certificate Number:	6718						
Customer Name and Address:		Scottish Government Water, Air, Soils and Flooding Division Environmental Quality Directorate Scottish Government Victoria Quay Edinburgh EH6 6QQ					
Description:	Calibration factors for the air monitoring station(s) at South Lanarkshire Council						
Ricardo Energy & Environment ID:	ED11194/6718						
The reported expanded uncertainties are based on a stal level of confidence of approximately 95% The uncertaint requirements. This certificate is issued in accordance with the laborato Service. It provides traceability of measurement to the S National Physical Laboratory or other recognised nation, than in full, except with the prior written approval of the Ricardo Energy & Environment Ricardo Energy & Environment 18 Blythswood Square (2 nd Floor), Glasgow, G2 4BG Tel: 01235 753205	y evaluation has been car ry accreditation requirem I system of units and/or t al metrology institutes. Th	rried out in accord ments of the Unite o units of measur nis certificate may	dance with UKAS d Kingdom Accreditation ement realised at the				
	VAT Registration No. GB 212 8365 24						

ee.**ricardo**.com



CERTIFICATE OF CALIBRATION



Page 2 of 3

Date of issue: 20 March 2024

Certificate Number: 6718

Ricardo Energy & Environment ID: ED11194/6718

South Lanarkshire Council

NOx analysers

NOX analysers								
Station	Date of Audit	Species	Analyser Serial no	Zero Response ¹	Zero uncertainty ppb	Calibration Factor ²	Factor uncertainty %	Converter eff. (%) ³
South Lanarkshire Blantyre	12 December 2023	NOx	18-0740	2.0	2.5	0.8374	3.61	100 (264nmol/mol)
		NO		1.0	2.5	0.8343	3.55	99.5 (167nmol/mol)
South Lanarkshire Cambuslang	27 February 2024	NOx	23-1956	0.5	2.5	1.0353	3.50	100.4 (253nmol/mol)
		NO		-0.1	2.5	1.0272	3.50	99.4 (142nmol/mol)
South Lanarkshire East Kilbride	27 February 2024	NOx	CM07460075	0.2	2.6	1.2527	3.50	98 (250nmol/mol)
		NO		0.1	2.6	1.2504	3.50	100.8 (145nmol/mol)
South Lanarkshire Lanark	11 December 2023	NOx	CM10020067	0.1	2.5	0.9006	3.50	99.4 (295nmol/mol)
		NO		-0.1	2.5	0.9021	3.50	99.6 (213nmol/mol)
South Lanarkshire Raith Interchange 2	14 December 2023	NOx	CM07460076	-0.2	2.5	0.9382	3.50	100 (253nmol/mol)
		NO		-0.1	2.5	0.9424	3.50	99.5 (170nmol/mol)
South Lanarkshire Rutherglen	14 December 2023	NOx	CM10220001	0.9	2.6	1.2035	3.50	100 (283nmol/mol)
		NO		1.2	2.6	1.2045	3.50	100 (183nmol/mol)

FIDAS analysers

TIBITIO UTICITY SCITS								
Station	Date of audit	Analyser Serial no	Calculated ko⁵	Uncertainty %	Total flow⁴	Uncertainty %	Main flow	Uncertainty %
South Lanarkshire Blantyre	12 December 2023	9750			5.00	2.2		2.2
South Lanarkshire Cambuslang	12 December 2023	8256			4.99	2.2		2.2
South Lanarkshire East Kilbride	27 February 2024	8257			5.15	2.2		2.2
South Lanarkshire Lanark	11 December 2023	6248			5.23	2.2		2.2
South Lanarkshire Raith Interchange 2	14 December 2023	9719			4.91	2.2		2.2
South Lanarkshire Rutherglen	14 December 2023	8140			4.84	2.2		2.2

ee.**ricardo**.com





CERTIFICATE OF CALIBRATION



Page 3 of 3

Date of issue: 20 March 2024

Certificate Number: 6718

Ricardo Energy & Environment ID: ED11194/6718

The gaseous ambient analysers listed above have been tested for zero response, calibration factor, linearity and converter efficiency (NOx analysers) by documented methods. The factors have been calculated using certified gas standards. The particulate analysers listed above have been tested for sample flow rates and k0 (where appropriate) by documented methods. Note that the test results are valid on the day of test only, as analyser drift over time cannot be quantified. All results for gaseous species are reported in concentration units of nmol/mol or $\mu mol/mol$.

Concentration = F(Output - Zero Response)

Where F = Calibration Factor provided on this certificate

Output = Reading on the data logging system of the analyser

Zero Response = Zero Response provided on this certificate

The calibration results shaded are those that fall within our scope of accreditation, all other results on this certificate are not UKAS accredited, but have been included for completeness.

******END OF CERTIFICATE*****

ee.**ricardo.**com

¹ The zero response is the zero reading on the data logging system of the analyser when audit zero gas was introduced to the analysers under test.

 $^{^2}$ The calibration factor is the multiplying factor required to scale the reading on the data logging system of the analyser into reported concentration units (nmol/mol for NO, NOx, SO2, O3 and μ mol/mol for CO). It should be used in conjunction with the zero response. A corrected concentration is calculated using the following equation:

³ Converter eff. is the measured efficiency of the NO₂ to NO converter within the oxides of nitrogen

⁴ The measured main flow rate (where this is applicable) is the flow rate through the sensor unit of the TEOM particulate analyser under test. The measured aux flow rate (where this is applicable) is the flow rate through the bypass tubing of the TEOM particulate analyser under test. The measured total flow rate is the total flow rate through the particulate analyser under test. Units of flow are l.min-1, reported at prevailing ambient conditions unless otherwise specified. Where flow rates are highlighted in bold, it indicates that measurements were not made at the analyser sample inlet. These measurements therefore may not accurately reflect analyser performance in normal operation.

⁵ The calculated ko value (specifically for TEOM analysers) is the calculated ko spring constant based on tests undertaken with filters of known weight. The % deviation indicates the closeness of the calculated result to the manufacturer's specified value of ko.