	CERTIFICATE OF to Energy & Environment 18 Bly Telephone 01235	thswood Square, Glasgow, (		
0401				Page 1 of 3
Approved Signatories:			S. Eaton D Hector N Rand B Davies	<ul> <li>□ B Stacey</li> <li>□ S Stratton</li> <li>☑ S Telfer</li> <li>□ S Gray</li> </ul>
	Stelfer			
Signed:				
Date of issue: 2	7 September 2022			
Certificate Number: 5	949			
Customer Name and Address:		South Lanarkshire ( Ground Floor CB05 Montrose House 154 Montrose Cres Hamilton ML3 6LB	1	
Description:		Calibration factor South Lanarkshir		toring station(s) at
Ricardo Energy & Environment ID:		594	9	
The reported expanded uncertainties are based on a stat level of confidence of approximately 95% The uncertaint requirements. This certificate is issued in accordance with the laborato Service. It provides traceability of measurement to the S National Physical Laboratory or other recognised nation. than in full, except with the prior written approval of the	ty evaluation has been carried of ry accreditation requirements of system of units and/or to unit al metrology institutes. This cer	out in accordance with UK of the United Kingdom Ac ts of measurement realise	AS creditation d at the	
<b>Ricardo Energy &amp; Environment</b> 18 Blythewood Square (2 <sup>nd</sup> Floor), Glaggow, 22 4BG Tel: 01235 753205	Registered office Shoreham Technical Centre Shoreham-by-Sea West Sussex BN43 5FG Registered in England No. 08229264 VAT Registration No. GB 212 8305 24		ee. <b>ricardo</b> .com	



CERTIFICATE OF CALIBRATION



Page 2 of 3

Date of issue:	27 September 2022
Certificate Number:	5949
Ricardo Energy & Environment ID:	5949

South Lanarkshire Council

NOx analysers								
Station	Date of Audit	Species	Analyser Serial no	Zero Response <sup>1</sup>	Zero uncertainty nmol/mol	Calibration Factor <sup>2</sup>	Factor uncertainty %	Converter eff. (%) <sup>3</sup>
South Lanarkshire Hamilton	17 August 2022	NOx	CM07460073	-2.8	2.7	1.3069	3.50	99.5
		NO		-1.3	2.7	1.3088	3.50	
South Lanarkshire Uddingston	17 August 2022	NOx	CM10020068	-0.3	2.6	1.0813	3.50	99.2
		NO		-0.5	2.6	1.0834	3.50	

PM10 analysers

Station	Date of audit	Analyser Serial no	Calculated ko <sup>₅</sup>	Uncertainty %	Total flow <sup>4</sup>	Uncertainty %	Main flow	Uncertaint y %
South Lanarkshire Hamilton	15 July 2022	8258			4.73	2.2		2.2
South Lanarkshire Uddingston	17 August 2022	6247			4.71	2.2		2.2

ee.**ricardo**.com



**CERTIFICATE OF CALIBRATION** 



Page 3 of 3

Date of issue:	27 September 2022	
Certificate Number:	5949	
Ricardo Energy & Environment ID:	5949	

The gaseous ambient analysers listed above have been tested for zero response, calibration factor, linearity and converter efficiency (NOx analysers) by documented methods. The factors have been calculated using certified gas standards. The particulate analysers listed above have been tested for sample flow rates and k0 (where appropriate) by documented methods. Note that the test results are valid on the day of test only, as analyser drift over time cannot be quantified. All results for gaseous species are reported in concentration units of nmol/mol.

<sup>1</sup> The zero response is the zero reading on the data logging system of the analyser when audit zero gas was introduced to the analysers under test.

<sup>2</sup> The calibration factor is the multiplying factor required to scale the reading on the data logging system of the analyser into reported concentration units (nmol/mol for NO, NOx, SO2, O3 and µmol/mol for CO). It should be used in conjunction with the zero response. A corrected concentration is calculated using the following equation:

Concentration = F(Output - Zero Response)

Where F = Calibration Factor provided on this certificate

Output = Reading on the data logging system of the analyser

Zero Response = Zero Response provided on this certificate

<sup>3</sup> Converter eff. is the measured efficiency of the NO<sub>2</sub> to NO converter within the oxides of nitrogen analyser under test.

<sup>4</sup> The measured main flow rate (where this is applicable) is the flow rate through the sensor unit of the TEOM particulate analyser under test. The measured aux flow rate (where this is applicable) is the flow rate through the bypass tubing of the TEOM particulate analyser under test. The measured total flow rate is the total flow rate through the particulate analyser under test. Units of flow are l.min-1, reported at prevailing ambient conditions unless otherwise specified. Where flow rates are highlighted in bold, it indicates that measurements were not made at the analyser sample inlet. These measurements therefore may not accurately reflect analyser performance in normal operation.

<sup>5</sup> The calculated ko value (specifically for TEOM analysers) is the calculated ko spring constant based on tests undertaken with filters of known weight. The % deviation indicates the closeness of the calculated result to the manufacturer's specified value of ko.

The calibration results shaded are those that fall within our scope of accreditation, all other results on this certificate are not UKAS accredited, but have been included for completeness.

ee.ricardo.com