	CERTIFICATE OF Ricardo Energy & Environment 18 Blyth		
UKAS CALIBRATION 0401	Telephone 01235 7	53434 RIC.	ARDO
			Page 1 of 3
Approved Signatories:		 S. Eaton S Copsey N Rand B Davies D Lane 	 B Stacey S Stratton S Telfer S Gray T Green
Signed:	Stelfer		
Date of issue:	21 March 2024		
Certificate Number:	6723		
Customer Name and Address:	G N 1 H	outh Lanarkshire Council Ground Floor CB051 Aontrose House .54 Montrose Crescent Hamilton AL3 6LB	
Description:		alibration factors for the air fouth Lanarkshire Council	monitoring station(s) at
Ricardo Energy & Environment ID:	E	D12686/6723	
The reported expanded uncertainties are based on level of confidence of approximately 95% The unc requirements. This certificate is issued in accordance with the lal Service. It provides traceability of measurement t National Physical Laboratory or other recognised than in full, except with the prior written approva	ertainty evaluation has been carried or poratory accreditation requirements of o the SI system of units and/or to units national metrology institutes. This cert	ut in accordance with UKAS f the United Kingdom Accreditation of measurement realised at the	
Ricardo Energy & Environment 18 Blythswood Square (2 nd Floor), Glasgow, G2 4BG	Registered office Shoreham Technical Cer Shoreham-by-Sea West Sussex BN43 5FG Registered in England		
Tel: 01235 763205	08229264 VAT Registration No. GB 212 8365 24		
		ee.ricardo.	com



CERTIFICATE OF CALIBRATION



Page 2 of 3

Date of issue:	21 March 2024
Certificate Number:	6723
Ricardo Energy & Environment ID:	ED12686/6723

South Lanarkshire Council

NOx analysers

Station	Date of Audit	Species	Analyser Serial no	Zero Response ¹	Zero uncertainty nmol/mol	Calibration Factor ²	Factor uncertainty %	Converter eff. $(\%)^3$
South Lanarkshire Hamilton	11 December 2023	NOx	CM07460073	-0.5	2.6	1.1829	3.71	99.1 (259nmol/mol)
		NO		0.0	2.6	1.1813	3.69	98.6 (159nmol/mol)
South Lanarkshire Uddingston	11 December 2023	NOx	CM10020068	-0.4	2.5	0.9622	3.50	101 (296nmol/mol)
		NO		-0.4	2.5	0.9601	3.50	98.6 (196nmol/mol)

FIDAS analysers

Station	Date of audit	Analyser Serial no	Calculated ko⁵	Uncertainty %	Total flow⁴	Uncertainty %	Main flow	Uncertainty %
South Lanarkshire Hamilton	11 December 2023	8258			5.03	2.2		2.2
South Lanarkshire Uddingston	11 December 2023	6267			4.96	2.2		2.2

ee.ricardo.com



CERTIFICATE OF CALIBRATION



Page 3 of 3

Certificate Number:

Ricardo Energy & Environment ID:

Date of issue:

ED12686/6723

6723

21 March 2024

The gaseous ambient analysers listed above have been tested for zero response, calibration factor, linearity and converter efficiency (NOx analysers) by documented methods. The factors have been calculated using certified gas standards. The particulate analysers listed above have been tested for sample flow rates and k0 (where appropriate) by documented methods. Note that the test results are valid on the day of test only, as analyser drift over time cannot be quantified. All results for gaseous species are reported in concentration units of nmol/mol or µmol/mol.

¹ The zero response is the zero reading on the data logging system of the analyser when audit zero gas was introduced to the analysers under test.

² The calibration factor is the multiplying factor required to scale the reading on the data logging system of the analyser into reported concentration units (nmol/mol for NO, NOx, SO2, O3 and µmol/mol for CO). It should be used in conjunction with the zero response. A corrected concentration is calculated using the following equation:

Concentration = F(Output - Zero Response)

Where F = Calibration Factor provided on this certificate

Output = Reading on the data logging system of the analyser

Zero Response = Zero Response provided on this certificate

³ Converter eff. is the measured efficiency of the NO₂ to NO converter within the oxides of nitrogen analyser under test.

⁴ The measured main flow rate (where this is applicable) is the flow rate through the sensor unit of the TEOM particulate analyser under test. The measured aux flow rate (where this is applicable) is the flow rate through the bypass tubing of the TEOM particulate analyser under test. The measured total flow rate is the total flow rate through the particulate analyser under test. Units of flow are l.min-1, reported at prevailing ambient conditions unless otherwise specified. Where flow rates are highlighted in bold, it indicates that measurements were not made at the analyser sample inlet. These measurements therefore may not accurately reflect analyser performance in normal operation.

⁵ The calculated ko value (specifically for TEOM analysers) is the calculated ko spring constant based on tests undertaken with filters of known weight. The % deviation indicates the closeness of the calculated result to the manufacturer's specified value of ko.

The calibration results shaded are those that fall within our scope of accreditation, all other results on this certificate are not UKAS accredited, but have been included for completeness.

******END OF CERTIFICATE*****

ee.ricardo.com