



CERTIFICATE OF CALIBRATION

Ricardo Energy & Environment 18 Blythswood Square, Glasgow, G2 4BG

Telephone 01235 753434



Page 1 of 3

Approved Signatories:			S. Eaton S Copsey N Rand B Davies D Lane	□ B Stacey □ S Stratton □ S Telfer □ S Gray □ T Green			
Signed: Date of issue: Certificate Number:	Stelfer 21 March 2024 6720						
Customer Name and Address:			Soils and Floodintal Quality Directory				
Description:		Calibration factors for the air monitoring station(s) at West Dunbartonshire Council					
Ricardo Energy & Environment ID:		ED11194/6	720				
The reported expanded uncertainties are based on a level of confidence of approximately 95% The uncert requirements. This certificate is issued in accordance with the labor Service. It provides traceability of measurement to the National Physical Laboratory or other recognised nat than in full, except with the prior written approval of Ricardo Energy & Environment 18 Blythswood Square (2nd Floor), Glasgow, G2 4BG Tel: 01235 753205	ainty evaluation has been car atory accreditation requirem ne SI system of units and/or to ional metrology institutes. Th	ried out in accorda ents of the United I to units of measurer is certificate may n al Centre	nce with UKAS Kingdom Accreditation nent realised at the				

ee.**ricardo**.com



CERTIFICATE OF CALIBRATION



Page 2 of 3

Date of issue: 21 March 2024

Certificate Number: 6720

Ricardo Energy & Environment ID: ED11194/6720

West Dunbartonshire Council

NOx analysers

TTOK GITGITOCIO								
Station	Date of Audit	Species	Analyser Serial no	Zero Response ¹	Zero uncertainty nmol/mol	Calibration Factor ²	Factor uncertainty %	Converter eff. (%) ³
West Dunbartonshire Clydebank	01 February 2024	NOx	19-0112	0.0	2.5	1.0703	3.50	101.3 (241nmol/mol)
		NO		1.0	2.5	1.0520	3.50	100 (132nmol/mol)

FIDAS analysers

Station	Date of audit	Analyser Serial no	Calculated ko⁵	Uncertainty %	Total flow⁴	Uncertainty %	Main flow	Uncertainty %
West Dunbartonshire Clydebank	01 February 2024	6250			4.79	2.2		2.2

ee.**ricardo**.com





CERTIFICATE OF CALIBRATION



Page 3 of 3

Date of issue: 21 March 2024

Certificate Number: 6720

Ricardo Energy & Environment ID: ED11194/6720

The gaseous ambient analysers listed above have been tested for zero response, calibration factor, linearity and converter efficiency (NOx analysers) by documented methods. The factors have been calculated using certified gas standards. The particulate analysers listed above have been tested for sample flow rates and k0 (where appropriate) by documented methods. Note that the test results are valid on the day of test only, as analyser drift over time cannot be quantified. All results for gaseous species are reported in concentration units of nmol/mol or µmol/mol.

Concentration = F(Output - Zero Response)

Where F = Calibration Factor provided on this certificate

Output = Reading on the data logging system of the analyser

Zero Response = Zero Response provided on this certificate

The calibration results shaded are those that fall within our scope of accreditation, all other results on this certificate are not UKAS accredited, but have been included for completeness.

******END OF CERTIFICATE*****

ee.ricardo.com

¹ The zero response is the zero reading on the data logging system of the analyser when audit zero gas was introduced to the analysers under test.

² The calibration factor is the multiplying factor required to scale the reading on the data logging system of the analyser into reported concentration units (nmol/mol for NO, NOx, SO2, O3 and µmol/mol for CO). It should be used in conjunction with the zero response. A corrected concentration is calculated using the following equation:

³ Converter eff. is the measured efficiency of the NO₂ to NO converter within the oxides of nitrogen analyser under test.

⁴ The measured main flow rate (where this is applicable) is the flow rate through the sensor unit of the TEOM particulate analyser under test. The measured aux flow rate (where this is applicable) is the flow rate through the bypass tubing of the TEOM particulate analyser under test. The measured total flow rate is the total flow rate through the particulate analyser under test. Units of flow are l.min-1, reported at prevailing ambient conditions unless otherwise specified. Where flow rates are highlighted in bold, it indicates that measurements were not made at the analyser sample inlet. These measurements therefore may not accurately reflect analyser performance in normal operation.

⁵ The calculated ko value (specifically for TEOM analysers) is the calculated ko spring constant based on tests undertaken with filters of known weight. The % deviation indicates the closeness of the calculated result to the manufacturer's specified value of ko.