	Ricardo Energy and Environment, Gemini B Didcot, Oxfordshire OX11 0QR. Tel	uilding, Fermi Avenue Harwell, ephone 01235 753692	RICARDO
			Page 1 of 3
roved Signatories:		<ul> <li>S. Eaton</li> <li>D Hector</li> <li>N Rand</li> <li>B Davies</li> </ul>	<ul> <li>□ B Stacey</li> <li>□ S Stratton</li> <li>☑ S Telfer</li> <li>□ S Gray</li> </ul>
ed:	Stelfer		
e of issue:	27 May 20		
ificate Number:	4993		
omer Name and Ad	dress:	Scottish Government Water, Air, Soils and Flooding	ı Division
		Water, Air, Soils and Flooding Environmental Quality Director Scottish Government Victoria Quay Edinburgh EH6 6QQ	
cription:		Calibration factors for the air West Dunbartonshire Council	monitoring station(s) at
rdo Energy & Enviro	onment ID:	ED11194 / 4993	
level of confidence of app requirements. This certificate is issued in Service. It provides traces	incertainties are based on a standard uncertaint proximately 95% The uncertainty evaluation has n accordance with the laboratory accreditation ability of measurement to the SI system of units tory or other recognised national metrology inst he prior written approval of the issuing laborato	: been carried out in accordance with UKAS requirements of the United Kingdom Accredi and/or to units of measurement realised at t itutes. This certificate may not be reproduce:	tation he
	Shoreham-by-	chnical Centre	

ee.ricardo.com

1



## **CERTIFICATE OF CALIBRATION**



Page 2 of 3

Date of issue:	27 May 20	
Certificate Number:	4993	
Ricardo Energy & Environment ID:	ED11194 / 4993	

West Dunbartonshire Council

NOx analysers

Station	Date of Audit	Species	Analyser Serial no	Zero Response <sup>1</sup>	Zero uncertainty ppb	Calibration Factor <sup>2</sup>	Factor uncertainty %	Converter eff. (%) <sup>3</sup>
West Dunbartonshire Clydebank	10-Jan	NOx	19-0112	6.0	2.7	1.1232	3.50	102.0
		NO		13.0	2.6	1.1232	3.50	

PM10 analysers

Station	Date of audit	Analyser Serial no	Calculated ko	Uncertainty %	Total flow	Uncertainty %	Main flow	Uncertainty %
West Dunbartonshire Clydebank	10-Jan	6250			4.42	2.2	4.42	2.2

## PM2.5 analysers

Station	Date of audit	Analyser Serial no	Calculated ko	Uncertainty %	Total flow	Uncertainty %	Main flow	Uncertainty %
West Dunbartonshire Clydebank	10-Jan	6250			4.42	2.2	4.42	2.2

ee.**ricardo**.com



## **CERTIFICATE OF CALIBRATION**



Page 3 of 3

Date of issue:	27 May 20
Certificate Number:	4993
Ricardo Energy & Environment ID:	ED11194 / 4993

The gaseous ambient analysers listed above have been tested for zero response, calibration factor, linearity and converter efficiency (NOx analysers) by documented methods. The factors have been calculated using certified gas standards. The particulate analysers listed above have been tested for sample flow rates and ko(where appropriate) by documented methods. Note that the test results are valid on the day of test only, as analyser drift over time cannot be quantified. All results for gaseous species are given in ppb (parts per billion) mole fractions.

<sup>1</sup> The zero response is the zero reading on the data logging system of the analyser when audit zero gas was introduced to the analysers under test.

<sup>2</sup> The calibration factor is the multiplying factor required to scale the reading on the data logging system of the analyser into reported concentration units (ppb for NO, NOx, SO<sub>2</sub>, O<sub>3</sub> and ppm for CO. Where 1ppm = 1000ppb). It should be used in conjunction with the zero response. A corrected concentration is calculated using the following equation:

Concentration = F(Output - Zero Response)

Where F = Calibration Factor provided on this certificate Output = Reading on the data logging system of the analyser Zero Response = Zero Response provided on this certificate

<sup>3</sup> Converter eff. is the measured efficiency of the NO<sub>2</sub> to NO converter within the oxides of nitrogen analyser under test.

<sup>4</sup> The measured main flow rate (where this is applicable) is the flow rate through the sensor unit of the TEOM particulate analyser under test. The measured total flow rate is the total flow rate through the particulate analyser under test. Units of flow are l.min<sup>-1</sup>, reported at prevailing ambient conditions unless otherwise specified. Where flow rates are highlighted in bold, it indicates that measurements were not made at the analyser sample inlet. These measurements therefore may not accurately reflect analyser performance in normal operation.

<sup>5</sup> The calculated ko value (specifically for TEOM analysers) is the calculated ko spring constant based on tests undertaken with filters of known weight. The % deviation indicates the closeness of the calculated result to the manufacturer's specified value of ko.

The calibration results shaded are those that fall within our scope of accreditation, all other results on this certificate are not UKAS accredited, but have been included for completeness.